



# Hydromassage bathtub systems



# ***Legal Notice for Harmonized Standard Jointly Developed by ASME and CSA Group***

## **Intellectual property rights and ownership**

As between American Society of Mechanical Engineers ("ASME") and Canadian Standards Association (Operating as "CSA Group") (collectively "ASME and CSA Group") and the users of this document (whether it be in printed or electronic form), ASME and CSA Group are the joint owners of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. The unauthorized use, modification, copying, or disclosure of this document may violate laws that protect the intellectual property of ASME and CSA Group and may give rise to a right in ASME and CSA Group to seek legal redress for such use, modification, copying, or disclosure. ASME and CSA Group reserve all intellectual property rights in this document.

## **Disclaimer and exclusion of liability**

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document's fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party's intellectual property rights. ASME and CSA Group do not warrant the accuracy, completeness, or currency of any of the information published in this document. ASME and CSA Group make no representations or warranties regarding this document's compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL ASME AND CSA GROUP, THEIR RESPECTIVE VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF ASME OR CSA GROUP HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, ASME and CSA Group are not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and ASME and CSA Group accept no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

ASME and CSA Group have no power, nor do they undertake, to enforce compliance with the contents of the standards or other documents they jointly publish.

## **Authorized use of this document**

This document is being provided by ASME and CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in print or paper form may be distributed only to persons who are authorized by ASME and CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and may not permit others to

- alter this document in any way or remove this Legal Notice from the attached standard;
- sell this document without authorization from ASME and CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.



# ***Standards Update Service***

## ***ASME A112.19.7-2020/CSA B45.10:20 April 2020***

**Title:** *Hydromassage bathtub systems*

To register for e-mail notification about any updates to this publication

- go to [store.csagroup.org](https://store.csagroup.org)
- click on **Product Updates**

The **List ID** that you will need to register for updates to this publication is **2428402**.

If you require assistance, please e-mail [techsupport@csagroup.org](mailto:techsupport@csagroup.org) or call 416-747-2233.

Visit CSA Group's policy on privacy at [www.csagroup.org/legal](https://www.csagroup.org/legal) to find out how we protect your personal information.

ASMENORMDOC.COM : Click to view the full PDF of ASME A112.19.7 CSA B45.10 2020

**Canadian Standards Association (operating as “CSA Group”)**, under whose auspices this National Standard has been produced, was chartered in 1919 and accredited by the Standards Council of Canada to the National Standards system in 1973. It is a not-for-profit, nonstatutory, voluntary membership association engaged in standards development and certification activities.

CSA Group standards reflect a national consensus of producers and users — including manufacturers, consumers, retailers, unions and professional organizations, and governmental agencies. The standards are used widely by industry and commerce and often adopted by municipal, provincial, and federal governments in their regulations, particularly in the fields of health, safety, building and construction, and the environment.

Individuals, companies, and associations across Canada indicate their support for CSA Group’s standards development by volunteering their time and skills to Committee work and supporting CSA Group’s objectives through sustaining memberships. The more than 7000 committee volunteers and the 2000 sustaining memberships together form CSA Group’s total membership from which its Directors are chosen. Sustaining memberships represent a major source of income for CSA Group’s standards development activities.

CSA Group offers certification and testing services in support of and as an extension to its standards development activities. To ensure the integrity of its certification process, CSA Group regularly and continually audits and inspects products that bear the CSA Group Mark.

In addition to its head office and laboratory complex in Toronto, CSA Group has regional branch offices in major centres across Canada and inspection and testing agencies in eight countries. Since 1919, CSA Group has developed the necessary expertise to meet its corporate mission: CSA Group is an independent service organization whose mission is to provide an open and effective forum for activities facilitating the exchange of goods and services through the use of standards, certification and related services to meet national and international needs.

For further information on CSA Group services, write to  
CSA Group  
178 Rexdale Boulevard  
Toronto, Ontario, M9W 1R3  
Canada



A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at [www.scc.ca](http://www.scc.ca).

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada's economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at [www.scc.ca](http://www.scc.ca).

Standards Council of Canada  
600-55 Metcalfe Street  
Ottawa, Ontario, K1P 6L5  
Canada



**Standards Council of Canada**  
**Conseil canadien des normes**

Cette Norme Nationale du Canada n'est disponible qu'en anglais.

*Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users to judge its suitability for their particular purpose.*

*\*A trademark of the Canadian Standards Association, operating as “CSA Group”*

# ***ASME/CSA Standard***

## ***ASME A112.19.7-2020/CSA B45.10:20 Hydromassage bathtub systems***



®A trademark of the Canadian Standards Association and CSA America Inc., operating as "CSA Group"

*Published in April 2020 by CSA Group  
A not-for-profit private sector organization  
178 Rexdale Boulevard, Toronto, Ontario, Canada M9W 1R3  
1-800-463-6727 • 416-747-4044*

**Visit the CSA Group Online Store at [store.csagroup.org](https://store.csagroup.org)**

*The American Society of Mechanical Engineers (ASME)  
Two Park Avenue  
New York, NY 10016-5990, USA  
1-800-843-2763*

**Visit the ASME Online Store at [www.asme.org](https://www.asme.org)**

## Commitment for Amendments

This Standard is issued jointly by the American Society of Mechanical Engineers (ASME) and the Canadian Standards Association (Operating as “CSA Group”). Amendments to this Standard will be made only after processing according to the Standards writing procedures of both ASME and CSA Group.

The American Society of Mechanical Engineers (ASME)  
Two Park Avenue  
New York, NY 10016-5990  
USA  
1-800-843-2763  
Visit the ASME Online Store at  
[www.asme.org](http://www.asme.org)

Copyright © 2020 by The American Society of Mechanical Engineers (ASME)

This Standard is available for public review on a continuous basis. This provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public at large.

Published in April 2020 by  
CSA Group  
A not-for-profit private sector organization  
178 Rexdale Boulevard  
Toronto, Ontario, Canada  
M9W 1R3  
1-800-463-6727 or 416-747-4044  
Visit the CSA Group Online Store at  
[store.csagroup.org](http://store.csagroup.org)

ISBN 978-1-4883-2526-7  
ICS 91.140.60  
© 2020 Canadian Standards Association

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

# Contents

ASME A112 Standards Committee on Plumbing Materials and Equipment 3

ASME A112.19.7 Project Team on Whirlpool Bathtub Appliances 7

CSA Technical Committee on Plumbing Fixtures 9

CSA/ASME Joint Harmonization Task Group on Plumbing Fixtures 14

Preface 16

**1 Scope 18**

**2 Reference publications 19**

**3 Definitions and abbreviations 20**

3.1 Definitions 20

3.2 Abbreviations 21

**4 General requirements 21**

4.1 Electrical requirements 21

4.2 Plumbing fixtures 21

4.3 Plumbing supply fittings 21

4.4 Piping and tubing 22

4.4.1 Copper 22

4.4.2 Plastic 22

4.4.3 Flexible hoses 22

4.4.4 Alternative materials 22

4.5 Solvent cements for use with flexible piping 22

4.6 Suction fittings 22

4.7 Circulation system installation 22

4.8 Pump or blower 23

4.9 Field-assembled or retrofitted bathtubs 23

4.10 Backflow prevention 23

4.11 Suction fitting assemblies (whirlpool bathtubs only) 23

4.12 Suction fitting cover apertures 23

**5 Testing 23**

5.1 Installation 23

5.2 Water retention in whirlpool or air-jetted bathtubs 23

5.2.1 General 23

5.2.2 Preconditioning 24

5.2.3 Performance 24

5.2.4 Chlorine test 24

5.2.5 Volumetric test 27

5.3 Physical tests for suction fittings (whirlpool bathtubs only) 27

5.3.1 General 27

5.3.2 Test conditions 27

5.3.3	Surface evaluation	28
5.3.4	Deflection test	28
5.3.5	Shear load test	28
5.3.6	Vacuum and point impact test	29
5.4	Hair entanglement test for suction fittings	29
5.4.1	General	29
5.4.2	Test preparation	29
5.4.3	Test with the fitting affixed to the test fixture	30
5.4.4	Test with the fitting affixed to the bathtub	31

## **6 Markings and installation instructions** 32

6.1	General	32
6.2	Factory-assembled whirlpool or air-jetted bathtubs	32
6.3	Field assemblies and retrofitted bathtubs (whirlpool bathtubs only)	32
6.4	Suction fittings (whirlpool bathtubs only)	32
6.5	Installation instructions	33
6.5.1	General	33
6.5.2	Factory-assembled whirlpool or air-jetted bathtubs	33
6.5.3	Roughing-in dimensions	33
6.5.4	Service access and controls	33
6.5.5	Electrical	33
6.5.6	Operation, use, and care instructions	33
6.5.7	Flushing instructions	33

---

Annex A (informative) — Unit conversion and rounding criteria 41

Annex B (normative) — Random sampling method for testing bathtubs 42



# ASME A112 Standards Committee on Plumbing Materials and Equipment

<b>W. Smith</b>	American Society of Plumbing Engineers, Montgomery, Alabama, USA	<i>Chair</i>
<b>S. M. Rawalpindiwala</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA	<i>Vice-Chair</i>
<b>M. R. Gibeault</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA	<i>Alternate</i>
<b>R. K. Adler</b>	City of San Jose, San Jose, California, USA	
<b>J. A. Ballanco</b>	JB Engineering & Code Consulting PC, Munster, Indiana, USA	
<b>J. E. Bertrand</b>	Fortune Brands — Global Plumbing Group, North Olmsted, Ohio, USA	
<b>C. McDonald</b>	Fortune Brands — Global Plumbing Group, North Olmsted, Ohio, USA	<i>Alternate</i>
<b>T. Burger</b>	NSF International, South Euclid, Ohio, USA	
<b>R. Burnham</b>	Zurn Industries LLC, Erie, Pennsylvania, USA	
<b>M. Campos</b>	ICC Evaluation Service, LLC, Brea, California, USA	
<b>S. L. Cavanaugh</b>	Cavanaugh Consulting, Santa Fe, New Mexico, USA	<i>Contributing Member</i>
<b>W. E. Chapin</b>	Professional Code Consulting, LLC, Cullman, Alabama, USA	
<b>P. V. DeMarco</b>	IAPMO, Dayton, New Jersey, USA	

<b>N. Dickey</b>	Hansgrohe, Inc., Alpharetta, Georgia, USA	
<b>G. S. Duren</b>	Code Compliance, Inc., South Pasadena, Florida, USA	
<b>R. Emmerson</b>	Consultant, Arlington Heights, Illinois, USA	
<b>K. Ernst</b>	Oakville Stamping & Bending Limited, Oakville, Ontario, Canada	
<b>R. L. George</b>	Plumb-Tech Design and Consulting Services LLC, Newport, Michigan, USA	
<b>D. Gleiberman</b>	Sloan, Los Angeles, California, USA	
<b>J. W. Lauer</b>	Sloan, Anaheim, California, USA	<i>Alternate</i>
<b>M. Guard</b>	Bradley Corporation, Menomonee Falls, Wisconsin, USA	<i>Non-voting</i>
<b>C. Haldiman</b>	Watts Water Technologies, Springfield Falls, Michigan, USA	
<b>G. W. Harrison</b>	Consultant/Plumbing Instructor, Edmond, Oklahoma, USA	
<b>L. Himmelblau</b>	The Chicago Faucet Company, Des Plaines, Illinois, USA	
<b>C. Jahrling</b>	ASSE International, Mokena, Illinois, USA	<i>Contributing Member</i>
<b>J. Kendzel</b>	American Supply Association, Itasca, Illinois, USA	<i>Contributing Member</i>
<b>J. M. Koeller</b>	Koeller and Company, Yorba Linda, California, USA	

<b>N. M. Kummerlen</b>	Consultant, Lorain, Ohio, USA	<i>Contributing Member</i>
<b>C. J. Lagan</b>	LIXIL Water Technologies Americas, Piscataway, New Jersey, USA	
<b>M. Malatesta</b>	LIXIL Water Technologies Americas, Piscataway, New Jersey, USA	<i>Alternate</i>
<b>W. LeVan</b>	Cast Iron Soil Pipe Institute, Watersound, Florida, USA	
<b>D. Liang</b>	CSA Group, Toronto, Ontario, Canada	<i>Contributing Member</i>
<b>D. Marbry</b>	Fluidmaster Inc., San Juan Capistrano, California, USA	
<b>R. Mata</b>	American Society of Plumbing Engineers, Mentor, Ohio, USA	
<b>L. A. Mercer</b>	IAPMO, Valley City, Ohio, USA	
<b>A. I. Murra</b>	Abraham Murra Consulting, Oakville, Ontario, Canada	
<b>D. Orton</b>	NSF International, Ann Arbor, Michigan, USA	
<b>A. Ciechanowski</b>	NSF International, Ann Arbor, Michigan, USA	<i>Alternate</i>
<b>R. Pickering</b>	Eastern Research Group, Inc. (ERG), Morrisville, North Carolina, USA	<i>Contributing Member</i>
<b>L. Pilla</b>	CSA Group, Toronto, Ontario, Canada	<i>Contributing Member</i>
<b>A. Poon</b>	Delta Faucet Company, Indianapolis, Indiana, USA	

<b>B. Ramkarran</b>	Infinity Drain, LTD, Amityville, New York, USA	<i>Contributing Member</i>
<b>S. A. Remedios</b>	Remedios Consulting, London, Ontario, Canada	
<b>M. Sigler</b>	Plumbing Manufacturers International, Orlando, Florida, USA	
<b>G. L. Simmons</b>	Charlotte Pipe & Foundry, Charlotte, North Carolina, USA	
<b>W. B. Morris</b>	Charlotte Pipe & Foundry, Charlotte, North Carolina, USA	<i>Alternate</i>
<b>S. Tanner</b>	U.S. Environmental Protection Agency, Washington, District of Columbia, USA	<i>Contributing Member</i>
<b>K. Thompson</b>	IAPMO, Ontario, California, USA	
<b>J. C. Watson</b>	Elkay, Oak Brook, Illinois, USA	
<b>M. Weiss</b>	Plumbing & Drainage Institute, Polson, Montana, USA	
<b>W. C. Whitehead</b>	Whitehead Consulting Services, Peabody, Massachusetts, USA	
<b>A. Guzman Rodriguez</b>	American Society of Mechanical Engineers (ASME), New York, New York, USA	<i>Secretary</i>

# ASME A112.19.7 Project Team on Whirlpool Bathtub Appliances

<b>P. V. DeMarco</b>	IAPMO, Dayton, New Jersey, USA	<i>Vice-Chair</i>
<b>D. R. Berge</b>	5D Infusion Canada Inc., Saint-Jean-sur-Richelieu, Québec, Canada	
<b>M. Campos</b>	ICC Evaluation Service, LLC, Brea, California, USA	
<b>N. Dickey</b>	Hansgrohe, Inc., Alpharetta, Georgia, USA	
<b>F. Fernández</b>	Toto U.S.A. Inc., Ontario, California, USA	
<b>L. Gibson</b>	QAI Laboratories, Coquitlam, British Columbia, Canada	<i>Contributing Member</i>
<b>R. Guinn</b>	Consultant, Oro-Medonte, Ontario, Canada	
<b>E. Ho</b>	IAPMO Group, Markham, Ontario, Canada	
<b>D. E. Holloway</b>	IAPMO, Broken Arrow, Oklahoma, USA	
<b>C. J. Lagan</b>	LIXIL Water Technologies Americas, Piscataway, New Jersey, USA	
<b>A. I. Murra</b>	Abraham Murra Consulting, Oakville, Ontario, Canada	
<b>S. M. Rawalpindiwala</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA	
<b>M. R. Gibeault</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA	<i>Alternate</i>

**G. L. Siggins**                      UL LLC,  
Fremont, California, USA

**D. Viola**                              IAPMO,  
Mokena, Illinois, USA

*Contributing  
Member*

ASMENORMDOC.COM : Click to view the full PDF of ASME A112.19.7 CSA B45.10 2020

# CSA Technical Committee on Plumbing Fixtures

<b>S. M. Rawalpindiwala</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA <i>Category: Producer Interest</i>	<i>Chair</i>
<b>F. Lemieux</b>	Health Canada, Ottawa, Ontario, Canada <i>Category: Regulatory Authority</i>	<i>Vice-Chair</i>
<b>J. Adili</b>	UL LLC, Northbrook, Illinois, USA	<i>Non-voting</i>
<b>W. T. Ball</b>	WCM Industries Inc., Colorado Springs, Colorado, USA	<i>Non-voting</i>
<b>J. E. Bertrand</b>	Fortune Brands — Global Plumbing Group, North Olmsted, Ohio, USA <i>Category: Producer Interest</i>	
<b>J. Briggs</b>	NSF International, Ann Arbor, Michigan, USA	<i>Non-voting</i>
<b>T. Burke</b>	Victoria + Albert Baths Ltd., Telford, Shropshire, United Kingdom	<i>Non-voting</i>
<b>R. Burnham</b>	Zum Industries LLC, Erie, Pennsylvania, USA <i>Category: Producer Interest</i>	
<b>M. Campos</b>	ICC Evaluation Service, LLC, Brea, California, USA	<i>Non-voting</i>
<b>W. E. Chapin</b>	Professional Code Consulting, LLC, Cullman, Alabama, USA	<i>Non-voting</i>
<b>S. Chen</b>	Masco R&D, Taylor, Michigan, USA	<i>Non-voting</i>
<b>D. J. Compton</b>	Thetford Corporation, Ann Arbor, Michigan, USA	<i>Non-voting</i>

<b>A. De Francesca</b>	City of Toronto, Toronto, Ontario, Canada	<i>Non-voting</i>
<b>N. Dickey</b>	Hansgrohe, Inc., Alpharetta, Georgia, USA	<i>Non-voting</i>
<b>Y. Duchesne</b>	Régie du bâtiment du Québec, Québec, Québec, Canada <i>Category: Regulatory Authority</i>	
<b>K. Ernst</b>	Oakville Stamping & Bending Limited, Oakville, Ontario, Canada <i>Category: Producer Interest</i>	
<b>W. Falcomer</b>	The Corporation of the City of Ottawa, Ottawa, Ontario, Canada <i>Category: Regulatory Authority</i>	
<b>F. Fernández</b>	Toto U.S.A. Inc., Ontario, California, USA <i>Category: Producer Interest</i>	
<b>M. E. Fish</b>	Zurn Industries, LLC, Cary, North Carolina, USA	<i>Non-voting</i>
<b>M. R. Gibeault</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA	<i>Non-voting</i>
<b>D. Gleiberman</b>	Sloan, Los Angeles, California, USA	<i>Non-voting</i>
<b>D. Grenier</b>	BainUltra Inc., Lévis, Québec, Canada	<i>Non-voting</i>
<b>M. Guard</b>	Bradley Corporation, Menomonee Falls, Wisconsin, USA	<i>Non-voting</i>
<b>R. Guinn</b>	Consultant, Oro-Medonte, Ontario, Canada <i>Category: User Interest</i>	
<b>N. Haynes</b>	Region of Waterloo, Kitchener, Ontario, Canada <i>Category: User Interest</i>	



<b>L. Himmelblau</b>	The Chicago Faucet Company, Des Plaines, Illinois, USA <i>Category: Producer Interest</i>	
<b>E. Ho</b>	IAPMO Group, Markham, Ontario, Canada	<i>Non-voting</i>
<b>E. Hood</b>	H. H. Angus & Associates Limited Consulting Engineers, Toronto, Ontario, Canada <i>Category: User Interest</i>	
<b>K. S. Hui</b>	Ontario Ministry of Municipal Affairs and Housing, Toronto, Ontario, Canada <i>Category: Regulatory Authority</i>	
<b>C. Jahrling</b>	ASSE International, Mokena, Illinois, USA	<i>Non-voting</i>
<b>J. Knapton</b>	Southern Alberta Institute of Technology, Calgary, Alberta, Canada <i>Category: General Interest</i>	
<b>T. Knull</b>	Alberta Municipal Affairs, Lethbridge, Alberta, Canada <i>Category: Regulatory Authority</i>	
<b>J. M. Koeller</b>	Koeller and Company, Yorba Linda, California, USA <i>Category: General Interest</i>	
<b>C. J. Lagan</b>	LIXIL Water Technologies Americas, Piscataway, New Jersey, USA <i>Category: Producer Interest</i>	
<b>D. Liang</b>	CSA Group, Toronto, Ontario, Canada	<i>Non-voting</i>
<b>R. Liao</b>	Xiamen Lota International Co. Ltd., Xiamen, Fujian, China	<i>Non-voting</i>
<b>J. MacDonald</b>	BLANCO Canada Inc., Brampton, Ontario, Canada	<i>Non-voting</i>

<b>D. Marbry</b>	Fluidmaster Inc., San Juan Capistrano, California, USA	<i>Non-voting</i>
<b>R. Mata</b>	American Society of Plumbing Engineers, Mentor, Ohio, USA	<i>Non-voting</i>
<b>T. J. McCann</b>	Department of National Defence, Ottawa, Ontario, Canada <i>Category: User Interest</i>	
<b>C. McDonald</b>	Fortune Brands — Global Plumbing Group, North Olmsted, Ohio, USA	<i>Non-voting</i>
<b>D. McNamara</b>	Franke Kindred Canada Limited, Midland, Ontario, Canada <i>Category: Producer Interest</i>	
<b>A. I. Murra</b>	Abraham Murra Consulting, Oakville, Ontario, Canada <i>Category: General Interest</i>	
<b>R. Neff</b>	Delta Faucet Company, Indianapolis, Indiana, USA <i>Category: Producer Interest</i>	
<b>D. Orton</b>	NSF International, Ann Arbor, Michigan, USA	<i>Non-voting</i>
<b>P. Paré</b>	Masco Canada Limited, St. Thomas, Ontario, Canada	<i>Non-voting</i>
<b>R. Pickering</b>	Eastern Research Group, Inc. (ERG), Morrisville, North Carolina, USA	<i>Non-voting</i>
<b>S. A. Remedios</b>	Remedios Consulting, London, Ontario, Canada <i>Category: User Interest</i>	
<b>A. Guzman Rodriguez</b>	American Society of Mechanical Engineers (ASME), New York, New York, USA	<i>Non-voting</i>
<b>S. Rouleau</b>	Intertek, Ste-Marie, Québec, Canada	<i>Non-voting</i>

<b>S. Shang</b>	China Building Material Test & Cert. Group (Shaanxi) Co. Ltd., Shaanxi, Shanxi, China	<i>Non-voting</i>
<b>M. Sigler</b>	Plumbing Manufacturers International, Orlando, Florida, USA	<i>Non-voting</i>
<b>W. Smith</b>	American Society of Plumbing Engineers (ASPE), Montgomery, Alabama, USA <i>Category: General Interest</i>	
<b>S. Tanner</b>	U.S. Environmental Protection Agency, Washington, District of Columbia, USA <i>Category: General Interest</i>	
<b>K. Thompson</b>	IAPMO, Ontario, California, USA	<i>Non-voting</i>
<b>J. C. Watson</b>	Elkay, Oak Brook, Illinois, USA	<i>Non-voting</i>
<b>C. Wright</b>	Ontario Pipe Trades, Dundalk, Ontario, Canada <i>Category: User Interest</i>	
<b>F. Zhang</b>	China Building Material Test & Cert. Group (Shaanxi) Co. Ltd., Shaanxi, Shanxi, China	<i>Non-voting</i>
<b>J. Menard</b>	CSA Group, Toronto, Ontario, Canada	<i>Project Manager</i>
<b>L. Pilla</b>	CSA Group, Toronto, Ontario, Canada	<i>Project Manager</i>

# CSA/ASME Joint Harmonization Task Group on Plumbing Fixtures

<b>C. J. Lagan</b>	LIXIL Water Technologies Americas, Piscataway, New Jersey, USA	<i>Co-Chair</i>
<b>F. Lemieux</b>	Health Canada, Ottawa, Ontario, Canada	<i>Co-Chair</i>
<b>M. Campos</b>	ICC Evaluation Service, LLC, Brea, California, USA	
<b>I. Chang</b>	Intertek Testing Services NA Ltd., Coquitlam, British Columbia, Canada	
<b>K. Ernst</b>	Oakville Stamping & Bending Limited, Oakville, Ontario, Canada	
<b>W. Falcomer</b>	The Corporation of the City of Ottawa, Ottawa, Ontario, Canada	
<b>F. Fernández</b>	Toto U.S.A. Inc., Ontario, California, USA	
<b>R. Guinn</b>	Independent, Oro-Medonte, Ontario, Canada	
<b>L. Himmelblau</b>	The Chicago Faucet Company, Des Plaines, Illinois, USA	
<b>E. Ho</b>	IAPMO Group, Markham, Ontario, Canada	
<b>D. Liang</b>	CSA Group, Toronto, Ontario, Canada	
<b>D. McNamara</b>	Franke Kindred Canada Limited, Midland, Ontario, Canada	
<b>S. M. Rawalpindiwala</b>	Kohler Co. Plumbing Division, Kohler, Wisconsin, USA	

<b>S.A. Remedios</b>	Remedios Consulting, London, Ontario, Canada	
<b>W. Smith</b>	American Society of Plumbing Engineers (ASPE), Montgomery, Alabama, USA	
<b>C. Wright</b>	Ontario Pipe Trades, Dundalk, Ontario, Canada	
<b>J. Menard</b>	CSA Group, Toronto, Ontario, Canada	<i>Project Manager</i>
<b>L. Pilla</b>	CSA Group, Toronto, Ontario, Canada	<i>Project Manager</i>

# Preface

This is the second edition of ASME A112.19.7/CSA B45.10, *Hydromassage bathtub systems*.

It supersedes the previous edition published in 2012.

This Standard is considered suitable for use for conformity assessment within the stated scope of the Standard.

This Standard was prepared by the ASME/CSA Joint Harmonization Task Group on Plumbing Fixtures, under the jurisdiction of the ASME Standards Committee on Plumbing Materials and Equipment and the CSA Technical Committee on Plumbing Fixtures. The CSA Technical Committee operates under the jurisdiction of the CSA Strategic Steering Committee on Construction and Civil Infrastructure. This Standard has been formally approved by the ASME A112 Standards Committee and the CSA Technical Committee.

This Standard has been developed in compliance with Standards Council of Canada requirements for National Standards of Canada. It has been published as a National Standard of Canada by CSA Group.

This Standard was approved as an American National standard by the American National Standards Institute on March 5, 2020.

## ASME Notes:

- 1) *This standard was developed under procedures accredited as meeting the criteria for American National Standards and it is an American National Standard. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed Standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.*
- 2) *ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.*
- 3) *ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.*
- 4) *Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this standard.*
- 5) *ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.*
- 6) *ASME issues written replies to inquiries concerning interpretation of technical aspects of this Standard. All inquiries regarding this Standard, including requests for interpretations, should be addressed to:*  
Secretary, A112 Standards Committee  
The American Society of Mechanical Engineers  
Two Park Avenue  
New York, NY 10016-5990

*A request for interpretation should be clear and unambiguous. The request should*

- *cite the applicable edition of the Standard for which the interpretation is being requested.*
- *phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings, which are necessary to explain the question; however, they should not contain proprietary names or information.*

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee.

Interpretations are published on the ASME Web site under the Committee Pages at <https://cstools.asme.org/> as they are issued.

**CSA Notes:**

- 1) Use of the singular does not exclude the plural (and vice versa) when the sense allows.
- 2) Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users of the Standard to judge its suitability for their particular purpose.
- 3) This publication was developed by consensus, which is defined by CSA Policy governing standardization — Code of good practice for standardization as “substantial agreement. Consensus implies much more than a simple majority, but not necessarily unanimity”. It is consistent with this definition that a member may be included in the Technical Committee list and yet not be in full agreement with all clauses of this publication.
- 4) This Standard is subject to review within five years from the date of publication. Suggestions for its improvement will be referred to the appropriate committee.
- 5) To submit a request for interpretation of this Standard, please send the following information to [inquiries@csagroup.org](mailto:inquiries@csagroup.org) and include “Request for interpretation” in the subject line:
  - a) define the problem, making reference to the specific clause, and, where appropriate, include an illustrative sketch;
  - b) provide an explanation of circumstances surrounding the actual field condition; and
  - c) where possible, phrase the request in such a way that a specific “yes” or “no” answer will address the issue.

Committee interpretations are processed in accordance with the CSA Directives and guidelines governing standardization and are available on the Current Standards Activities page at [standardsactivities.csa.ca](http://standardsactivities.csa.ca).

- 6) Attention is drawn to the possibility that some of the elements of this Standard may be the subject of patent rights. CSA Group is not to be held responsible for identifying any or all such patent rights. Users of this Standard are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.

# ASME A112.19.7-2020/CSA B45.10:20

## *Hydromassage bathtub systems*

### 1 Scope

#### 1.1

This Standard specifies general requirements, test methods, and markings for whirlpool and air-jetted bathtubs and suction fittings used in hydromassage bathtub systems that incorporate a bathtub and circulation pump. The circulation pump can be with or without

- a) a piping system; and
- b) induction of air (which can be achieved by integral suction or through an air pump).

#### 1.2

This Standard does not cover

- a) spas and hot tubs covered in CAN/CSA-C22.2 No. 218.1 and UL 1563;
- b) portable hydromassage products covered in CSA Electrical Bulletin 1268 and CSA Electrical Bulletin 1270; and
- c) hydrotherapy bathtubs or patient bathing systems for institutional use.

#### 1.3

In this Standard, “shall” is used to express a requirement, i.e., a provision that the user is obliged to satisfy in order to comply with the standard; “should” is used to express a recommendation or that which is advised but not required; and “may” is used to express an option or that which is permissible within the limits of the standard.

Notes accompanying clauses do not include requirements or alternative requirements; the purpose of a note accompanying a clause is to separate from the text explanatory or informative material.

Notes to tables and figures are considered part of the table or figure and may be written as requirements.

Annexes are designated normative (mandatory) or informative (nonmandatory) to define their application.

#### 1.4

SI units are the units of record in Canada. In this Standard, the inch/pound units are shown in parentheses.

The values stated in each measurement system are equivalent in application; however, each system is to be used independently. Combining values from the two measurement systems can result in non-conformance with this Standard.

All references to gallons are to U.S. gallons.

For information on the conversion criteria used in this Standard, see Annex [A](#).



## 2 Reference publications

This Standard refers to the following publications, and where such reference is made, it shall be to the edition listed below, including all amendments published thereto.

### **ASME (The American Society of Mechanical Engineers)/CSA Group**

ASME A112.18.1-2018/CSA-B125.1-18

*Plumbing supply fittings*

ASME A112.18.2-2015/CSA-B125.2-15

*Plumbing waste fittings*

ASME A112.19.1-2018/CSA B45.2-18

*Enamelled cast iron and enamelled steel plumbing fixtures*

### **CSA Group**

B137 Series-15

*Thermoplastic pressure piping compendium*

B137.1-15

*Polyethylene (PE) pipe, tubing, and fittings for cold-water pressure services*

B137.5-15

*Crosslined polyethylene (PEX) tubing systems for pressure applications*

C22.1-18

*General requirements — Canadian Electrical Code, Part I, Safety standard for electrical installations*

CAN/CSA-C22.2 No. 218.1-13

*Spas, hot tubs, and associated equipment*

C22.2 No. 218.2-15

*Hydromassage bathtub appliances*

Electrical Bulletin No. 1268 (May 1980)

*Requirements for household, cord-connected, portable air pump hydromassage units for use with bathtubs*

Electrical Bulletin No. 1270 (May 1980)

*Requirements for household, cord-connected, portable water pump hydromassage units for use with bathtubs*

### **CSA Group/IAPMO (Canadian Standards Association/International Association of Plumbing and Mechanical Officials)**

CSA B45.5-17/IAPMO Z124-2017

*Plastic plumbing fixtures*

**ASTM International (American Society for Testing and Materials)**

D2444-17

*Standard Test Method for Determination of the Impact Resistance of Thermoplastic Pipe and Fittings by Means of a Tup (Falling Weight)*

D2564-12

*Standard Specification for Solvent Cements for Poly(Vinyl Chloride) (PVC) Plastic Piping Systems*

F876-19

*Standard Specification for Crosslinked Polyethylene (PEX) Tubing***IAPMO (International Association of Plumbing and Mechanical Officials)**

IAPMO/ANSI Z1033-2013e1

*Flexible PVC Hoses and Tubing for Pools, Hot Tubs, Spas, and Jetted Bathtubs***NFPA (National Fire Protection Association)**

70 (2017)

*National Electrical Code***UL (Underwriters Laboratories Inc.)**

1563-2009

*Standard for Electric Spas, Equipment Assemblies, and Associated Equipment*

1795-2016

*Standard for Hydromassage Bathtubs***3 Definitions and abbreviations****3.1 Definitions**

The following definitions shall apply in this Standard:

**Accessible** — accessible by removing an access panel, door, or similar obstruction, using tools.

**Circulation system** — the inlets, outlets, pumps, air induction systems, valves, piping or tubing, fittings, and other appurtenances used to circulate water from a hydromassage bathtub system.

**Note:** The circulation system can be factory or field assembled, and it can be independent or interconnected.

**Disintegrate** — to lose any material from a fitting, exclusive of plating or finish.

**Fixture** — a device that receives water, waste matter, or both and directs these substances into a drainage system.

**Hydromassage bathtub system** — a plumbing system that incorporates one or both of the following:

- a) water jets, with or without air introduced by integral suction. The water jets include a water recirculation system with self-draining piping and a water pump; and
- b) an air induction system that introduces air into the system through jets using a blower or air pump.

**Note:** A hydromassage bathtub system can be piped or unpiped (e.g., a pipeless whirlpool bathtub).

**Jet** — a fitting that creates a high-velocity stream of water with or without induction of air.

**Pipeless whirlpool bathtub** — a bathtub equipped with one or more unitized jet/suction fittings to circulate water without piping and discharge the water after each use.

**Plumbing appurtenance** — a manufactured device, prefabricated assembly, or field assembly of component parts that is an adjunct to the basic piping system and plumbing fixture.

**Note:** An appurtenance demands no additional water supply, nor does it add any discharge load to a fixture or the drainage system.

**Standard liquid detergent** — a mixture of 8.0% tetrapotassium pyrophosphate, 7.0% ethoxylated-alkyl-phenol, 8.0% sodiumxylenesulfonate, 1.5% butyl cellosolve, and 75.5% water, measured by volume.

**Note:** The following commercial products are acceptable:

- a) tetrapotassium pyrophosphate: Monsanto TKPP;
- b) ethoxylated-alkyl-phenol: Monsanto Sterox NJ or Rohm & Haas Triton X-100;
- c) sodiumxylenesulfonate: Stepan Chemical Co. Stepan SXS; and
- d) butyl cellosolve: 2-butoxy ethanol.

**Unitized jet/suction fitting** — an apparatus with a means for circulating water in a whirlpool bathtub without routing the water through the circulation system.

### 3.2 Abbreviations

The following abbreviations shall apply in this Standard:

ABS	— acrylonitrile-butadiene-styrene
CPVC	— chlorinated polyvinylchloride
GFCI	— ground fault circuit interrupter
ID	— inside diameter
OD	— outside diameter
PEX	— crosslinked polyethylene
PVC	— polyvinylchloride

## 4 General requirements

### 4.1 Electrical requirements

When tested as a full assembly, the electrical systems of hydromassage bathtubs shall comply with CSA C22.2 No. 218.2 and/or UL 1795, as appropriate.

### 4.2 Plumbing fixtures

Plastic bathtubs shall comply with CSA B45.5/IAPMO Z124. Enamelled cast iron and enamelled steel bathtubs shall comply with ASME A112.19.1/CSA B45.2.

### 4.3 Plumbing supply fittings

Plumbing supply fittings shall comply with ASME A112.18.1/CSA B125.1 and plumbing waste fittings shall comply with ASME A112.18.2/CSA B125.2.

## 4.4 Piping and tubing

### 4.4.1 Copper

Copper water tubes shall be not less than Type M.

### 4.4.2 Plastic

#### 4.4.2.1

Acrylonitrile-butadiene-styrene (ABS) and polyvinylchloride (PVC) piping and tubing may be rigid or flexible. Fittings and rigid tubing shall be at least Schedule 40.

#### 4.4.2.2

Chlorinated polyvinylchloride (CPVC) piping shall be at least SDR-PR.

#### 4.4.2.3

Crosslinked polyethylene (PEX) tubing shall comply with the dimensional tolerances specified in the appropriate PEX standard.

### 4.4.3 Flexible hoses

Flexible hoses shall comply with IAPMO/ANSI Z1033.

### 4.4.4 Alternative materials

Piping made of alternative materials shall be acceptable if it meets all of the performance requirements of this Standard.

## 4.5 Solvent cements for use with flexible piping

Solvent cements used in the assembly of the recirculation piping of hydromassage bathtubs shall

- a) be used in accordance with the solvent cement manufacturer's instructions; and
- b) be suitable for jointing flexible PVC pipe to rigid PVC fittings.

## 4.6 Suction fittings

Suction fittings shall comply with Clauses [5.3](#) and [5.4](#).

## 4.7 Circulation system installation

### 4.7.1

Rigid and flexible piping and tubing shall be installed to allow for drainage of the water from the circulation system in accordance with Clause [5.2](#). Flexible tubing shall be provided with support to reduce sagging in accordance with the tubing manufacturer's instructions.

### 4.7.2

Pumps shall be connected to the circulation system in such a way that they can be removed, repaired, or replaced.

### 4.7.3

When a self-draining volute is not provided, a means to drain the pump volute, e.g., 6.4 mm (0.24 in) ID tubing, shall be provided. The volute drain opening in a self-draining pump shall be not less than 4.8 mm (0.1875 in) ID.

### 4.7.4

The separation between multiple suction fittings shall be at least 305 mm (12 in). The fittings shall be in different planes.

### 4.7.5

The circulation system shall be watertight. Leakage from the circulation system during testing shall be cause for rejection.

## 4.8 Pump or blower

The location of the pump or blower shall be determined by the manufacturer. A means to fasten the pump or blower shall be provided.

## 4.9 Field-assembled or retrofitted bathtubs

Field-assembled or retrofitted bathtubs shall meet the requirements of this Standard.

## 4.10 Backflow prevention

Backflow prevention shall be provided in accordance with the applicable plumbing code for

- a) bathtubs with submerged inlets;
- b) potable water flush systems; or
- c) hydraulic seat lifts.

## 4.11 Suction fitting assemblies (whirlpool bathtubs only)

Suction fitting assemblies shall be designed so that tools are required for disassembly. Standard slotted screws shall not be used for affixing grates and covers to the suction fitting body.

## 4.12 Suction fitting cover apertures

Suction fitting cover apertures shall not allow the passage of a 7.87 mm (0.31 in) circular rod with an applied force of 22 N (5 lbf).

# 5 Testing

## 5.1 Installation

Hydromassage bathtub systems shall be installed in accordance with the manufacturer's instructions. When installation tolerances are specified, the hydromassage system shall be tested in the least favourable slope for drainage, but within the manufacturer's specifications.

## 5.2 Water retention in whirlpool or air-jetted bathtubs

### 5.2.1 General

Water retention in whirlpool or air-jetted bathtubs may be evaluated using the chlorine test specified in Clause [5.2.4](#) or the volumetric test specified in Clause [5.2.5](#).

### 5.2.2 Preconditioning

The specimen shall be preconditioned as follows:

- a) Fill the specimen with water at  $57 \pm 3$  °C ( $135 \pm 5$  °F) until the jets are completely covered and it can be properly operated.
- b) Circulate the water for  $2 \text{ h} \pm 10 \text{ min}$  and ensure that the water temperature is maintained at not less than  $54$  °C ( $130$  °F).
- c) Drain the specimen and allow it to cool to ambient temperature.

### 5.2.3 Performance

Hydromassage bathtubs shall not allow retention of water in excess of 44 mL (1.5 fl oz) for each jet and suction fitting. The water retention for air-jetted hydromassage bathtubs shall not exceed 400 mL (13.5 fl oz), regardless of the number of air jets. Sampling shall be performed in accordance with Annex B.

For combination whirlpool and air-jetted bathtubs, the water volumes shall be cumulative.

A whirlpool bathtub with four jets and one suction fitting shall be considered to satisfy the requirements of this Clause if the residual water does not exceed 220 mL (7.5 fl oz).

The maximum residual water in combination four jet, one suction fitting whirlpool and air-jetted bathtubs shall be 620 mL (21 fl oz).

### 5.2.4 Chlorine test

#### 5.2.4.1

The following requirements shall apply:

- a) The procedure shall be conducted within a 1 h time interval.
- b) The quality of the water used in the chlorine method shall have a total organic content no greater than 5 mg/L and a pH between 6 and 8, with the pH variation during the test no greater than  $\pm 0.1$ .
- c) The original chlorine level shall be accurately measured to within  $\pm 0.05$  mg/L, recorded, and factored out of the test reading.

#### 5.2.4.2

To prepare the chlorine solution, approximately 2% of the water in the hydromassage system shall be removed, and the chlorine compound shall be dissolved into the water removed. The quantity of chlorine compound shall be as specified in Table 1, with the concentration of the chlorine compound accurate within  $\pm 0.5\%$ . Measurement of the chlorine compound shall be within  $\pm 0.1$  g. The tester shall ensure that the compound is completely dissolved and shall carefully add the prepared solution to the hydromassage system, avoiding spillage.

#### 5.2.4.3

A cover shall be placed over the hydromassage system to prevent loss of water due to turbulence or splashing. The hydromassage system shall be run for a period of 2 min as follows:

- a) For a whirlpool system, the system shall be run for 2 min continuously.
- b) For an air bath system, the system shall be run for 30 s and allowed to settle for 30 s. This cycle shall be repeated a total of two times.

**5.2.4.4**

At the completion of the 2 min, the hydromassage system shall be shut off, and the water within the system shall be allowed to drain completely for an additional 2 min. Then, with a non-porous rubber squeegee, all the remaining water in the basin shall be scraped into the drain.

**5.2.4.5**

The hydromassage system shall be refilled with the same total volume of fresh water to the nearest  $\pm 10$  mL (0.338 oz) as determined in Clause 5.2.4.7. The procedure outlined in Clause 5.2.4.3 shall be repeated.

**5.2.4.6**

A sample of the water in the hydromassage system shall be tested for free chlorine using a suitable chlorine colorimeter. The chlorine colorimeter shall be accurate to within  $\pm 5\%$ , using the DPD (N, N-diethyl-p-phenylenediamine) indicator method. A period of more than 1 min shall not be allowed to elapse before taking the free chlorine reading. The original chlorine reading of the tap water shall be subtracted from the chlorine reading to obtain the final free chlorine concentration. The volume of water retained in the hydromassage system shall be determined by using Table 2.

**5.2.4.7**

With the drain closed, the hydromassage system shall be filled with water at  $24 \pm 3^\circ\text{C}$  ( $75 \pm 5^\circ\text{F}$ ) to a level at least 6 cm (2.4 in) above the highest jet. The quantity of water shall be measured to the nearest 10 mL (0.338 oz).

**Table 1**  
**Preparation of chlorine solution**  
(See Clause 5.2.4.2.)

Amount of water in bathtub, L	Amount of chlorine, g			
	100%	62%*	55%*	32.5%*
20	2	3.2	3.6	6.1
40	8	12.9	14.6	24.7
60	18	29.1	32.8	55.3
80	32	51.7	58.2	98.5
100	50	80.6	90.9	153.8
120	72	116.1	130.9	221.4
140	98	158.1	178.2	301.4
160	128	206.4	232.7	393.8
180	162	261.2	294.5	498.5
200	200	322.5	363.6	615.6
220	242	390.0	440.1	744.6
240	288	464.6	523.6	886.1
260	338	545.1	614.5	1039.9

(Continued)

**Table 1 (Concluded)**

<b>Amount of water in bathtub, L</b>	<b>Amount of chlorine, g</b>			
	<b>100%</b>	<b>62%*</b>	<b>55%*</b>	<b>32.5%*</b>
280	392	632.3	712.7	1206.0
300	450	725.8	818.2	1384.6
320	512	825.8	930.9	1575.5
340	578	932.2	1050.9	1778.4
360	648	1045.2	1178.2	1994.0
380	722	1164.6	1312.8	2221.6
400	800	1290.4	1454.6	2461.5

\* Where chlorine concentration is not one of the above, use the 100% column and divide by the new percentage to obtain the new mass of chlorine required.

**Table 2**  
**Residual water comparison**  
 (See Clause [5.2.4.6.](#))

<b>Chlorine reading, ppm</b>	<b>Residual water, L</b>	<b>Chlorine reading, ppm</b>	<b>Residual water, L</b>
3.0	0.568	1.5	0.284
2.9	0.549	1.4	0.265
2.8	0.530	1.3	0.246
2.7	0.511	1.2	0.227
2.6	0.492	1.1	0.208
2.5	0.473	1.0	0.189
2.4	0.454	0.9	0.170
2.3	0.435	0.8	0.151
2.2	0.416	0.7	0.132
2.1	0.397	0.6	0.114
2.0	0.379	0.5	0.095
1.9	0.360	0.4	0.076
1.8	0.341	0.3	0.057
1.7	0.322	0.2	0.038
1.6	0.303	0.1	0.019

**Note:** Where chlorinated tap water is used, the chlorination reading of the water shall be factored out of the test reading.



## 5.2.5 Volumetric test

### 5.2.5.1 Set-up

The hydromassage system shall be installed in accordance with the manufacturer's instructions. When installation tolerances are specified, the hydromassage system shall be tested in the least favourable slope for drainage, but within the manufacturer's specifications.

### 5.2.5.2 Procedure

The volumetric test shall be conducted as follows:

- a) Place a cover over the specimen to prevent loss of water due to turbulence or splashing.
- b) Operate the specimen for 2 min as follows:
  - i) whirlpool systems: 2 min continuously; or
  - ii) air-jetted systems: 30 s, followed by 30 s of non-operation to allow the water to settle. Repeat this cycle once.
- c) At the end of the 2 min period, shut off the specimen and allow the water in the specimen to drain completely for 2 min.
- d) Once the specimen is drained, tip it to empty the remaining water into a container.
- e) Push any water that still remains in the specimen into the container using a non-porous rubber squeegee.
- f) Measure the volume of water collected in the container (i.e., the retained water) to the nearest 10 mL (0.34 fl. oz).

## 5.3 Physical tests for suction fittings (whirlpool bathtubs only)

### 5.3.1 General

The physical tests for suction fittings specified in Clauses [5.3.3](#) to [5.3.5](#) shall be conducted to establish the structural performance of each model of suction fitting supplied as original equipment on a whirlpool bathtub. It shall not be necessary to conduct these tests on previously rated suction fittings.

### 5.3.2 Test conditions

#### 5.3.2.1 Laboratory room temperature

The tests shall be conducted at a laboratory room temperature of  $23 \pm 2$  °C ( $73.4 \pm 3$ °F).

#### 5.3.2.2 Conditioning

Specimens shall be submerged in water at  $23 \pm 2$  °C ( $73.4 \pm 3$ °F) for at least 2 h before testing. Testing shall be performed immediately after conditioning.

#### 5.3.2.3 Number of specimens

A minimum of six fittings shall be tested in each test. If one fitting fails the test, the test shall be repeated with six new fittings. No failures shall occur in the second set of fittings (i.e., not more than one specimen of the twelve specimens shall fail).

#### 5.3.2.4 Test fixture

The specimen shall be installed in a rigid test fixture capable of supporting the specimen in a manner similar to the actual installation.

### 5.3.2.5 Load apparatus

A point load machine capable of reading 2.3 kg (5 lb) increments and equipped with a  $51 \pm 0.8$  mm ( $2 \pm 0.03$  in) diameter steel tup with a  $51 \pm 13$  mm ( $2 \pm 0.5$  in) radius nose shall be used. The load speed shall be 5.1 to 6.4 mm/min (0.20 to 0.25 in/min).

### 5.3.3 Surface evaluation

#### 5.3.3.1 General

After each physical test in Clauses [5.3.4](#), [5.3.5](#), and [5.3.6](#), the surface shall be examined in accordance with Clause [5.3.3.2](#) and shall meet the performance requirements of Clause [5.3.3.3](#).

#### 5.3.3.2 Surface examination procedure

The surface examination shall be conducted as follows:

- Wash the specimen with a solution of standard liquid detergent and water, rinse with water, and dry.  
**Note:** To hasten drying, surfaces can be wiped with a clean chamois leather or a clean, absorbent, lint-free material.
- Rub the entire finished surface of the specimen with a sponge and a 50% solution of water and water-soluble black or blue-black ink (if the specimen is white). When inspecting specimens that are not white, use ink of an appropriate contrasting colour.
- Rinse the ink immediately from the surface with water and dry the surface before examination.
- Examine the surface of the specimen for defects and blemishes with the unaided eye from a distance of between 300 and 610 mm (1 and 2 ft) using a light source of partially diffused artificial light giving an illuminance on the surface of  $1615 \pm 540$  lx ( $150 \pm 50$  ft-candles).

**Note:** "Unaided eye" includes vision assisted by corrective lenses normally worn by the person examining the specimen.

#### 5.3.3.3 Performance

The specimen shall be free from cracks, chipped areas, and blisters. Seams, flow lines, and knit lines in the specimen shall not be considered cracks.

### 5.3.4 Deflection test

#### 5.3.4.1 Procedure

The centre of the fitting face shall be subjected to a point load of  $68 \pm 2.3$  kg ( $150 \pm 5$  lb) using the apparatus specified in Clause [5.3.2.5](#).

#### 5.3.4.2 Performance

The specimen shall not disintegrate. Deflection exceeding 8 mm (0.35 in) at the  $68 \pm 2.3$  kg ( $150 \pm 5$  lb) load shall be deemed a failure.

### 5.3.5 Shear load test

#### 5.3.5.1 General

The shear load test shall be conducted on any vertically mountable suction fitting whose horizontal edge extends perpendicularly 13 mm (0.5 in) or more from the vertical mounting plane. If the fitting has a rounded or tapered surface, the fitting shall be tested if the angle of taper is  $30^\circ$  to the vertical surface or less, regardless of the installation orientation (see Figure [1](#)).

### 5.3.5.2 Procedure

A  $46 \pm 1.5$  kg ( $100 \pm 3$  lb) load shall be applied to the specimen parallel to the mounting plane using the apparatus specified in Clause [5.3.2.5](#).

### 5.3.5.3 Performance

The grating or cover shall remain in place and the specimen shall not disintegrate.

## 5.3.6 Vacuum and point impact test

### 5.3.6.1 Procedure

The vacuum and point impact test shall be conducted as follows:

- a) Cover the specimen with a 0.51 mm (20 mil) plastic film or other suitable material.
- b) Connect the specimen outlet to a vacuum system and subject it to a 724 mm Hg (28.5 in Hg) vacuum within  $60 \pm 5$  s.
- c) Maintain the vacuum for  $5 \text{ min} \pm 10 \text{ s}$ .
- d) Remove the plastic film and the vacuum.
- e) Strike the centre of the specimen with an energy of 20 J (15 lbf-ft) in accordance with ASTM D2444, using the apparatus specified in Clause [5.3.2.5](#) and dropping the tup from a height of 0.9 m (3 ft).
- f) Repeat Items a) to d).
- g) Remove the specimen from the test fixture.

### 5.3.6.2 Performance

The grating or cover shall remain in place and the specimen shall not disintegrate.

## 5.4 Hair entanglement test for suction fittings

### 5.4.1 General

Suction fittings in whirlpool bathtubs shall be tested for hair entanglement in accordance with Clauses [5.4.2](#) to [5.4.4](#). Clause [5.4.3](#) establishes a flow rating for suction fittings and Clause [5.4.4](#) tests the suction fitting when installed in the bathtub. Sampling shall be performed in accordance with Annex [B](#).

The test shall be conducted on suction fittings supplied as original equipment on hydromassage bathtub systems. It shall not be necessary to conduct the test on suction fittings which are already in compliance with this Standard.

One fitting in the bathtub shall be selected at random and the test shall be conducted with the pump operating at its highest speed.

### 5.4.2 Test preparation

#### 5.4.2.1

The test fixture shall comprise a test tank, with baffles, a support for the pull structure, and a pull cylinder mechanism (see Figures [2](#) to [5](#)).

The test cylinder shall be affixed to the fixture as shown in Figure [6](#).

The support structure shown in Figure [4](#) shall be made of wood or similar materials to provide a rigid test apparatus.

A properly grounded pump capable of providing a flow rate at least 25% greater than the manufacturer's fitting flow rate shall be used.

A 2 hp pump has been found to be suitable for fittings up to 51 mm (2 in) in diameter. For fittings larger than 51 mm (2 in) in diameter, the manufacturer's recommended pump shall be used for testing.

## 5.4.2.2

### 5.4.2.2.1

Natural, medium to fine, straight, light-coloured human hair that weighs  $57 \pm 3$  g ( $2 \pm 0.11$  oz) and is 400 mm (16 in) long shall be affixed to a wooden dowel with a diameter of 25 mm (1 in) and a length of 300 mm (12 in). The hair shall be trimmed evenly.

A means for attaching a scale shall be provided on the opposite end of the dowel.

When tangles in the hair cannot be removed, a new sample of hair shall be used.

### 5.4.2.2.2

The following steps shall be performed:

- the hair shall be cleaned thoroughly in a 10% solution by volume of alpha olefin sulfonate and water and rinsed in clear water before use;
- the hair then shall be saturated for at least 2 min in the test tank;
- after saturation, the free end of the hair shall be placed approximately 300 mm (12 in) in front of the suction fitting and 50 mm (2 in) above the face of the fitting, as illustrated in Figure 7 a); and
- the hair shall be cleaned after every ten pulls.

### 5.4.2.3

A scale with an accuracy of 100 g (0.25 lb) shall be used to determine the pull against the entanglement.

**Note:** A Chatillon scale, model number 791-10, has been found acceptable.

## 5.4.3 Test with the fitting affixed to the test fixture

### 5.4.3.1 Procedure

The test for a fitting affixed to the test fixture shall be conducted as follows:

- Install the specimen in accordance with manufacturer's installation instructions through the side wall of the test tank, in the vertical position, and connected to a 90° elbow the same size as the fitting outlet located on the outside and as close to the fitting as possible. Attach Schedule 40 plastic pipe of the same size as the fitting socket as shown in Figure 2. The distance from the suction fitting to the first baffle should be at least 400 mm (16 in).
- Connect the pump inlet to the Schedule 40 plastic pipe (using adapters if necessary).
- Fill the test tank with water at  $32 \pm 6$  °C ( $90 \pm 10$  °F) to a depth  $300 \pm 13$  mm ( $12 \pm 0.5$  in) above the top edge of the suction cover.
- Activate the pump and regulate the flow to 38 L/min (10 gpm) less than the fitting manufacturer's recommended flow rate. If the fitting rating is not known, start the test at 95 L/min (25 gpm).
- Slowly lower the hair towards the fitting and feed the ends of the hair into the fitting in the direction of the intake flow as illustrated in Figure 7 b). Continue feeding the hair into the fitting while moving the dowel from side to side in a sweeping motion as illustrated in Figure 7 c). Reduce the magnitude of the sweeping motion with each pass of the dowel.

- f) Feed the hair into the fitting for  $35 \pm 25$  s and then hold the dowel end against the fitting for  $30 \pm 5$  s as illustrated in Figure 7 d). Release the dowel and allow it to float freely for  $30 \pm 5$  s.
- g) With the pump still operating, measure the force necessary to free the hair from the fitting using the scale specified in Clause 5.4.2.3. Attach the dowel to the scale and pull the scale and dowel in a vertical orientation, as illustrated in Figure 7 e), by activating the pneumatic hair removal mechanism.
- h) Measure and record the force of the entanglement.
- i) Repeat Items e) to h) ten times.
- j) Increase the flow rate by 19 L/min (5 gpm) increments and repeat Items e) to h) ten times at each flow rate until test failure occurs (see Clause 5.4.3.2), brushing the hair before each set of repetitions to keep it tangle free.
- k) When test failure occurs, retest the specimen using 3.8 L/min (1 gpm) increments up to the flow rate at which failure occurred to determine its best performance value.

### 5.4.3.2 Performance

The pulling force to remove the dowel test assembly shall be less than 22 N (5 lbf) when tested ten times. A pull of 22 N (5 lbf) or greater, including the weight of the saturated test apparatus, on any one of the ten pulls, shall be deemed a failure, and shall be as follows:

If one failure in ten pulls occurs, the test shall be repeated ten more times. All additional pulls shall pass before moving to the next flow rate value. The highest passing flow rate shall be divided by 1.25 to determine the maximum allowable flow rating of the fitting.

### 5.4.4 Test with the fitting affixed to the bathtub

#### 5.4.4.1 Procedure

The test for a fitting affixed to the bathtub shall be conducted as follows:

- a) Install the specimen in the bathtub in accordance with the manufacturer's instructions.
- b) Fill the bathtub to 25 mm (1 in) below the drain overflow or 6 cm (2.4 in) below the rim of the tub with water at  $32 \pm 10$  °C ( $90 \pm 50$  °F).
- c) Activate the pump and direct the flow of the jets away from the fitting.
- d) Place the free end of the hair approximately 300 mm (12 in) in front of the fitting and 50 mm (2 in) above the face of the fitting.
- e) Slowly lower the hair towards the fitting and feed the ends of the hair into the fitting in the direction of the intake flow as illustrated in Figure 7 b). Continue feeding the hair into the fitting while moving the dowel from side to side in a sweeping motion as illustrated in Figure 7 c). Reduce the magnitude of the sweeping motion with each pass of the dowel.
- f) Feed the hair into the fitting for not less than 15 s and not more than 60 s and then hold the dowel end against the fitting for  $30 \pm 5$  s as illustrated in Figure 7 d).
- g) With the pump still operating, measure the force necessary to free the hair from the fitting using the scale specified in Clause 5.4.2.3. Attach the dowel to the scale and pull the scale and dowel in a vertical orientation.
- h) Measure and record the force of the entanglement.
- i) Repeat Items d) to f) ten times.

#### 5.4.4.2 Performance

The pulling force to remove the dowel test assembly shall be less than 22 N (5 lbf) when tested ten times. A pull of 22 N (5 lbf) or greater, including the weight of the saturated test apparatus, on any one of the ten pulls, shall be deemed a failure.

For pipeless whirlpool bathtubs, the unitized jet/suction fitting shall not pull the hair into its opening holes.

## 6 Markings and installation instructions

### 6.1 General

#### 6.1.1

Factory-assembled whirlpool or air-jetted bathtubs, circulation systems, and suction fittings shall be marked with the manufacturer's name or registered trademark or, in the case of private labelling, the name of the customer for whom the fixture or device was manufactured.

#### 6.1.2

Markings shall be permanent, legible, and visible after installation.

**Note:** See Clauses [6.2](#) to [6.4](#) for additional marking requirements.

### 6.2 Factory-assembled whirlpool or air-jetted bathtubs

Factory-assembled whirlpool or air-jetted bathtubs shall have an adequately sized label that is affixed to a visible surface adjacent to the waste and overflow, is printed in 5 mm (0.2 in) high letters of a contrasting colour; and reads as follows: "Bathtub shall be tested. Fill the bathtub with water to overflow during rough inspection and inspect for leaks."

### 6.3 Field assemblies and retrofitted bathtubs (whirlpool bathtubs only)

#### 6.3.1

Piping systems that are field assembled or retrofitted shall be marked with an adequately sized label containing

- a) the circulation system manufacturer's name, address, and telephone number;
- b) the installer's name, address, and telephone number; and
- c) the date of installation.

The label shall be affixed in a location that is visible after installation.

#### 6.3.2

Assembled units shall have an adequately sized label that is affixed to a visible surface adjacent to the waste and overflow, is printed in 5 mm (0.2 in) high letters of a contrasting colour; and reads as follows: "Bathtub shall be tested. Fill the tub with water to overflow during rough inspection and inspect for leaks."

### 6.4 Suction fittings (whirlpool bathtubs only)

Suction fittings shall be marked with the model number and maximum flow rate, expressed in L/min (gpm).

## 6.5 Installation instructions

### 6.5.1 General

Installation instructions in accordance with Clauses [6.5.2](#) to [6.5.7](#) shall be provided for every hydromassage bathtub system.

### 6.5.2 Factory-assembled whirlpool or air-jetted bathtubs

Installation instructions for factory-assembled whirlpool or air-jetted bathtubs shall include warnings specifying potential dangers or damage to the bathtub during installation.

### 6.5.3 Roughing-in dimensions

Roughing-in dimensions for the water supply and drainage piping shall be provided.

### 6.5.4 Service access and controls

Service access shall be provided for pump or motor removal and the recommended minimum dimensions for access shall be specified. If the bathtub is equipped with an air volume control, the control shall be accessible to the final user.

### 6.5.5 Electrical

Information shall be provided pertaining to the safe installation of electrical components and lighting in accordance with the *Canadian Electrical Code, Part I*, or the NFPA's *National Electrical Code*. The instructions shall include a warning that the ground fault circuit interrupter (GFCI) protection needs to be installed in accordance with the applicable code.

### 6.5.6 Operation, use, and care instructions

Instructions and precautionary warnings on the operation, use, and care of the hydromassage bathtub system by the final user shall be provided.

### 6.5.7 Flushing instructions

The instructions shall contain a notice to flush the hydromassage bathtub system plumbing system periodically.

**Note:** *Flushing should be performed every 90 d.*