



ASME A17.8-2021/CSA B44.8:21
National Standard of Canada
American National Standard



Standard for wind turbine tower elevators

Click to view the full PDF of ASME A17.8 CSA B44.8 2021



Legal Notice for Harmonized Standard Jointly Developed by ASME and CSA Group

Intellectual property rights and ownership

As between The American Society of Mechanical Engineers ("ASME") and Canadian Standards Association (operating as "CSA Group") (collectively "ASME and CSA Group") and the users of this document (whether it be in printed or electronic form), ASME and CSA Group are the joint owners of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. The unauthorized use, modification, copying, or disclosure of this document may violate laws that protect the intellectual property of ASME and CSA Group and may give rise to a right in ASME and CSA Group to seek legal redress for such use, modification, copying, or disclosure. ASME and CSA Group reserve all intellectual property rights in this document.

Disclaimer and exclusion of liability

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document's fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party's intellectual property rights. ASME and CSA Group do not warrant the accuracy, completeness, or currency of any of the information published in this document. ASME and CSA Group make no representations or warranties regarding this document's compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL ASME AND CSA GROUP, THEIR RESPECTIVE VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF ASME OR CSA GROUP HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, ASME and CSA Group are not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and ASME and CSA Group accept no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

ASME and CSA Group have no power, nor do they undertake, to enforce compliance with the contents of the standards or other documents they jointly publish.

Authorized use of this document

This document is being provided by ASME and CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in print or paper form may be distributed only to persons who are authorized by ASME and CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and may not permit others to

- alter this document in any way or remove this Legal Notice from the attached standard;
- sell this document without authorization from ASME and CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.



Standards Update Service

ASME A17.8-2021/CSA B44.8:21 December 2021

Title: *Standard for wind turbine tower elevators*

To register for e-mail notification about any updates to this publication

- go to www.csagroup.org/store/
- click on **Product Updates**

The **List ID** that you will need to register for updates to this publication is **2429614**.

If you require assistance, please e-mail techsupport@csagroup.org or call 416-747-2233.

Visit CSA Group's policy on privacy at www.csagroup.org/legal to find out how we protect your personal information.

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8 2021

Canadian Standards Association (operating as “CSA Group”), under whose auspices this National Standard has been produced, was chartered in 1919 and accredited by the Standards Council of Canada to the National Standards system in 1973. It is a not-for-profit, nonstatutory, voluntary membership association engaged in standards development and certification activities.

CSA Group standards reflect a national consensus of producers and users — including manufacturers, consumers, retailers, unions and professional organizations, and governmental agencies. The standards are used widely by industry and commerce and often adopted by municipal, provincial, and federal governments in their regulations, particularly in the fields of health, safety, building and construction, and the environment.

More than 10 000 members indicate their support for CSA Group’s standards development by volunteering their time and skills to Committee work.

CSA Group offers certification and testing services in support of and as an extension to its standards development activities. To ensure the integrity of its certification process, CSA Group regularly and continually audits and inspects products that bear the CSA Group Mark.

In addition to its head office and laboratory complex in Toronto, CSA Group has regional branch offices in major centres across Canada and inspection and testing agencies in fourteen countries. Since 1919, CSA Group has developed the necessary expertise to meet its corporate mission: CSA Group is an independent service organization whose mission is to provide an open and effective forum for activities facilitating the exchange of goods and services through the use of standards, certification and related services to meet national and international needs.

For further information on CSA Group services, write to
CSA Group
178 Rexdale Boulevard
Toronto, Ontario, M9W 1R3
Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada's economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

Standards Council of Canada
600-55 Metcalfe Street
Ottawa, Ontario, K1P 6L5
Canada



Cette Norme Nationale du Canada n'est disponible qu'en anglais.

Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users to judge its suitability for their particular purpose.

**A trademark of the Canadian Standards Association, operating as “CSA Group”*

CSA Group

The Canadian Standards Association (operating as "CSA Group"), under whose auspices this National Standard has been produced, was chartered in 1919 and accredited by the Standards Council of Canada to the National Standards system in 1973. It is a not-for-profit, nonstatutory, voluntary membership association engaged in standards development and certification activities.

CSA Group standards reflect a national consensus of producers and users including manufacturers, consumers, retailers, unions and professional organizations, and governmental agencies. The standards are used widely by industry and commerce and often adopted by municipal, provincial, and federal governments in their regulations, particularly in the fields of health, safety, building and construction, and the environment.

More than 10 000 members indicate their support for CSA Group's standards development by volunteering their time and skills to Committee work.

CSA Group offers certification and testing services in support of and as an extension to its standards development activities. To ensure the integrity of its certification process, CSA Group regularly and continually audits and inspects products that bear the CSA Group Mark.

In addition to its head office and laboratory complex in Toronto, CSA Group has regional branch offices in major centres across Canada and inspection and testing agencies in fourteen countries. Since 1919, CSA Group has developed the necessary expertise to meet its corporate mission: CSA Group is an independent service organization whose mission is to provide an open and effective forum for activities facilitating the exchange of goods and services through the use of standards, certification and related services to meet national and international needs.

For further information on CSA Group services, write to
CSA Group
178 Rexdale Boulevard, Toronto, Ontario,
Canada M9W 1R3

American National Standards Institute

The American National Standards Institute (ANSI), Inc. is the nationally recognized coordinator of voluntary standards development in the United States through which voluntary organizations, representing virtually every technical discipline and every facet of trade and commerce, organized labor and consumer interests, establish and improve the some 10 000 national consensus standards currently approved as American National Standards.

ANSI provides that the interests of the public may have appropriate participation and representation in standardization activity, and cooperates with departments and agencies of U.S. Federal, state and local governments in achieving compatibility between government codes and standards and the voluntary standards of industry and commerce.

ANSI represents the interests of the United States in international nontreaty organizations such as the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC). The Institute maintains close ties with regional organizations such as the Pacific Area Standards Congress (PASC) and the Pan American Standards Commission (COPANT). As such, ANSI coordinates the activities involved in the U.S. participation in these groups.

ANSI approval of standards is intended to verify that the principles of openness and due process have been followed in the approval procedure and that a consensus of those directly and materially affected by the standards has been achieved. ANSI coordination is intended to assist the voluntary system to ensure that national standards needs are identified and met with a set of standards that are without conflict or unnecessary duplication in their requirements.

Responsibility of approving American standards rests with the
American National Standards Institute, Inc.
25 West 43rd Street, Fourth floor
New York, NY 10036

ASME/CSA Standard

ASME A17.8-2021/CSA B44.8:21 Standard for wind turbine tower elevators



®A trademark of the Canadian Standards Association and CSA America Inc., operating as "CSA Group"

*Published in December 2021 by CSA Group
A not-for-profit private sector organization
178 Rexdale Boulevard, Toronto, Ontario, Canada M9W 1R3
1-800-463-6727 • 416-747-4044*

Visit the CSA Group Online Store at www.csagroup.org/store/

*The American Society of Mechanical Engineers (ASME)
Two Park Avenue
New York, NY 10016-5990, USA
1-800-843-2763*

Visit the ASME Online Store at www.asme.org

Date of Issuance: January 28, 2022

Commitment for Amendments

This Standard is issued jointly by The American Society of Mechanical Engineers (ASME) and the Canadian Standards Association (operating as “CSA Group”). Amendments to this Standard will be made only after processing according to the Standards writing procedures of both ASME and CSA Group. The next edition of this Standard is scheduled for publication in 2026.

The American Society of Mechanical Engineers
(ASME)
Two Park Avenue
New York, NY 10016-5990 USA
www.asme.org

ISBN 978-0-7918-7439-4

© Copyright 2021

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

To purchase standards and related publications, visit ASME Online Store at www.asme.org.

This international code or standard was developed under the procedures accredited as meeting the criteria for American National Standards and it is an American National Standard. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted. The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

Published in December 2021 by CSA Group
A not-for-profit private sector organization
178 Rexdale Boulevard
Toronto, Ontario, Canada M9W 1R3
www.csagroup.org

ISBN 978-1-4883-3920-2

© 2021 CSA Group
ICS 53.020.01

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

To purchase standards and related publications, visit the CSA Group Online Store at www.csagroup.org/store/ or call toll-free 1-800-463-6727 or 416-747-4044.

Contents

ASME A17 Elevator and Escalator Standards Committee	6
CSA B44 Technical Committee on the Elevator Safety Code	8
ASME A17.8/CSA B44.8 Joint Committee on Wind Turbine Tower Elevators	13
Foreward	16
Preface	19

1 General 25

1.1	Scope	25
1.1.1	Effective date	25
1.2	Purpose and exceptions	25
1.2.1	Purpose	25
1.2.2	Exceptions to ASME A17.8/CSA B44.8	25
1.3	Definitions	25
1.4	References	33

2 Wind turbine tower elevators 35

2.1	Construction of hoistways	35
2.1.1	Hoistway enclosure not required	35
2.1.2	Enclosures required at landings	35
2.1.3	Floor over travel path not required	35
2.2	Pits	36
2.3	Location and enclosing of counterweights	36
2.3.1	Counterweight runways	36
2.3.2	Access to enclosed counterweights and ropes	36
2.4	Vertical clearances for cars and counterweights	36
2.4.1	Top car clearance (maintenance/inspection access required)	36
2.4.2	Top car clearance (maintenance/inspection access not required)	37
2.4.3	Top counterweight clearance	37
2.5	Horizontal car and counterweight clearances	37
2.5.1	Between car and landing platforms	37
2.5.2	Between car and any stationary object	37
2.5.3	Between car and counterweight and counterweight guard	37
2.5.4	Measurement of clearances	37
2.6	Protection of spaces below the travel path	37
2.7	Machinery spaces and control spaces	37
2.7.1	Equipment location	37
2.8	Equipment in the travel path, machinery space, and control spaces	38
2.8.1	Electrical equipment and wiring	38
2.9	Machinery and sheave beams, supports, and foundations	38
2.9.1	Securing of machinery beams and type of supports	38
2.9.2	Loads on overhead beams and supports	39

2.9.3	Allowable stresses and deflections for machinery and sheave beams, their supports, and any support members that transmit load to the turbine tower walls	39
2.10	Guarding of equipment and standard railing	39
2.10.1	Guarding of equipment	39
2.10.2	Standard railing	39
2.10.3	Landing platform protection	40
2.11	Protection of landing platform openings	40
2.11.1	Landing platform doors or gates	40
2.11.2	Door or gate closers	40
2.11.3	Horizontal platform inside enclosure	40
2.11.4	Platform lighting	40
2.11.5	Landing platform enclosures	40
2.12	Landing platform door and gate locking devices, electric contacts, and trapped key systems	41
2.12.1	Landing platform door and gate locking devices	41
2.12.2	Where required (for automatic call operation)	41
2.12.3	Listing/certification door locking devices and door or gate electric contacts and landing platform enclosure gate combination mechanical locks and electric contacts	41
2.12.4	General design requirements	42
2.12.5	Listing/certification door locking devices and door or gate electric contacts	43
2.13	Power operation of landing platform doors and car doors or gates	43
2.14	Car enclosures, car doors and gates, and car illumination	43
2.14.1	Car enclosure	43
2.14.2	Car height	43
2.14.3	Vision panels	44
2.14.4	Enclosure panels	44
2.14.5	Strength of car top	44
2.14.6	Top of car railing	44
2.14.7	Car illumination	44
2.14.8	Emergency lighting	44
2.14.9	Car emergency exit	45
2.14.10	Car doors and gates	45
2.14.11	Car door and gate electric contacts	45
2.14.12	Clear openings	46
2.14.13	Sectioning	46
2.14.14	Ventilation	46
2.15	Car frames and platforms	46
2.15.1	Car frames and floors	46
2.15.2	Use of cast iron	46
2.15.3	Number of compartments	46
2.15.4	Guiding means	46
2.15.5	Strength of guiding means	46
2.15.6	Car frame	47
2.15.7	Guiding members	47
2.15.8	Kickboard	47
2.15.9	Obstruction-detection devices	47
2.15.10	Warning devices	47
2.15.11	Ladder-guided platforms	48
2.16	Capacity and loading	48

2.16.1	Capacity and data plates	48
2.16.2	Information required on plates	48
2.16.3	Limitation of load, speed, and platform area	48
2.16.4	Overload detection means	48
2.16.5	Speed-limiting device	48
2.17	Car and counterweight safeties	48
2.17.1	Wire rope gripping safety	49
2.17.2	Rack-and-pinion safety	49
2.17.3	Safety marking plates	50
2.17.4	Opening of driving-machine motor and brake control circuits on safety application	50
2.17.5	Application of safety	50
2.18	Reserved for future use	50
2.19	Reserved for future use	50
2.20	Suspension means and their connections	50
2.20.1	Suspension means for counterweighted traction elevators	51
2.20.2	Suspension means for uncounterweighted traction elevators	51
2.20.4	Replacement of suspension means	53
2.21	Counterweights	53
2.21.1	Counterweight guides	53
2.21.2	Types of counterweight construction	53
2.22	Buffers, bumpers, and retardations	53
2.22.1	Bumpers	54
2.22.2	Spring buffers	54
2.22.3	Retardations	54
2.23	Car and counterweight guidance systems, supports, and fastenings	54
2.23.1	Wire rope guidance system for uncounterweighted traction drive machines	54
2.23.2	Ladder guidance systems	56
2.24	Driving machines, sheaves, and brakes	57
2.24.1	Rack-and-pinion driving machines	57
2.24.2	Traction driving machines, sheave and brakes	58
2.24.3	Material and grooving for sheaves	59
2.24.4	Factor of safety for driving machines and sheaves	59
2.24.5	Bolts transmitting torque and set screws	59
2.24.6	Friction-gearing or clutch mechanism	59
2.24.7	Use of cast iron in gears	59
2.24.8	Braking system of driving machines	59
2.24.9	Means for manual release of driving machine brake	60
2.25	Terminal stopping devices	60
2.25.1	Final terminal stopping	60
2.25.2	Normal terminal stopping	61
2.25.3	Slack rope detection	62
2.26	Operating devices and control equipment	62
2.26.1	Operation and operating devices	62
2.26.2	Electrical protective devices	62
2.26.3	Contactors and relays for use in critical operating circuits	63
2.26.4	Electrical equipment and wiring	63
2.26.5	Phase protection of motors	64
2.26.6	Installation of capacitors or other devices to make electrical protective devices ineffective	64
2.26.7	Control and operating circuits	64

2.26.8	Release and application of driving-machine brakes	65
2.27	Emergency operation and signaling devices	66
2.28	Layout drawings	66
2.29	Welding	66
2.29.1	Qualification of welders	66
2.29.2	Welding steel	66
2.29.3	Welding metals other than steel	66
2.30	Engineering tests, type tests, and certification requirements	67
2.30.1	General requirements for tests and certifications	67
2.30.2	Type tests of interlocks, combination mechanical locks and electric contacts, and door or gate electric contacts	68
2.30.3	General requirements	69
2.30.4	Required tests and procedure	69
2.31	Code data plate	71
2.31.1	Required information	71
2.31.2	Location	71
2.31.3	Material and construction	71

3	Maintenance, repair, replacement, testing, and alterations	72
3.1	Maintenance	72
3.1.1	General maintenance requirements	72
3.1.2	Maintenance personnel	73
3.1.3	Maintenance records	73
3.1.4	Code data plate	74
3.1.5	General maintenance methods and procedures	74
3.1.6	Periodic tests	75
3.2	General repair requirements	76
3.2.1	Applicable codes	76
3.2.2	Welding and design	76
3.2.3	Repair of suspension, guide, and safety ropes	76
3.2.4	Repair of safety	76
3.3	General replacement requirements	76
3.3.1	Replacement parts	76
3.3.2	Replacement suspension, guide, and safety rope	76
3.3.3	Replacement of car or counterweight safety	77
3.3.4	Replacement of driving machine	77
3.3.5	Replacement of controller	77
3.3.6	Listed/certified devices	77
3.4	Maintenance and testing of wind turbine tower elevators	77
3.4.1	Suspension means	77
3.4.2	Wire rope gripping safeties	78
3.4.3	Brakes	78
3.4.4	Car and counterweight safeties	78
3.4.5	Tests without load via alternative test methodologies	79
3.5	Alterations	80
3.5.1	Applicability of alteration requirements	80
3.5.2	Items not covered in 3.5	80
3.5.3	Testing	80
3.5.4	Welding	80

3.5.5	Design	80
3.5.6	Temporary wiring	80
3.5.7	Repairs and replacements	80
3.5.8	Code data plate	80
3.5.9	Location and guarding of counterweights	80
3.5.10	Vertical car and counterweights clearances and runbys	80
3.5.11	Horizontal car and counterweight clearances	80
3.5.12	Machinery spaces, and control spaces	80
3.5.13	Machinery and shave beams, and supports	81
3.5.14	Platform door locking devices	81
3.5.15	Car enclosures, car doors and gates, and car illumination	81
3.5.16	Car frames and platforms	81
3.5.17	Change in rated speed	81
3.5.18	Driving machines and sheaves	82
3.5.19	Controllers	82
3.5.20	Car and counterweight safeties	82
3.6	Acceptance inspections and tests	82
3.6.1	General requirements for acceptance inspections and tests	83
3.6.2	Acceptance inspections and tests	84
3.6.3	Inspection and test requirements for altered installations	87
3.7	Periodic inspections and witnessing of tests	87
3.7.1	General requirements for periodic inspections and witnessing of tests	87
3.7.2	Periodic inspection requirements	89
3.7.3	Periodic test requirements — Category 1	91
3.7.4	Periodic test requirements — Category 5	91
3.7.5	Category 5 tests without load via alternative test methodologies	92
Annex A (informative) — Wind turbine tower elevator clearances		94
Annex B (informative) — Maintenance control program records		95
Annex C (informative) — Acceptance tests		97

(ED) ***ASME A17 Elevator and Escalator
Standards Committee***

H.E. Peelle III, *Chair*

R. E. Baxter, *Vice-Chair*

M. H. Tevyaw, *Vice-Chair*

G.A. Burdeshaw, *Secretary*

E.V. Baker, IUEC

M.D. Morand, *Alternate*, Qualified Elevator Inspector Training Fund (QEITF)

R.E. Baxter, Baxter Residential Elevators, LLC

P. R. Bothwell, EHC Global Inc.

K.L. Brinkman, National Elevator Industry, Inc.

R. C. Burch, VANTAGE / GAL Manufacturing Company, LLC

G.A. Burdeshaw, American Society of Mechanical Engineers (ASME)

J.W. Coaker, Coaker & Co., PC

J. Filippone, Vertical Transportation Consultant

R. Gregory, Vertex Corp.

P. Rosenberg, *Alternate*, Performance Elevator Consulting, LLC

P. Hampton, Thyssenkrupp Elevator US Manufacturing Headquarters

J. D. Henderson, *Alternate*, Thyssenkrupp Elevator US Manufacturing Headquarters

J.T. Herrity, Department of the Navy, Naval Facilities Command (NAVFAC)

D.A. Kalgren, KONE Inc.

D.S. Boucher, *Alternate*, KONE Inc.

J. Koshak, Elevator Safety Solutions, LLC

H. Simpkins, *Alternate*, Thyssenkrupp Elevator

R. Kremer, Technical Standards & Safety Authority

D. McColl, Otis Canada Inc.

D. McLellan, Technical Standards & Safety Authority

A. L. Peck, VDA Consultants

H. M. Vyas, *Alternate*, vda® Thevda- Leader in Delivering Vertical Transportation Consulting

H.E. Peelle III, The Peelle Company Ltd.

S.P. Reynolds, *Alternate*, The Peelle Company Ltd.

D. Prince, Motion Control Engineering

J. Rearick, Rearick & Company Inc.

V. Robibero, RobiberoV Consultancy LLC

J. W. Blain, *Alternate*, Edgett Williams Consulting Group

R. Seymour, Robert L. Seymour & Associates, Inc.

R. D. Shepherd, Retired

J. Day, *Alternate*, NAESA International

W. M. Snyder, VTE Solution, LLC

M. H. Tevyaw, MHT Codes & Consulting

D. L. Turner, Davis L Turner & Assoc., LLC

M. Farinola, *Alternate*, MV Farinola Inc.

J. Xue, *Delegate*, Shanghai Institute of Special Equipment Inspection and Technical Research

(ED) ***CSA B44 Technical Committee on the Elevator Safety Code***

D. McColl	Otis Canada Inc., Mississauga, Ontario, Canada <i>Category: Producer Interest</i>	<i>Chair</i>
C. M. Ayling	PCL Constructors Canada Inc., Mississauga, Ontario, Canada <i>Category: User/General Interest</i>	
T. Baik	Toronto Transit Commission, Toronto, Ontario, Canada	<i>Non-voting</i>
L. Bialy	Louis Bialy and Associates LLC, San Rafael, California, USA	<i>Non-voting</i>
S. Bornstein	KONE Elevators, Mississauga, Ontario, Canada <i>Category: Producer Interest</i>	
M. Brierley	Coldwater, Ontario, Canada	<i>Non-voting</i>
K. L. Brinkman	National Elevator Industry, Inc., Eureka, Illinois, USA	<i>Non-voting</i>
D. Bruce	Alberta Municipal Affairs, Edmonton, Alberta, Canada <i>Category: Regulatory Authority</i>	
E. Chayer	STM, Montréal, Québec, Canada <i>Category: User/General Interest</i>	
K. C. Cheong	MKC Engineering Corp, Vancouver, British Columbia, Canada <i>Category: User/General Interest</i>	
C. Cowen	Tyssenkrupp Elevator (Canada) Limited, Toronto, Ontario, Canada <i>Category: Producer Interest</i>	

K. Duncan	Inspection and Technical Services, Winnipeg, Manitoba, Canada <i>Category: Regulatory Authority</i>	
T. Evans	Underwriters Laboratories Inc., Toronto, Ontario, Canada	<i>Non-voting</i>
P. Fraser	Government of Newfoundland & Labrador/ Service NL, Mount Pearl, Newfoundland and Labrador, Canada <i>Category: Regulatory Authority</i>	
A. Ghazanchaei	Otis Canada, Inc., Mississauga, Ontario, Canada	<i>Non-voting</i>
G. W. Gibson	George W. Gibson & Associates Inc., Sedona, Arizona, USA	<i>Non-voting</i>
S. Gurumurthy	KONE Inc., Canada, Mississauga, Ontario, Canada	<i>Non-voting</i>
A. S. Hopkirk	Trident Elevator Company Limited, Scarborough, Ontario, Canada <i>Category: User/General Interest</i>	
R. Isabelle	KJA Consultants Inc., Toronto, Ontario, Canada <i>Category: User/General Interest</i>	
F. Kassem	ThyssenKrupp Elevator Canada, Montréal, Québec, Canada	<i>Non-voting</i>
J. W. Koshak	Elevator Safety Solutions, LLC, Collierville, Tennessee, USA	<i>Non-voting</i>
R. Kremer	Technical Standards & Safety Authority, Toronto, Ontario, Canada	<i>Non-voting</i>
D. Laguerre	Schindler Elevator Corporation, Toronto, Ontario, Canada <i>Category: Producer Interest</i>	
D. Lenardis	Public Service Procurement Canada, Ottawa, Ontario, Canada	<i>Non-voting</i>

S. MacArthur	OTIS, Ottawa, Ontario, Canada	<i>Non-voting</i>
S. E. MacArthur	Department of Community and Cultural Affairs and Labour, Charlottetown, Prince Edward Island, Canada <i>Category: Regulatory Authority</i>	
R. Marsiglio	H. H. Angus & Associates Ltd, Toronto, Ontario, Canada <i>Category: User/General Interest</i>	
P. McClare	Dept of Labour and Advanced Education, Dartmouth, Nova Scotia, Canada <i>Category: Regulatory Authority</i>	
E. McClaskey	International Union of Elevator Constructors, Pleasant Hill, California, USA <i>Category: User/General Interest</i>	
K. L. McGettigan	Elevator Industry Work Preservation Fund, Effingham, New Hampshire, USA <i>Category: User/General Interest</i>	
A. McGregor	Rooney, Irving & Associates Ltd., Ottawa, Ontario, Canada	<i>Non-voting</i>
C. McIntyre	Canadian Elevator Industry Educational Program, Pickering, Ontario, Canada	<i>Non-voting</i>
D. McLellan	Technical Standards & Safety Authority (TSSA), Toronto, Ontario, Canada <i>Category: Regulatory Authority</i>	
M. Mihai	Technical Standards & Safety Authority (TSSA), Toronto, Ontario, Canada	<i>Non-voting</i>
T. Miller	Priestman Neilson & Associates Ltd, Ottawa, Ontario, Canada <i>Category: User/General Interest</i>	
R. Murphy	Garaventa Canada Ltd, Surrey, British Columbia, Canada <i>Category: Producer Interest</i>	

S. Palko	Regina, Saskatchewan, Canada	<i>Non-voting</i>
M. Pedram	Modern Elevator Innovations Inc., Hamilton, Ontario, Canada <i>Category: Producer Interest</i>	
H. Peelle	The Peelle Company Limited, Brampton, Ontario, Canada <i>Category: Producer Interest</i>	
B. Potvin	National Research Council - Codes Canada, Ottawa, Ontario, Canada <i>Category: User/General Interest</i>	
A. Rehman	Schindler Elevator Corporation, Morristown, New Jersey, USA	<i>Non-voting</i>
A. Reistetter	National Elevator & Escalator Association, Mississauga, Ontario, Canada	<i>Non-voting</i>
S. Reynolds	The Peelle Company Limited, Brampton, Ontario, Canada	<i>Non-voting</i>
E. Ryba	Public Services and Procurement Canada, Ottawa, Ontario, Canada <i>Category: User/General Interest</i>	
R. Santos	Technical Safety Authority of Saskatchewan (TSASK), Regina, Saskatchewan, Canada <i>Category: Regulatory Authority</i>	
R. Scharfe	Pembroke, Ontario, Canada	<i>Non-voting</i>
P. Sorensen	Technical Safety BC, Vancouver, British Columbia, Canada	<i>Non-voting</i>
K. Steeves	Province of New Brunswick Department of Public Safety, Moncton, New Brunswick, Canada <i>Category: Regulatory Authority</i>	
M. Tevyaw	MHT Codes & Consulting Specialists, Burlington, Ontario, Canada	<i>Non-voting</i>

T. Thomas	Government of the Northwest Territories, Yellowknife, NWT, Canada <i>Category: Regulatory Authority</i>	
E. Towson	Technical Safety BC, West Kelowna, British Columbia, Canada <i>Category: Regulatory Authority</i>	
K. Virk	UT Elevator Inc., Toronto, Ontario, Canada	<i>Non-voting</i>
J. Virk	Unitech Elevator Company, Pickering, Ontario, Canada	<i>Non-voting</i>
B. Virk	UT Elevator, Toronto, Ontario, Canada <i>Category: Producer Interest</i>	
L. Yang	CSA Group, Toronto, Ontario, Canada	<i>Non-voting</i>
M. Zingarelli	MAD-Elevator Inc., Mississauga, Ontario, Canada	<i>Non-voting</i>
J. Menard	CSA Group, Toronto, Ontario, Canada	<i>Project Manager</i>

(ED) ***ASME A17.8/CSA B44.8 Joint Committee on
Wind Turbine Tower Elevators***

R. S. Hultstrom	Industry Work Preservation Fund, Columbia, Maryland, USA	<i>Chair</i>
J. Koshak	Elevator Safety Solutions, LLC, Germantown, Tennessee, USA	<i>Vice-Chair</i>
R. Mohamed	American Society of Mechanical Engineers (ASME), New York, New York, USA	<i>Secretary</i>
C. Barrett	Elevator Industry Work Preservation Fund, Kent, Washington, USA	
J.L. Borwey	NAESA International, Mankato, Minnesota, USA	
G. Brickell	Brickell Technology, Auckland, New Zealand	<i>Contributing Member</i>
C.E. Cuenin	Cuenin Elevator Corporation, Grand Ridge, Florida, USA	<i>Alternate</i>
T. Daqoune	ENERCON Canada Inc., Montreal, Quebec, Canada	
K. Govaert	Sky Man International NV, Boom, Belgium	<i>Contributing Member</i>
P.S. Grewal	Hailo LLC, Elberton, Georgia, USA	<i>Contributing Member</i>
R.J. Gromek	Bechtel National Inc., Richland, Washington, USA	<i>Contributing Member</i>
P. Gulletson	CSA Group, Toronto, Ontario, Canada	
J.J. Haigh	SafeWorks, LLC, Menomonee Falls, Wisconsin, USA	

J.T. Herrity	Department of the Navy, Naval Facilities Command (NAVFAC), Fleming Island, Florida, USA	<i>Contributing Member</i>
G. G. Johnston	Universal Builders Supply, Montross, Virginia, USA	
R. Kaspersma	KONE Den Haag, The Hague, Netherlands	<i>Contributing Member</i>
K. Matharu	Tractel, Scarborough, Ontario, Canada	<i>Contributing Member</i>
G. S. McDonald	Safeworks, Tukwila, Washington, USA	<i>Alternate</i>
L. Metzinger	Avanti Wind Systems Inc., Franklin, Wisconsin, USA	
J. Rearick	Rearick & Company Inc., Houston, Texas, USA	
P.D. Smith	Tempest Group, Grand Ridge, Florida, USA	
S. Strawn	Elevator Safety and Technical Services, Tallahassee, Florida, USA	
S. Swett	SwettCorp, Houston, Texas, USA	
D. Swett	Swett & Associates, Houston, Texas, USA	<i>Alternate</i>
G. Vanderploeg	Select Elevator Solutions Inc., London, Ontario, Canada	
S.W. Weaver	Consultant, Amarillo, Texas, USA	<i>Contributing Member</i>

L. Yang CSA Group,
Toronto, Ontario, Canada

J. Menard CSA Group,
Toronto, Ontario, Canada

Project Manager

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8 2021

(ED) **Foreword**

Equipment covered by this standard was originally codified and incorporated into ASME A17.1-2013/CSA B44-13, Section 5.11, in October 2013. The first edition of this Standard was published in November 2016 and prepared by The American Society of Mechanical Engineers (ASME), Wind Turbine Tower Elevator Committee with the assistance of representatives of a number of interests including manufacturers, certifying organizations, regulatory bodies, and technical consultants from North America and Europe.

The work to develop this Standard originated when the A17 Standards Committee was presented information on the numbers of these elevators already installed and the estimate of projected number of elevators to be constructed in North America.

The A17 Standards Committee voted that these elevators were under the Scope of ASME A17.1/CSA B44, Safety Code for Elevators and Escalators and in January 2009, assigned the project of developing language to the Special Purpose Personnel Elevator (SPPE) Committee. The SPPE Committee created a Project Team consisting of A17/B44 representatives, technical advisors from the American Wind Energy Association (AWEA), specialists in the design of these types of elevators, manufacturers from Denmark, Belgium, Spain, and Canada, and two members from Accredited Elevator/Escalator Certifying Organizations (AECOs) from the Netherlands and the United States.

The first Project Team meeting was held in March 2009. A number of meetings of the Team were held during the next three years, using the Special Purpose Personnel Elevator language, Section 5.7, as a basis for developing Wind Turbine Elevator Code language. The Team performed hazard assessment to establish equivalent levels of safety considering the very unique environment these elevators are installed where current ASME A17.1/CSA B44 codes do not address specific circumstances and structural requirements. In 2012, the Project Team was converted to a full Working Committee of A17, and the ASME A17.1/CSA B44, Section 5.11 was completed, approved by ANSI, and published as an American National Standard, ASME A17.1-2013/CSA B44-13. In 2013, the A17 Standards Committee approved the conversion of Section 5.11 into ASME A17.8/CSA B44.8 to provide a global code to international manufacturers in an effort to harmonize worldwide construction, installation, operation, testing, inspection, maintenance, alteration, and repair requirements.

ASME A17.8-2016/CSA B44.8-16 was approved as an American National Standard by the American National Standards Institute (ANSI) on January 8, 2016.

The second edition of ASME A17.8-2021/CSA B44.8:21 includes revisions listed in the summary of changes section. This edition adds requirements for engineering tests, type tests, and certifications; maintenance, repair, replacements, testing, and alterations; as well as suspension means and their connections. These additions were to create a document not dependent on ASME A17.1/CSA B44, but separate their unique requirements into a separate standard. This 2021 edition is also being changed from periodic maintenance to a five-year cycle continuous maintenance publication. This Standard was approved as an American National Standard by the American National Standards Institute (ANSI) on October 27, 2021.

Correspondence with the A17 Committee

General

This Standard is one of numerous codes and standards developed and published by The American Society of Mechanical Engineers (ASME) under the general auspices of the American National Standards Institute (ANSI).

ASME codes and standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this and other ASME A17 codes and standards may interact with the committee by requesting interpretations, proposing revisions, and attending committee meetings. Correspondence should be addressed to:

Secretary, A17 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016

All correspondence to the Committee must include the individual's name and post office address in case the Committee needs to request further information.

Proposing Revisions

Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the procedures, and in order to conform to developments in the elevator art. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible: citing the Section number(s), the proposed wording, and a detailed description of the reasons for the proposal including any pertinent documentation.

Requesting Interpretations

Upon request, the A17 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the A17 Standards Committee at: <http://go.asme.org/Inquiry>.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his request utilizing the following format:

Subject: Cite the applicable Section number(s) and a concise description.

Edition: Cite the applicable edition and supplement of the Standard for which the interpretation is being requested.

Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The question shall be phrased, where possible, to permit a specific "yes" or "no" answer. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format will be rewritten in this format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

Moreover, ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Code requirements. If, based on the inquiry information submitted, it is the opinion of the Committee that the Inquirer should seek assistance, the inquiry will be returned with the recommendation that such assistance be obtained.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME committee or subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings

The A17 Standards Committee and the various Working Committees regularly hold meetings and/or telephone conferences all of which are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the Standards Committee. Future committee meeting dates and locations can be found on the committee page at <https://cstools.asme.org/>.

ASME A17.8-2021/CSA B44.8:21

Click to view the full PDF of ASME A17.8-2021/CSA B44.8:21

Preface

This is the second edition of ASME A17.8/CSA B44.8, *Standard for wind turbine tower elevators*. It supersedes the previous edition published in 2016.

Originally, wind turbine tower elevators were covered in ASME A17.1-2013/CSA B44-13, Section 5.11, published in October 2013. This Standard supersedes those requirements. This is a fully harmonized binational Standard.

This Standard was prepared for use in Canada by the CSA Technical Committee on the Elevator Safety Code under the jurisdiction of the CSA Strategic Steering Committee on Mechanical Industrial Equipment Safety, and has been formally approved by the CSA Technical Committee.

This standard has been developed in compliance with Standards Council of Canada requirements for National Standards of Canada. It has been published as a National Standard of Canada by CSA Group.

Notes:

- 1) *Use of the singular does not exclude the plural (and vice versa) when the sense allows.*
- 2) *Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users of the Standard to judge its suitability for their particular purpose.*
- 3) *This publication was developed by consensus, which is defined by CSA Policy governing standardization — Code of good practice for standardization as "substantial agreement. Consensus implies much more than a simple majority, but not necessarily unanimity". It is consistent with this definition that a member may be included in the Technical Committee list and yet not be in full agreement with all clauses of this publication.*
- 4) *To submit a request for interpretation of this Standard, please send the following information to inquiries@csagroup.org and include "Request for interpretation" in the subject line:*
 - a) *define the problem, making reference to the specific clause, and, where appropriate, include an illustrative sketch;*
 - b) *provide an explanation of circumstances surrounding the actual field condition; and*
 - c) *where possible, phrase the request in such a way that a specific "yes" or "no" answer will address the issue.*

Committee interpretations are processed in accordance with the CSA Directives and guidelines governing standardization and are available on the Current Standards Activities page at standardsactivities.csa.ca.

- 5) *This Standard is subject to review five years from the date of publication. Suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include "Proposal for change" in the subject line:*
 - a) *designation;*
 - b) *relevant clause, table, and/or figure number;*
 - c) *wording of the proposed change; and*
 - d) *rationale for the change.*
- 6) *Attention is drawn to the possibility that some of the elements of this Standard may be the subject of patent rights. CSA Group is not to be held responsible for identifying any or all such patent rights. Users of this Standard are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.*

Summary of Changes

Following approval by the ASME A17 Elevator and Escalator Committee and ASME, and after public review, ASME A17.8-2021/CSA B44.8:21 was approved by the American National Standards Institute on October 27, 2021.

The 2021 edition of ASME A17.8/CSA B44.8 includes revisions that are identified by a margin note, **(21)**.

Changes made to correct errors, as well as other editorial changes, are identified by **(ED)**. The following is a summary of the latest revisions and changes:

Page	Location	Change
1–5	Contents	Revised
6–15	Committee Rosters	Updated
16	ASME Foreword	Updated
25–35	Part 1 , Scope, Definitions, and References	Title Revised
25	1.1.1	Editorially revised, “code” revised to “standard” throughout document
25	1.2	Added
	1.2, 1.3	Redesignated to 1.3 , 1.4
25–33	1.3 Definitions	“Accredited certifying organization” Added
		“Accrediting body” Added
		“Alteration” Added
		“Approved” Added
		“Authority having jurisdiction” Added
		“Brake, driving machine, elevator dumbwaiter, or material lift” Revised
		“Car door or gate electric contact” Added
		“Clearance, top car, inclined elevators” Revised
		“Control, AC motor” Added
		“Control, two speed AC” Added
		“Operation, automatic” Revised
		“Control system” Added
		“Controller, motion” Added
		“Door or gate closer” Added
		“Elevator personnel” Revised
		“Emergency personnel” Added

Page	Location	Change
		"Emergency stop switch" Revised
		"Fail safe" Added
		"Guiding means, ladder" Added
		"Hard copy" Added
		"Hoistway (shaft), elevator, dumbwaiter, or material lift" Revised
		"Hoistway gate separate mechanical lock" Revised
		"Installation" Revised
		"Landing, elevator or material lift" Revised
		"Landing, bottom terminal" Deleted
		"Landing, top terminal" Deleted
		"Landing, terminal" Deleted
		"Maintenance control program (MCP)" Revised
		"Maintenance interval" Added
		"Maintenance task" Added
		"Mechanical lock" Revised
		"Periodic tests, category" Added
		"Rated load, elevator, dumbwaiter, material lift, or escalator" Revised
		"Rated speed" Revised
		"Elevator, dumbwaiter, or material lift" Revised
		"Regulatory authority" Added
		"Residual strength" Added
		"Rise" Added
		"Rope, suspension (hoisting)" Revised
		"Sound engineering practice" Added
		"Terminal stopping device, normal" Revised
		"Trailing Cable" Added
		"Travelling Cable" Revised
33–35	1.4	Revised
35	2.1.3.2	Revised
37	2.5	Revised
37	2.7	Title Revised
38	2.7.1.1	Revised

Page	Location	Change
38	2.9	Revised
38	2.9.1.5	Added
39	2.9.2	Revised
39	2.9.3	Deleted
	2.9.4	Redesignated
	2.9.4.1	Redesignated
	2.9.4.2	Redesignated
39	2.10.1	Revised
40	2.11	Revised
41	2.12	Title Revised
41	2.12.1	Revised
41	2.12.2	Revised
41	2.12.3	Revised
41	2.12.3.1	Revised
42	2.12.3.2	Revised
42	2.12.3.3	Revised
	2.12.3.5.1	Redesignated and Revised
	2.12.3.5.2	Redesignated and Revised
	2.12.3.5.3	Redesignated and Revised
42	2.12.4	Added
44	2.14.8.3	Deleted
	2.14.8.4	Redesignated
45	2.14.9.2	Revised
45	2.14.9.3	Revised
46	2.14.12	Revised
46	2.14.13	Revised
46	2.15	Revised
46	2.15.1	Revised
47	2.15.8	Revised
47	2.15.10.1	Revised
47	2.15.10.2	Revised
39	2.15.11	Revised
48	2.16.4	Revised
49	2.17.1.1	Revised
50	2.20	Revised

Page	Location	Change
51	2.20.1	Revised
51	2.20.1.1	Revised
51	2.20.1.2	Revised
51	2.20.1.3	Revised
51	2.20.2	Revised
51	2.20.2.1	Revised
51	2.20.2.2	Revised
51	2.20.2.3	Revised
51	2.20.2.5	Revised
52	2.20.2.9	Revised
52	2.20.2.10	Revised
	2.20.2.11	Redesignated and Revised
53	2.20.2.12	Revised
	2.20.2.13	Redesignated
	2.20.3	New Para. Added, Revised, and Redesignated
53	2.21	Revised
54	2.23.1	Revised
54	2.23.1.1	Revised
54	2.23.1.3	Revised
55	2.23.1.6	Revised
55	2.23.1.9	Revised
55	2.23.1.12	Added
56	2.23.2	Revised
56	2.23.2.3	Revised
56	2.23.2.9	Added
57	2.24	Revised
	2.24.3	Deleted
	2.24.4	Redesignated
	2.24.4.1	Redesignated
	2.24.5	Redesignated
	2.24.6	Redesignated and Revised
	2.24.7	Redesignated
	2.24.8	Redesignated
	2.24.9	Redesignated and Revised
	2.24.9.1	Redesignated

Page	Location	Change
	2.24.9.2	Redesignated
	2.24.9.3	Redesignated
	2.24.9.4	Redesignated
	2.24.9.5	Redesignated
	2.24.9.6	Redesignated
	2.24.9.7	Redesignated
	2.24.10	Redesignated
60	2.25.1.1	Revised
61	2.25.2.4	Revised
61	2.25.2.5	Added
62	2.26.1.2	Revised
63	2.26.2.7	Added
63	2.26.2.8	Added
66	2.29	Revised
67	2.30	Revised in its entirety
71	2.31	Revised
	2.32	Deleted
	2.33	Deleted
72	3	Added
95	Annex B (informative)	Maintenance Control Program Records Added
96	Table B-1	Maintenance Control Program Records Added
97	Annex C (informative)	Acceptance Tests Added

ASME A17.8-2021/CSA B44.8:21

Standard for wind turbine tower elevators

(ED) 1 General

1.1 Scope

ASME A17.8/CSA B44.8 applies to elevators permanently installed in a wind turbine tower to provide vertical transportation of authorized personnel and their tools and equipment only.

Such elevators are typically subjected to extreme temperatures, humidity variations, and substantial horizontal motions where, by reason of their limited use and the types of construction of the structures served, full compliance with ASME A17.1/CSA B44 Part 2 is not practicable or necessary.

(ED) 1.1.1 Effective date

The requirements of this edition and subsequent addenda to the Standard are effective as of the date noted on the copyright page of this document. The authority having jurisdiction will establish the effective date for its local regulations.

(21) 1.2 Purpose and exceptions

1.2.1 Purpose

The purpose of this Standard is to provide for the safety of life and limb, and to promote the public welfare. Compliance with this Standard shall be achieved by

- a) conformance with the requirements in ASME A17.8/CSA B44.8; or
- b) conformance with some of the requirements of ASME A17.8/CSA B44.8 and for systems, subsystems, components, or functions that do not conform with certain requirements in ASME A17.8/CSA B44.8, conform with the applicable requirements in ASME A17.7/CSA B44.7; or
- c) conformance with the requirements in ASME A17.7/CSA B44.7

1.2.2 Exceptions to ASME A17.8/CSA B44.8

The provisions of this Standard are not intended to prevent the use of systems, methods, or devices of equivalent or superior quality, strength, fire resistance, effectiveness, durability, and safety to those prescribed by this Standard, provided that there is technical documentation to demonstrate the equivalency of the system, method, or device.

1.2.2.1

The specific requirements of this Standard shall be permitted to be modified by the authority having jurisdiction based upon technical documentation or physical performance verification to allow alternative arrangements that will assure safety equivalent to that which would be provided by conformance to the corresponding requirements of this Standard.

1.2.2.2

Exceptions shall be based on the requirements of [1.2.2.1](#).

(21) 1.3 Definitions

The following definitions shall apply in this Standard:

- (21) **Accredited certifying organization** — a certifying organization that holds valid Documentation of Accreditation issued by an independent internationally or nationally recognized accrediting organization that accredits personnel certification bodies.

Note: A Certificate of Accreditation is an example of such documentation.

- (21) **Accrediting body** — an independent internationally or nationally recognized organization that accredits organizations concerned with personnel certification.
- (21) **Alteration** — any change to equipment, including its parts, components, and/or subsystems, other than maintenance, repair, or replacement.
- (21) **Approved** — acceptable to the authority having jurisdiction.
- (21) **Authority having jurisdiction** — the organization, office, or individual responsible for enforcement of this Standard. Where compliance with this Standard has been mandated by legislation or regulation, the “authority having jurisdiction” is the regulatory authority (see **Regulatory authority**).

Authorized personnel — persons who have been instructed in the operation of the equipment and designated by the owner to use the equipment.

- (21) **Brake, driving machine or elevator** — an electromechanically released spring, or gravity applied device, that is part of the electric driving machine of the elevator used to apply a controlled force at a braking surface to hold or retard the elevator.

Electromechanically released — a means of brake release in which an electric current applied to an actuator (such as a solenoid) causes an electromagnetic force that overcomes a resisting force (such as a spring) as long as the electric current flows.

Buffer — a device designed to stop a descending car or counterweight beyond its normal limit of travel by storing or by absorbing and dissipating the kinetic energy of the car or counterweight.

Spring buffer — a buffer utilizing one or more springs to cushion the impact force of the descending car or counterweight.

Bumper — a device other than an oil or spring buffer designed to stop a descending car or counterweight beyond its normal limit of travel by absorbing the impact.

Cable, traveling — see **Traveling cable**.

Capacity — see **Rated load**.

- (21) **Car door or gate electric contact** — an electrical device, the function of which is to prevent operation of the driving machine by the normal operating devices unless the car door or gate is in the closed position.

Car, elevator — the load-carrying unit including its platform, car frame, enclosure, and car door or gate.

Car enclosure — the top and the walls of the car resting on and attached to the car platform.

Car frame — the supporting frame to which the car platform, upper and lower sets of guide shoes, car safety, and the hoisting ropes or hoisting-rope sheaves, or the plunger or cylinder of a direct-acting elevator, are attached.

Car platform — the structure that forms the floor of the car and that directly supports the load.

Certified — see **Listed/certified**.

Certifying organization — an approved or accredited, independent organization concerned with product evaluation that maintains periodic inspection of production of listed/certified equipment or material and whose listing/certification states whether that equipment meets appropriate standards or has been tested and found suitable for use in a specified manner.

Note: For the purpose of this definition, *accredited means that an organization has been evaluated and approved by an Authorized Agency to operate a Certification/Listing program, and is designated as such in a publication of the Authorized Agency.*

- (21) **Clearance, top car** — the shortest vertical distance between any part of the car structure and the nearest part of the overhead structure or any other obstruction when the car is level with the top terminal landing.

Clearance, top counterweight — the shortest vertical distance between any part of the counterweight structure and the nearest part of the overhead structure or any other obstruction when the car floor is level with the bottom terminal landing.

Control, motion — that portion of a control system that governs the acceleration, speed, retardation, and stopping of the moving member.

- (21) **Control, AC motor** — a motion control that uses an alternating current motor to drive the machine.

Control, single speed AC — a motion control for an AC motor that has a single synchronous speed.

- (21) **Control, two speed AC** — a motion control for an AC motor that has two different synchronous speeds by connecting the motor windings so as to obtain a different number of poles.

Control, operation — that portion of a control system that initiates the starting, stopping, and direction of motion in response to a signal from an operating device.

- (ED) **Operation, automatic** — operation control wherein the starting of the elevator car is effected in response to the momentary actuation of operating devices at the landing, and/or of operating devices in the car identified with the landings, and/or in response to an automatic starting mechanism, and wherein the car is stopped automatically at the landings.

Operation, automatic call — operation control wherein the starting of a wind turbine tower elevator car is effected in response to the momentary actuation of operating devices not mounted on the car and wherein the car is stopped automatically at the terminal landing or at the next landing in the direction of travel.

Operation, automatic send — operation control wherein the starting of a wind turbine tower elevator car is effected in response to the momentary actuation of operating devices mounted on the car and only accessible from outside the car, wherein the car is stopped automatically at the terminal landing or at the next landing in the direction of travel.

- (21) **Control system** — the overall system governing the starting, stopping, direction of motion, acceleration, speed, and retardation of the moving member.

Controller — a device or group of devices that serves to control in a predetermined manner the apparatus to which it is connected.

- (21) **Controller, motion** — an operative unit comprising a device or group of devices for actuating the moving member.

Controller, motor — the operative units of a motion control system comprising the starter devices and power conversion equipment required to drive an electric motor.

Door — the movable portion(s) of an entrance that closes the openings. It consists of one or more solid face panels that are permitted to be equipped with a vision panel.

Door, horizontally sliding — a door that moves horizontally.

Door or gate, self-closing — a manually opened door or gate that closes when released.

Door, swinging — a door that pivots around a vertical axis.

- (21) **Door or gate closer** — a device that closes a door or gate by means of a spring or gravity.

Door or gate electric contact — an electrical device, the function of which is to prevent operation of the driving machine by the normal operating device unless the door or gate is in the closed position.

Driving machine — see **Machine, driving**.

Driving machine, traction climbing — an uncounterweighted driving machine where traction results from the weight of the car and its load.

Elevator — a hoisting and lowering mechanism, equipped with a car, that moves within guides and serves two or more landings and is classified by the following type:

Elevator, wind turbine tower — a hoisting and lowering mechanism equipped with a car installed in a wind turbine tower.

- (21) **Elevator personnel** — persons trained in the construction, maintenance, repair, inspection, or testing of wind turbine tower elevators, including climb training, rescue at height, fall arrest and evacuation training, personal protective equipment training, and first aid training with continuing education requirements annually..

- (21) **Emergency personnel** — persons who have been trained in emergency evacuation.

- (21) **Emergency stop switch** — a device located as required and readily accessible for operation that, when manually operated, causes the electric power to be removed from the driving-machine motor and brake of a wind turbine tower elevator.

Endurance limit of a component — the maximum stress that can be alternated or reversed within specified limits without producing fracture of the component material.

Engineering test — a test carried out or witnessed by a registered or licensed professional engineer, testing laboratory, or certifying organization to ensure conformance to Standard requirements.

Factor of safety — the ratio of the ultimate strength to the working stress of a member under maximum static loading, unless otherwise specified in a particular requirement.

- (21) **Fail safe** — a characteristic of a system or its elements whereby any failure or malfunction affecting safety will cause the system to revert to a state that is known to be safe.

Gate — the moveable portion(s) of an entrance that closes the opening. A gate has through openings.

Governor — see **Speed governor**.

Guide rope fixes — wire guide rope attachment hardware securing the guiding system to the structure.

- (21) **Guiding means, ladder** — the guide system where the tower ladder is used to guide the car within the travel path.
- (21) **Hard copy** — a written record or log of all items specified in the maintenance records.
- (21) **Hoistway (shaft), elevator** — an opening through a building or structure for the travel of elevators extending from the floor of the lowest platform to the roof or floor above the top platform. (see **Travel path**).

Hoistway door or gate locking device — a device that secures a hoistway door or gate in the closed position and prevents it from being opened from the landing side except under certain specified conditions.

Hoistway door combination mechanical lock and electric contact — a combination mechanical and electrical device with two related, but entirely independent functions that are

- a) to prevent operation of the driving machine by the normal operating device unless the hoistway door is in the closed position
- b) to lock the hoistway door in the closed position and prevent it from being opened from the landing side unless the car is within the landing zone

Note: *As there is no positive mechanical connection between the electric contact and the door locking mechanism, this device ensures only that the door will be closed, but not necessarily locked, when the car leaves the landing. Should the lock mechanism fail to operate as intended when released by a stationary or retiring car-cam device, the door can be opened from the landing side even though the car is not at the landing. If operated by a stationary car-cam device, it does not prevent opening the door from the landing side as the car passes the floor.*

- (21) **Hoistway gate separate mechanical lock** — a mechanical device the function of which is to lock a hoistway gate in the closed position after the car leaves a landing and prevent the gate from being opened from the landing side unless the car is within the landing zone.

Hoistway enclosure — the fixed structure consisting of vertical walls or partitions that isolates the hoistway from all other areas or from an adjacent hoistway and in which entrances are installed.

- (ED) **Installation** — a complete elevator including its hoistway, hoistway enclosures and related construction, and all machinery and equipment necessary for its operation.

Labeled/marked — equipment or material to which has been attached a label, symbol, or other identifying mark of an approved or accredited independent certifying organization, concerned with product evaluation, that maintains periodic inspection of production of labeled/marked equipment or material, and by whose labeling/marking the manufacturer indicates compliance with appropriate standards or performance in a specified manner.

Note: *For the purpose of this definition, “accredited” means that an organization has been evaluated and approved by an Authorized Agency to operate a Certification/Listing program, and is designated as such in a publication of the Authorized Agency.*

Landing, elevator — that portion of a floor or platform used to receive and discharge passengers.

- (21) **Landing, terminal** — the most extreme landing at the top or bottom served by the elevator that is equipped with a hoistway entrance.

Listed/certified — equipment or materials accepted for inclusion in a publication by a certifying organization.

Note: *The means for identifying listed/certified equipment may vary for each organization concerned with product evaluation, some of which do not recognize equipment as listed/certified unless it is also labeled/marked. The authority having jurisdiction utilizes the system employed by the listing/certifying organization to identify a listed/certified product.*

Load, dynamic — the load applied as a result of acceleration or deceleration.

Load, impact — a suddenly applied load.

Load, static — the load applied as a result of the weight.

Machine, driving — the power unit that applies the energy necessary to drive an elevator or other equipment covered by the scope of this Standard.

Driving machine, electric — a driving machine in which the energy is applied by an electric motor. It includes the motor, driving-machine brake, and the driving sheave or drum, together with its connecting gearing, belt, or chain, if any.

Driving machine, rack-and-pinion — an electric driving machine in which the motion of the car is obtained by a power-driven rotation pinion(s) mounted on the car, traveling on a stationary rack mounted in the hoistway.

Traction machine — a direct driving machine in which the motion of a car is obtained through friction between the suspension ropes and a traction sheave.

Maintenance — a process of routine examination, lubrication, cleaning, and adjustment of parts, components, and/or subsystems for the purpose of ensuring performance in accordance with the applicable Standard requirements. (See also **Repair** and **Replacement**.)

- (ED) **Maintenance control program (MCP)** — a documented set of maintenance tasks, maintenance procedures, examinations, and tests to ensure that equipment is maintained in compliance with the requirements of this Standard.

- (21) **Maintenance interval** — the specified period between the occurrences of a specific maintenance task.

Maintenance procedure — an instruction or sequence of instructions for performing a specific task(s).

- (21) **Maintenance task** — a maintenance activity (work) that needs to be accomplished.

Manually (manual) reset, elevator —

- a type or feature of an elevator part or component that, when actuated, requires intervention of a person in order to reinstate it to its nonactuated state.
- a type of action required to be taken by a person to reinstate an elevator part or component from an actuated state to its nonactuated state.

May — indicates permission, not a mandatory requirement.

Means, suspension — tensile components that support, raise, and lower a car, counterweight, or both.

- (21) **Mechanical lock** — see **Hoistway door combination mechanical lock and electric contact** and **Hoistway door or gate locking device**.

Member, suspension — an individual load-carrying component of the suspension means (e.g., a single rope or belt).

Normal stopping means — that portion of the operation control that initiates stopping of the car in normal operation at landings.

Operating device — the car switch, push buttons, key or toggle switches, or other devices used to actuate the operation control.

Operation, inspection — a special case of continuous-pressure operation used for troubleshooting, maintenance, repair, adjustments, rescue, and inspection.

Overhead structure — all of the structural members, walls, platforms, etc., supporting the elevator machinery, sheaves, and equipment at the top of the hoistway.

- (21) **Periodic tests, category** — a grouping of tests performed at common time intervals required by the authority having jurisdiction.

Pit, elevator — the portion of a hoistway extending from the sill level of the bottom terminal landing to the floor at the bottom of the hoistway.

Platform, landing — permanent deck installed in wind turbine towers to access tower components.

- (ED) **Rated load, elevator** — the load that the equipment is designed and installed to lift at the rated speed.

- (ED) **Rated speed** — the speed at which the elevator is designed to operate under the following conditions:

- (ED) **Elevator** — the speed in the up direction with rated load in the car.

Readily accessible — capable of being reached quickly for operation, renewal, or inspection without requiring those to whom ready access is a requisite to climb over or remove obstacles or resort to portable ladders, chairs, etc.

- (21) **Regulatory authority** — the person or organization responsible for the administration and enforcement of the applicable legislation or regulation governing the design construction, installation, operation, inspection, testing, maintenance, or alteration of equipment covered by this Standard. (see also **Authority having jurisdiction**.)

Repair — reconditioning or renewal of parts, components, and/or subsystems necessary to keep equipment in compliance with applicable Standard requirements. (See also **Replacement** and **Maintenance**.)

Replacement — the substitution of a device or component and/or subsystems, in its entirety, with a unit that is basically the same as the original for the purpose of ensuring performance in accordance with applicable Standard requirements. (See also **Repair** and **Maintenance**.)

- (21) **Residual strength** — the actual breaking strength of a suspension member at any time during its operational life cycle.

Note: *The residual strength will be reduced as the suspension member is used and is subjected to wear.*

(21) **Rise** — the vertical distance between the bottom terminal landing and the top terminal landing of an elevator.

(ED) **Rope, suspension (hoisting)** — wire rope used to raise and lower an elevator or its counterweight, or both.

Safety, car or counterweight — a mechanical device attached to the car, car frame, or to an auxiliary frame; or to the counterweight or counterweight frame; to stop and hold the car or counterweight under one or more of the following conditions: predetermined overspeed, free fall, or if the suspension ropes slacken.

Shaft — see **Hoistway**.

Shall — indicates a mandatory requirement.

Should — indicates a recommendation, not a mandatory requirement.

Slack-rope switch — a device that automatically causes the electric power to be removed from the elevator driving machine motor and brake when the suspension ropes of a winding drum machine become slack.

(21) **Sound engineering practice** — the use of engineering or technical methods to design or evaluate a device or system by taking into account relevant factors that may influence its efficacy and operation. This practice also involves the use of applicable standards, specifications, codes, and regulatory and industry guidelines, as well as accepted engineering and design methods and installation and maintenance practices.

Speed governor — a continuously operating speed monitoring and detection device that, at predetermined speeds, provides signals to the controller and imparts a retarding force to activate the car or counterweight safety.

Tail line — the slack portion of the suspension member extending below the traction climbing driving machine.

Terminal landing — see **Landing, elevator or material lift**.

Terminal stopping device, final — a device that automatically causes the power to be removed from a driving machine motor and brake, or from a hydraulic machine, after the car has passed a terminal landing.

(ED) **Terminal stopping device, normal** — device(s) to slow down and stop an elevator car automatically at or near a terminal landing.

(21) **Trailing cable** — a cable made up of electric conductors, that provides electrical connection between an elevator car and a fixed container at the bottom of the travel path.

Travel path — in a wind turbine tower elevator, the space defined by the projected footprint of the car, inclusive of any horizontal displacement of the car, from the bottom landing platform to the uppermost point of travel or the final limit.

(ED) **Traveling cable** — a cable made up of electric conductors that provides electrical connection between an elevator car or counterweight and a fixed outlet in the hoistway.

Type test — a test carried out or witnessed by a certifying organization concerned with product evaluation and the issuing of certificates to ensure conformance to Code or Standard requirements.

(21) 1.4 References

The following is a list of publications referenced in this Standard:

16 CFR Part 1201 (Sections 1201.1 and 1201.2), Safety Standard for Architectural Glazing Materials

29 CFR OSHA 1910.66 (Appendix C), Powered Platforms for Building Maintenance

Publisher: U.S. Government Publishing Office

732 N. Capitol Street, NW

Washington, DC 20401

Telephone: (202) 512-1800 / (866) 512-1800

<http://www.gpo.gov/>

AGMA 218.01 (withdrawn), Rating the Pitting Resistance and Bending Strength of Spur and Helical Involute Gear Teeth

Publisher: American Gear Manufacturers Association

1001 N. Fairfax Street

Alexandria, VA 22314-1587

Telephone: (703) 684-0211

<http://www.agma.org>

ANSI Z535.2 (latest edition), Environmental and Facility Safety Signs

Publisher: American National Standards Institute

25 West 43rd Street

New York, NY 10036

Telephone: (212) 642-4900

<http://www.ansi.org>

AISC S326 (1978), Specification for Design, Fabrication, and Erection of Structural Steel for Buildings

Publisher: American Institute of Steel Construction

130 East Randolph Street

Suite 2000

Chicago, IL 60601

Telephone: (312) 670-2400

<http://www.aisc.org>

ANSI/AWS D1.1 (latest edition), Structural Welding Code — Steel

ANSI/AWS D1.3 (latest edition), Structural Welding Code — Sheet Steel

Publisher: American Welding Society

8669 NW 36 Street, #130

Miami, FL 33166

Telephone: (800) 443-9353

<http://www.aws.org>

ASME A17.1/CSA B44 (2013), Safety Code for Elevators and Escalators

ASME A17.6 (latest edition), Standard for Elevator Suspension, Compensation, and Governor Systems

ASME QEI-1-2018, Standard for the Qualification of Elevator Inspectorss

Publisher: The American Society of Mechanical Engineers

Two Park Avenue

New York, NY 10016-5990

Telephone: (212) 591-8500

<http://www.asme.org>

ASTM E8/E8M (latest edition), Standard Test Methods for Tension Testing of Metallic Materials

Publisher: American Society for Testing and Materials

100 Barr Harbor Drive

P.O. Box C700

West Conshohocken, PA 19428-2959

Telephone: (610) 832-9585

<http://www.astm.org>

CAN/CGSB-12.1 (1990), Tempered or Laminated Safety Glass

CAN/CGSB-12.11 (latest edition), Wired Safety Glass

CAN/CGSB-12.12 (latest edition), Plastic Safety Glazing Sheets

Publisher: Canadian General Standards Board

11 Laurier Street

Gatineau, QC K1A 1G6

Telephone: (819) 956-0425

<http://www.tpsgc-pwgsc.gc.ca/ongc-cgsb/index-eng.html>

CSA B44.1:19/ASME A17.5-2019, Elevator and Escalator Electrical Equipment

CSA C22.1:21, Canadian Electrical Code, Part I

CSA C22.2 No. 141-15 (R2020), Emergency lighting equipment

CSA S16:19, Limit states design of steel structures

CSA W47.1:19, Certification of companies for fusion welding of steel

CSA W59-18, Welded steel construction (metal arc welding)

CSA Z259.16:21, Design of active fall-protection systems

CAN/CSA-Z321 (withdrawn), Signs and symbols for the workplace

Publisher: CSA Group

178 Rexdale Boulevard

Toronto, ON M9W 1R3

Telephone: (416) 747-4044 / (800) 463-6727

shop.csa.ca

Elevator Industry Field Employees' Safety Handbook, 2020

Publisher: Elevator World

354 Morgan Ave.

Mobile, AL 36606

Telephone: (251) 479-4514

<https://elevatorworld.com/>

EN 12016:2009, Electromagnetic compatibility — Product family standard for lifts, escalators and moving walks — Immunity

EN 13411-3:2004, Terminations for steel wire ropes — Safety — Part 3: Ferrules and ferrule-securing

Publisher: British Standards Institution

389 Chiswick High Road

London, W4 4AL United Kingdom

Telephone: +44 020 8996 9000

<http://www.bsi-global.com>

ISO/IEC 17024:2012, Conformity assessment — General requirements for bodies operating certification of persons

Publisher: International Organization for Standardization

Chemin de Blandonnet 8

CP 401 - 1214 Vernier, Geneva, Switzerland

Telephone: +41 22 749 01 11

<https://www.iso.org>

NFPA 70 (latest edition), National Electrical Code

Publisher: National Fire Protection Association

1 Batterymarch Park

Quincy, MA 02169-7471

Telephone: (617) 770-3000

<http://www.nfpa.org>

UL 924 (latest edition), Emergency Lighting and Power Equipment

Publisher: Underwriters Laboratories, Inc.

333 Pfingsten Road

Northbrook, IL 60062-2096

Telephone: (847) 272-8800

<http://www.ul.com>

2 Wind turbine tower elevators

2.1 Construction of hoistways

2.1.1 Hoistway enclosure not required

Full hoistway enclosures are not required.

2.1.2 Enclosures required at landings

Partial hoistway enclosures shall be required at landing platforms and shall conform to [2.11](#).

2.1.3 Floor over travel path not required

A floor over the travel path is not required; however, when provided shall conform to [2.1.3.1](#) and [2.1.3.2](#).

2.1.3.1

Overhead floors shall be capable of sustaining a concentrated load of 1 000 N (225 lb) on any 2 000 mm² (3 in²) area, and in addition, where it constitutes the floor of the main or secondary level machinery space, it shall be designed for a live load not less than 6 kPa (125 lb/ft²) in all open areas.

(21) 2.1.3.2

Floors shall be of metal construction and if perforated, the openings shall reject a ball 13 mm (0.5 in) in diameter or be provided with a guard surrounding the perforation a minimum of 100 mm (4 in) in height.

2.2 Pits

2.2.1

Pits shall not be provided.

2.3 Location and enclosing of counterweights

2.3.1 Counterweight runways

Counterweights, where provided, shall have their runways fully enclosed and shall run in separate guides.

2.3.2 Access to enclosed counterweights and ropes

Access shall be provided for inspection, maintenance, and repair of an enclosed counterweight and its ropes. Doors or gates in the counterweight enclosures shall be self-closing and shall be provided with

- a) an electric contact, the opening of which will remove power from the elevator driving-machine motor and brake
- b) a self-locking keyed tumbler lock.

2.4 Vertical clearances for cars and counterweights

2.4.1 Top car clearance (maintenance/inspection access required)

Where access to the car top is required for maintenance or inspection and when the car has reached its maximum upward movement, the clearance above the car top, measured vertically up to the horizontal plane described by the lowest part of the overhead structure or other obstruction and measured within the projection of the car enclosure top exclusive of the area outside the standard railing (see [2.10.2](#)), where provided, shall be not less than 1 100 mm (43 in). In no case shall the following additional clearances be less than:

- a) 600 mm (24 in) above the car crosshead assembly except when the crosshead is located over the car enclosure top or the distance which any sheave assembly mounted in or on the crosshead projects above the top of the car crosshead, whichever is greater, but in no case shall there be less than 150 mm (6 in) clearance above the sheave assembly.
- b) 300 mm (12 in) above the car crosshead assembly where the crosshead is adjacent to the car enclosure top. The crosshead shall not overlap the car enclosure top by more than 100 mm (4 in) horizontally.
- c) 600 mm (24 in) above equipment attached to and projecting above the car enclosure top, exclusive of
 - i) standard railings
 - ii) areas outside of the standard railing, the vertical clearance shall be not less than 100 mm (4 in)
 - iii) roller and sliding guide assemblies.

Where access to the car top is required for maintenance and inspection of equipment, a railing conforming to [2.10.2](#) within 50 mm (2 in) of the perimeter of the car enclosure top shall be provided. When the car has reached its maximum upward movement, there shall be a clearance not less than 100 mm (4 in) from the highest projection of the car top railing to the nearest part of the overhead structure.

2.4.2 Top car clearance (maintenance/inspection access not required)

Where access to the car top is not required for maintenance or inspection

- a) equipment mounted on the car top shall not strike any part of the overhead structure or the equipment located in the travel path when the car has reached its maximum upward movement, and
- b) a sign shall be provided with the words “DANGER LOW CLEARANCE”* prominently posted on the car top equipment. The sign shall conform to ANSI Z535.2 or CAN/CSA-Z321, whichever is applicable. The sign shall be of such material and construction that the letters and figures stamped, etched, cast, or otherwise applied to the face shall remain permanently legible.

* The equivalent French wording is “DANGER, JEU RÉDUIT”.

2.4.3 Top counterweight clearance

Top counterweight clearance, where counterweights are provided, shall not be less than 600 mm (24 in).

(21) 2.5 Horizontal car and counterweight clearances

2.5.1 Between car and landing platforms

The clearance between the car and the landing platform shall be greater than or equal to 25 mm (1 in) on the sides used for loading and unloading (see Nonmandatory Annex [A](#)).

2.5.2 Between car and any stationary object

There shall be a minimum of 25 mm (1 in) clearance between the car structure and any stationary objects. Clearances are permitted to be maintained by rollers or similar devices mounted on the car. Clearance shall be measured from the car structure.

2.5.3 Between car and counterweight and counterweight guard

The clearance between the car and the counterweight shall be not less than 40 mm (1.5 in) at all times and under all operating conditions. The clearance between the car and the counterweight guard, counterweight and the counterweight guard, and between the counterweight and the hoistway enclosure shall be not less than 20 mm (0.8 in).

2.5.4 Measurement of clearances

The clearances shall be measured with no load on the car platform.

2.6 Protection of spaces below the travel path

Where the travel path does not extend to the lowest floor of the structure and there is space below the travel path that is accessible, the floor shall be capable of sustaining

- a) a concentrated load of 1 kN (225 lb) on any 2 000 mm² (3 in²) area, and
- b) a live load not less than 6 kPa (125 lb/ft²) in all open areas.

(ED) 2.7 Machinery spaces and control spaces

Elevator machine rooms and control rooms are not permitted in wind turbine towers.

2.7.1 Equipment location

Elevator equipment shall be located in machinery spaces and control spaces on the car or outside the travel path and shall conform to [2.7.1.1](#) and [2.7.1.2](#).

(21) 2.7.1.1 Motor controller location

The motor controller shall be

- a) located in a machinery space or control space, in an enclosure with a door(s) or panel(s) that is (are) not self-closing and that shall be kept closed
- b) readily accessible for maintenance and inspection at all times
- c) lit by permanently installed electric lighting with a lighting intensity of at least 200 lx (19 fc) at the cabinet when power is applied to the motor controller or temporary lighting with a lighting intensity of at least 200 lx (19 fc) at the cabinet when power is removed from the motor controller.

2.7.1.2 Temperature and humidity

All equipment shall be designed for the ambient air temperature and humidity range specified by the wind turbine manufacturer. The temperature and humidity range shall be permanently posted on the cabinet. The height of the letters and figures shall be not less than 3 mm (0.125 in).

2.8 Equipment in the travel path, machinery space, and control spaces**2.8.1 Electrical equipment and wiring**

Installation of electrical equipment and wiring shall conform to NFPA 70 or CSA C22.1, whichever is applicable. Turbine electrical generation equipment is permitted in spaces outside the travel path provided the nonelevator equipment does not interfere with the operation of the elevator equipment.

(ED) 2.9 Machinery and sheave beams, supports, and foundations**2.9.1 Securing of machinery beams and type of supports****2.9.1.1**

All machinery and sheaves shall be so supported and secured as to effectively prevent any part becoming loose or displaced.

2.9.1.2

Overhead beams directly supporting machinery shall be of steel.

2.9.1.3

Machinery or equipment shall be secured to and supported on, or from the top of, overhead beams, except for the following equipment:

- a) secondary or deflecting sheaves of traction elevators
- b) devices and their accessories for limiting or retarding car speed
- c) driving machines on the car.

2.9.1.4

Cast iron in tension shall not be used for supporting members for sheaves where they are hung beneath beams.

(21) 2.9.1.5

Beam torque stripes shall be applied to all bolt nuts used to fasten the overhead beam to the tower wall. The date torquing data shall be readily available to elevator personnel onsite.

(ED) 2.9.2 Loads on overhead beams and supports

Overhead beams, floors, and their supports shall be designed for not less than the load imposed by the guide ropes of rope-guided systems plus the sum of the following loads:

- a) the load secured to or supported by the beams and supports, that shall include the complete weight of the machine, sheaves, controller, governor, and any other equipment, together with that portion, if any, of the machinery space or control space supported thereon; and
- b) twice the sum of the tensions in all suspension members supported by the beams and their supports with rated load in the car.

Note: (2.9.2) *The object in doubling the suspended load is to allow for impact, accelerating stresses, etc.*

(21) 2.9.3 Allowable stresses and deflections for machinery and sheave beams, their supports, and any support members that transmit load to the turbine tower walls**(21) 2.9.3.1**

The unit stresses for all machinery and sheave beams and their supports, based on the loads computed as specified in 2.9.2, shall not exceed 80% of those permitted for static loads by AISC S326 or CAN/CSA-S16.1, whichever is applicable.

(ED) 2.9.3.2

The allowable deflections of machinery and sheave beams, their immediate supports, and any support members loaded in bending that transmit load to guide rails or turbine tower walls under static load shall not exceed 1/1666 of the span.

2.10 Guarding of equipment and standard railing**(ED) 2.10.1 Guarding of equipment**

In machinery and control spaces, the following shall be guarded to protect against accidental contact of exposed:

- a) sheaves and pinch points
- b) gears, sprockets, and chains
- c) keys, keyways, and screws in projecting shafts.

2.10.2 Standard railing

A standard railing shall be substantially constructed of metal and shall consist of a top rail, intermediate rail or equivalent structural member or solid panel, and toe-board.

2.10.2.1

The top rail shall have a smooth surface, and the upper surface shall be located at a vertical height of 1 070 mm (42 in) from the working surface.

2.10.2.2

The intermediate rail or equivalent structural member or solid panel shall be located approximately centered between the top rail and the working surface.

2.10.2.3

The toe-board shall be securely fastened and have a height not less than 100 mm (4 in) above the working surface.

2.10.2.4

A standard railing shall be capable of resisting anywhere along its length the following forces when applied separately, without deflecting more than 75 mm (3 in) and without permanent deformation:

- a) A force of at least 890 N (200 lbf) applied in any lateral or downward vertical direction at any point along the top rail.
- b) A force of at least 666 N (150 lbf) applied in any lateral or downward vertical direction at any point along the center of the intermediate rail, member, or panel. If the standard railing is a solid panel extending from the top rail to the toe-board, the application of the force specified in [2.10.2.4 a\)](#) shall be considered to meet the requirements of [2.10.2.4 b\)](#).
- c) A force of 225 N (50 lbf) applied in a lateral direction to the toe-board.

2.10.3 Landing platform protection

A standard railing protecting the openings in landing platforms shall be provided and conform to [2.11.5](#).

(ED) 2.11 Protection of landing platform openings

2.11.1 Landing platform doors or gates

A landing platform door or gate shall be permanently installed and shall be one of the following types:

- a) horizontally sliding
- b) horizontally swinging
- c) combination horizontally sliding and swinging.

2.11.2 Door or gate closers

Landing platform doors and gates shall be openable with not more than 50 N (11 lbf) and be self-closing or provided with a means to assure the door is closed when the car is not at a landing.

2.11.3 Horizontal platform inside enclosure

The horizontal distance between the travel path side of the door or gate and the edge of the landing platform shall be less than or equal to 65 mm (2.5 in) (see Nonmandatory Annex [A](#)).

2.11.4 Platform lighting

The landing platform shall be so lighted that the illumination, when the elevator is in service, shall be not less than 27 lx (2.5 fc) at the standing surface.

2.11.5 Landing platform enclosures

Where the travel path is adjacent to areas accessible by authorized or elevator personnel, the landing platform enclosure shall conform to [2.11.5.1](#) through [2.11.5.7](#).

2.11.5.1

It shall be enclosed to a height not less than 1 070 mm (42 in) above the floor or stair treads with a standard railing (see [2.10.2](#)).

2.11.5.2

It shall be at the bottom landing and have a solid or openwork enclosure that rejects a ball 25 mm (1 in) in diameter.

2.11.5.3

It shall be of sufficient strength to prevent contact between the enclosure and the car or counterweight when the enclosure is subjected to a force of

- a) 890 N (200 lbf) applied within 50 mm (2 in) of the top edge; and
- b) 1 112 N (250 lbf) applied at right angles at any point over an area of 100 mm × 100 mm (4 in × 4 in).

2.11.5.4

It shall have a horizontal clearance not less than 90 mm (3.5 in) and no more than 150 mm (6 in) between loading side of the car and inside of landing platform enclosure (see Nonmandatory Annex [A](#)).

2.11.5.5

It shall be provided with a means of entrance to the car complying with [2.11.2](#).

2.11.5.6

Landing platform horizontally sliding doors and gates shall have means provided to prevent the hangers from jumping the track and stops provided in the assembly to prevent hangers from overrunning the end of the track.

2.11.5.7

The hoistway face or hardware of the landing platform doors or gates shall not project into the travel path beyond the edge of the landing platform.

(21) **2.12 Landing platform door and gate locking devices, electric contacts, and trapped key systems**

(21) **2.12.1 Landing platform door and gate locking devices**

Landing platform door and gate mechanical locking and electric contacts are required where automatic call operation is provided unless a trapped key system conforming to [2.12.4](#) is provided.

(21) **2.12.2 Where required (for automatic call operation)**

When automatic call is provided conforming to [2.26.1.2](#) c), landing platform door or gate mechanical locking and electric contacts shall be provided.

(21) **2.12.3 Listing/certification door locking devices and door or gate electric contacts and landing platform enclosure gate combination mechanical locks and electric contacts**

Combination mechanical locks and electric contacts shall conform to [2.12.3.1](#) through [2.12.3.4](#), [2.12.5](#) and [2.26.2.8](#).

(21) **2.12.3.1**

They shall be so designed that the mechanical locking member and the electric contact are mounted on and attached to a common base in such a manner that there is a fixed relation between the location of the contact and the location of the locking member.

They shall be so installed and adjusted that the electric contact cannot close until the door or gate is in the closed position and so that the mechanical locking member is in a position to lock the door or gate when or before the contact closes. In order to prevent motion of the door or gate from opening the

electric contact while the door is locked in the closed position, multiple-locking points shall, where necessary, be provided on the locking mechanism.

(21) **2.12.3.2**

The electric contact shall be positively opened by the locking bar of the mechanical locking member or by a lever or other device attached to and operated by the door or gate, and the electric contact shall be maintained in the open position by the action of gravity or by a restrained compression spring, or both, or by positive mechanical means.

(21) **2.12.3.3**

The mechanical locking member shall hold the door or gate in the locked position by means of gravity, a restrained compression spring, or both.

(21) **2.12.3.4**

Mercury tube switches shall not be used.

(21) **2.12.4 General design requirements**

Trapped key systems shall conform to [2.12.4.1](#) through [2.12.4.8](#).

2.12.4.1

The trapped key system shall be provided and consist of the following components:

- a) one special key permanently tethered inside the car
- b) a car access lock inside the car
- c) a landing platform door access lock on each landing platform door.

2.12.4.2

The tether shall be no longer than required to actuate the access lock inside the car and actuate the access lock on the platform landing doors or gates. The permanent tether shall be of sufficient strength to prevent removing it without the use of tools.

2.12.4.3

The special key shall not be accessible from the outside of the car when the car door is closed.

2.12.4.4

The special key and locks shall be designed to prevent common tools from defeating the access locks.

2.12.4.5

Landing platform doors or gates shall not be openable unless the special key is actuated with that landing platform's door or gate access lock. The key shall not be removable from (trapped in) the landing access lock unless the doors or gates are closed and locked.

2.12.4.6

The car shall be prevented from moving by one of the following methods:

- a) where a special key actuates the car access lock and closes an electric contact. The special key shall not be removable from (trapped in) the car access lock unless power is concurrently removed from the driving machine motor and brake or
- b) where the special key is tethered such that it mechanically prevents the car door from being fully closed until the key is inside the elevator car.

2.12.4.7

The electric contact, where provided, in the trapped key devices shall conform to [2.26.2.7](#).

2.12.4.8

The lock on the landing platform door or gate shall withstand a force in accordance with [2.10.2.4](#).

2.12.5 Listing/certification door locking devices and door or gate electric contacts

2.12.5.1 Type tests

Each type and make of landing platform door or gate combination mechanical lock and electric contact shall conform to the type tests specified in ASME A17.1/CSA B44, 8.3.3. The tests shall be done by or under the supervision of a certifying organization.

2.12.5.2 Listing/certification

Each type and make of landing platform door or gate combination mechanical lock and electric contact shall conform to the general requirements for tests and certification specified in ASME A17.1/CSA B44, 8.3.1.

2.12.5.3 Identification marking

Each listed/certified device shall be labeled. It shall be permanently attached to the device and shall be so located as to be readily visible when the device is installed in its operating position.

The label shall include the following data:

- a) the name, trademark, or certifying organization file number by which the organization that manufactured the product can be identified
- b) the certifying organization name or identifying symbol
- c) statement of compliance with ASME A17.1/CSA B44 or ASME A17.8/CSA B44.8
- d) a distinctive type, model, or style letter or number
- e) rated voltage and current, and whether AC or DC
- f) date (month and year) devices subjected to type test specified in [2.12.5.1](#)
- g) if the device has only been type tested and listed/certified for use on a wind turbine tower elevator, the label shall indicate the restricted use.

2.13 Power operation of landing platform doors and car doors or gates

Power operation of landing platform doors and car doors or gates is prohibited.

2.14 Car enclosures, car doors and gates, and car illumination

2.14.1 Car enclosure

Cars shall be enclosed with metal at the sides and top. The enclosure walls shall be designed to reject a 25 mm (1 in) ball up to a height of 2 135 mm (84 in).

2.14.2 Car height

The minimum clear height inside the car shall be no less than 2 000 mm (78 in). The clear height shall be permitted to be reduced to 1 930 mm (76 in) provided all projections below 2 000 mm (78 in) are marked with yellow and black diagonal stripes not less than 25 mm (1 in) in width.

2.14.3 Vision panels

Vision panels are permitted in the enclosure walls provided they are located 1 000 mm (39 in) above the floor.

2.14.4 Enclosure panels

Where enclosures include panels of glass, or transparent or translucent plastic, the panels shall

- a) be constructed of laminated glass that complies with the requirements of 16 CFR Part 1201, Sections 1201.1 and 1201.2; or be constructed of laminated glass, safety glass, or safety plastic that complies with CAN/CGSB-12.1, CAN/CGSB-12.11, or CAN/CGSB-12.12, whichever is applicable
- b) be mounted in the structure so that the assembly shall withstand the required elevator tests without damage
- c) have markings as specified in the applicable glazing standard that shall be on each separate piece, and shall remain visible after installation.

2.14.5 Strength of car top

The car enclosure top shall be so designed and installed as to be capable of sustaining a load of 135 kg (300 lb) on any area 600 mm × 600 mm (24 in × 24 in), or 45 kg (100 lb) applied to any point, without permanent deformation. The resulting deflection under these loads shall be limited to prevent damage to any equipment, devices, or lighting assemblies fastened to or adjacent to the car enclosure top.

2.14.6 Top of car railing

Where the car top is intended to be used for operation of the car for maintenance or inspection, it shall be provided with a car top standard railing conforming to [2.10.2](#).

2.14.7 Car illumination

Illumination in the car shall be provided from a permanent light source inside or outside the car. The light source shall provide illumination of at least 27 lx (2.5 fc) at the floor of the car platform with car door or gate in the closed position.

2.14.8 Emergency lighting

Illumination in the car shall be provided from an emergency light source in the car or from outside the car. The light source shall provide a minimum level of illumination of 2 lx (0.2 fc), measured at any point between 890 mm (35 in) and 1 225 mm (48 in) above the car floor and approximately 300 mm (12 in) centered horizontally in front of a car.

2.14.8.1

Emergency lights shall be automatically turned on when normal car lighting power fails.

2.14.8.2

The power system shall be capable of maintaining the minimum light intensity specified for a period of at least 30 min.

(21) 2.14.8.3

Battery-operated units mounted on the car, where provided, shall

- a) conform to CSA C22.2 No. 141 or UL 924
- b) be permanently connected to a car light circuit provided from the elevator controller.

2.14.9 Car emergency exit

Means for emergency exit from the car shall be provided and shall conform to [2.14.9.1](#) and either [2.14.9.2](#) or [2.14.9.3](#).

(21) **2.14.9.1**

Rated personnel protective equipment anchorage point(s), appropriate to the number of persons the car is designed to carry, shall be provided for safe emergency exit conforming to OSHA 29 CFR 1910.140, CSA Z259.16, or the fall protection requirements of the jurisdiction where the elevator is being installed.

(21) **2.14.9.2**

Emergency exit through the car door or gate is permitted where the distance from the point of emergency exit to the accessible means of evacuation does not exceed 1 000 mm (39 in).

(21) **2.14.9.3**

Access through the top or bottom of a ladder-guided car is permitted where

- a) the distance from the point of access to the accessible means of evacuation is equal to or less than 1 000 mm (39 in) and the exit,
- b) the opening has an area not less than 227 000 mm² (352 in²), and shall not measure less than 380 mm (15 in) on any side,
- c) be so located as to provide a clear passageway, unobstructed by fixed elevator equipment located in or on top of the car,
- d) the access covers are hinged, or otherwise attached, to the car and open in the upward direction only, and
- e) the ladder access door is equipped with a switch or contact conforming to [2.26.2.6](#) that, when opened, removes power from the driving-machine motor and brake .

2.14.10 Car doors and gates

Each car shall be equipped with a car door or gate conforming to the following:

- a) when closed, guard the opening to its full height,
- b) be mechanically prevented from unintentional opening,
- c) be openable from inside the car and from outside the car at any point in the travel path,
- d) be of solid or openwork construction that will reject a ball 25 mm (1 in) in diameter,
- e) when made of materials other than metal, conform to [2.14.3](#) and [2.14.4](#),
- f) not be power operated, and
- g) when subjected to a force of 335 N (75 lbf) applied on an area 300 mm (12 in) square at right angles to and approximately at the center of the door or gate, doors and gates shall not be permanently deformed or be displaced from their guides or tracks.

2.14.11 Car door and gate electric contacts

Each car door or gate shall be provided with a door or gate electric contact conforming to the following:

- a) it shall remove power from the driving-machine motor and brake when the car door or gate is not in the closed position,
- b) it shall be positively opened by a device attached to and operated by the door or gate,
- c) it shall be maintained in the open position by the action of gravity or by a restrained compression spring, or both, or by positive mechanical means, and
- d) it shall not utilize mercury tube switches.

2.14.11.1

Each type and make of car door or gate electric contact shall be type tested per [2.30](#). The tests shall be done by or under the supervision of a certifying organization.

2.14.11.2

Each listed/certified device shall be labeled. It shall be permanently attached to the device, and shall be so located as to be readily visible when the device is installed in its operating position. The label shall include the following data:

- a) the name, trademark, or certifying organization file number by which the organization that manufactured the product can be identified
- b) the certifying organization name or identifying symbol
- c) a distinctive type, model, or style letter or number
- d) rated voltage and current, and whether AC or DC.

(21) 2.14.12 Clear openings

The clear opening of the car door or gate shall be a minimum of 450 mm (18 in) wide and 1 900 mm (74 in) high.

(ED) 2.14.13 Sectioning

Car doors or gates are permitted to be sectioned provided each section partially covering the car enclosure entrance conforms to [2.14.10](#) through [2.14.12](#). The lower door section shall be a minimum of 1 100 mm (43 in) in height.

2.14.14 Ventilation

Natural ventilation openings shall be provided in the car enclosures with a total area of not less than 3.5% of the inside car floor area divided equally between the bottom and top of the car enclosure.

(ED) 2.15 Car frames and platforms**(21) 2.15.1 Car frames and floors**

Car frames and car floors shall be made of metal and supported by the car frame. Floors shall extend over the entire area of the interior of the car and shall be designed to minimize slipping (e.g., dimpling, coating with skid-resistant material, etc.).

2.15.2 Use of cast iron

Cast iron shall not be used in the construction of any member of the car frame or platform other than for guide shoes and guide-shoe brackets.

2.15.3 Number of compartments

The car shall not have more than one compartment.

2.15.4 Guiding means

Car frames shall be guided on each side by upper and lower guiding members attached to the frame.

2.15.5 Strength of guiding means

Guiding members shall be designed to withstand the forces imposed during normal operation of the elevator, emergency stopping, and the application of safeties.

2.15.6 Car frame

All structural components of the car frames and platforms shall have a minimum factor of safety of 5.

2.15.7 Guiding members

Failure of any guiding member shall not permit the car and car frame to strike any portion of the tower structure. Obstruction-detection devices (see [2.15.9](#)) shall be permitted to detect when the car is outside the travel path.

(21) 2.15.8 Kickboard

The car platform shall be provided with a kickboard with a minimum of 25 mm (1 in) and a maximum of 100 mm (4 in) in height, located on the side used for loading and unloading and shall be marked yellow. The height of the kickboard shall not be considered in the clear height opening required by [2.14.12](#).

2.15.9 Obstruction-detection devices

The top and bottom of the car shall be provided with a means to detect an obstruction in the travel path and stop the car by causing the power to be removed from the driving-machine motor and brake. Each obstruction-detection device shall

- a) be provided with a switch actuated by the obstruction-detection device whose contacts are positively opened mechanically; their opening shall not be solely dependent on springs,
- b) be designed in such a manner that it cannot be reset until the obstruction-detection mechanism has been returned to the unapplied position,
- c) be designed to withstand the forces imposed on it,
- d) have a maximum actuation force of 70 N (15 lbf) and a throw not to exceed 100 mm (4 in). The switch shall actuate upon movement of the obstruction-detection device,
- e) detect a ball greater than 100 mm (4 in) in diameter within the projected area of the car, and
- f) not permit restarting of the elevator when an obstruction device resets, after being actuated.

2.15.10 Warning devices

Cars shall be provided with an external visual warning device or an audible warning device (or both) that operates while the car is in motion.

(21) 2.15.10.1

The illumination of the external visual warning device shall be a minimum of 10 candela measured at a point 2.5 m (8 ft) from the horizontal surfaces of the car with a flash frequency between 50 to 80 times per minute and be visible above and below the car.

2.15.10.2

The audible warning device shall have a minimum sound level of 70 dBA at 1 000 mm (39 in) in the travel path and below the elevator, with a 50% duty cycle and a frequency between 1 kHz and 4 kHz and be audible above and below the car.

2.15.10.3

Means shall be provided to assure operation of the visual or audible warning device during primary power loss for a minimum of 30 min. If a battery is used for this purpose, testing, replacement, and inspection procedures shall be provided in the MCP (see [3.1.1](#)).

(21) **2.15.11 Ladder-guided platforms**

Platforms for ladder-guided systems are permitted to have perforations or be of fabricated openwork construction. Openings shall reject a ball 13 mm (0.5 in) in diameter. See [2.23.2.5](#).

2.16 Capacity and loading

2.16.1 Capacity and data plates

Every car shall be provided with a capacity plate and a data plate permanently and securely attached. The capacity plate shall be located in a conspicuous position inside the car.

2.16.2 Information required on plates

2.16.2.1 Capacity plates

Capacity plates shall be marked in a legible and permanent manner with letters and figures not less than 25 mm (1 in) in height indicating the rated load of the elevator in kilograms or pounds, or both.

2.16.2.2 Data plates

Data plates shall be marked in a legible and permanent manner with letters and figures not less than 3 mm (0.125 in) in height indicating

- a) the weight of the complete car, including the driving machine and all auxiliary equipment attached to the car,
- b) the rated load and speed,
- c) the suspension-means data required,
- d) the name or trademark of the manufacturer and year manufactured, and
- e) guiding means lubrication instructions.

2.16.3 Limitation of load, speed, and platform area

The rated load shall not exceed 454 kg (1 000 lb). The inside net platform area shall not exceed 1.2 m² (13 ft²). The minimum rated load shall not be less than that based on 3.4 kPa (70 lbf/ft²) of inside net platform area or 113 kg (250 lb), whichever is greater. The rated speed shall not exceed 0.4 m/s (80 ft/min).

(21) **2.16.4 Overload detection means**

A means to detect an overload shall be provided and the overload value determined by the manufacturer's recommendations, but shall not exceed 150% of the rated load. A visual or audible signal device shall be provided so that authorized personnel are notified of an overload condition. Electrical operation in either direction shall be prohibited when overload is detected.

2.16.5 Speed-limiting device

A means shall be provided to limit the descent speed of the car to less than safety tripping speed when the manual brake release system is operated.

2.17 Car and counterweight safeties

Each car, and where required by [2.6](#) each counterweight, shall be provided with a safety conforming to [2.17.1](#) or [2.17.2](#) and the applicable requirements of [2.17.3](#) through [2.17.5](#).

2.17.1 Wire rope gripping safety

The safety shall be operated without delay by the breakage of the suspension means or by the action of an internal centrifugal governor when the car exceeds rated speed up to a maximum of 0.9 m/s (175 ft/min).

(ED) 2.17.1.1

The safety shall act on an independent safety wire rope upon loss of suspension or overspeed (see [2.20.2](#)).

2.17.1.2

Safeties shall be applied mechanically. Electric, hydraulic, or pneumatic devices shall not be used to apply the safeties or to hold such safeties in the retracted position.

2.17.1.3

When car safeties are applied, no motion of the car in the down direction shall release the safeties, but such safeties shall be permitted to be released by the motion of the car in the up direction.

2.17.1.4

Safeties shall be so designed that, on their application, the forces that provide the stopping action shall be compressive forces and shall not cause permanent deformation of the safety wire rope upon whose dimensional stability the stopping capability of the safeties is dependent.

2.17.1.5

The safety shall be located where it is readily accessible and it cannot be struck by any moving object in normal operation or under conditions of overtravel.

2.17.1.6

The minimum factors of safety and stresses of safety parts and rope connections shall not be less than 3.5, and the materials used shall have an elongation not less than 15% in a length of 50 mm (2 in) when tested in accordance with ASTM E8. Forged, cast, or welded parts shall be stress relieved.

2.17.1.7

Springs are permitted in the operation of car or counterweight safeties. Where used, and where partially loaded prior to safety operation, the loading on the spring shall not produce a fibre stress exceeding one-half the elastic limit of the material. During operation of the safety, the fibre stress shall not exceed 85% of the elastic limit of the material. Helical springs, where used, shall be in compression.

2.17.1.8

The factors of safety shall be based on the maximum stresses developed in the parts during the operation of the safety when stopping rated load from overspeed.

2.17.2 Rack-and-pinion safety

Where a single rack-and-pinion drive machine is used, the car shall be provided with one or more safeties conforming to [2.17.1](#) or a safety consisting of a freely rotating safety pinion, a governor, and a clamping device that shall be permitted to form an integral unit mounted on the car.

2.17.2.1

The safety shall operate without delay when the car exceeds rated speed up to a maximum of 0.9 m/s (175 ft/min) bringing the car to a gradual stop on the vertical rack.

2.17.2.2

Where multiple rack-and-pinion driving machines are provided, a safety is not required when

- a) each driving machine is independently able to prevent a car that is loaded to 125% of rated load from descending uncontrolled,
- b) each driving machine is capable of moving the car to the bottom floor under manual control, and
- c) the failure of one driving machine is detected and power is removed from the other driving-machine motor and brake.

2.17.2.3

The stopping distance of the car measured from the time the safety or alternate means actuates to a full stop shall be a minimum of 25 mm (1 in) and a maximum of 380 mm (15 in).

2.17.3 Safety marking plates

Marking plates shall be metal and be securely attached or adjacent to each safety so as to be readily visible, and shall be marked in a legible and permanent manner with letters and figures not less than 3 mm (0.125 in) in height indicating

- a) the type of safety, based on [2.17](#),
- b) the maximum tripping speed in m/s (ft/min) for which the safety is permitted,
- c) the maximum weight in kg (lb) that the safety is designed and installed to stop and sustain,
- d) the manufacturer's name or trademark,
- e) the year of manufacture, and
- f) the force in N (lbf) required to activate the safety if applicable.

2.17.4 Opening of driving-machine motor and brake control circuits on safety application

Safeties shall be provided with a switch that opens (actuates) causing the power to be removed from the driving-machine motor and brake at the time the safety actuates and shall be of a type that cannot be reset until the safety mechanism has been returned to the unapplied position and conforms to [2.26.2.3](#).

2.17.5 Application of safety

A safety device that depends on the completion or maintenance of an electric circuit for the application of the safety is not permitted. Safeties shall be applied mechanically.

2.18 Reserved for future use

2.19 Reserved for future use

(21) 2.20 Suspension means and their connections

Suspension means shall conform to ASME A17.6, Part 4 and manufacturer's recommendations using sound engineering practice and [2.20.1](#) through [2.20.4](#).

(21) **2.20.1 Suspension means for counterweighted traction elevators**

For counterweighted traction elevators, suspension means shall be drawn-galvanized steel wire rope and [2.20.1.1](#) through [2.20.1.5](#).

(21) **2.20.1.1**

The minimum diameter of any steel wire rope shall be not less than 9.5 mm (0.375 in). Access for suspension means inspection purposes shall be provided.

(21) **2.20.1.2**

The factor of safety of the steel wire rope shall not be less than 7.95. See [2.20.3](#).

(21) **2.20.1.3**

Where counterweighted systems are provided, sufficient traction shall be provided between the steel wire ropes and drive sheave grooves, to safely stop and hold the car at the overload value specified in [2.16.4](#), at rated speed in the down direction and safely stop and hold the car with no load at rated speed in the up direction.

2.20.1.4

No car or counterweight steel wire rope shall be lengthened or repaired by splicing. If one rope of a set is worn or damaged and requires replacement, the entire set of ropes shall be replaced.

2.20.1.5

The car or counterweight ends of steel wire ropes shall be fastened by properly attached fittings as recommended by wire-rope manufacturers.

(21) **2.20.2 Suspension means for uncounterweighted traction elevators**

For uncounterweighted traction elevators, the suspension members shall be drawn-galvanized steel wire rope and comply with [2.20.2.1](#) through [2.20.2.12](#).

(21) **2.20.2.1**

The minimum diameter of any suspension steel wire rope shall not be less than 8 mm (0.3125 in). Access for suspension means inspection purposes shall be provided.

(21) **2.20.2.2**

The factor of safety of the suspension means shall be not less than 10. See [2.20.3](#).

(21) **2.20.2.3**

Sufficient traction shall be provided between the steel wire ropes and drive sheave grooves, to safely stop and hold the car at the overload value specified in [2.16.4](#), at rated speed in the down direction.

2.20.2.4

No car suspension rope shall be lengthened or repaired by splicing.

(21) **2.20.2.5**

Suspension steel wire rope terminations shall be fastened by properly attached fittings or swages as recommended by wire-rope manufacturers and swage fittings shall comply with the following:

- a) Use of swage fittings only on regular lay, synthetic core, or IWRC ropes are permitted.

- b) They are swaged in a shop with a press under controlled conditions to guarantee reliable attachment.
- c) Where rope adjustment is required, it may only be used at one end of the rope.
- d) Swages shall be designed and tested in accordance with the design and testing requirements of BS EN 13411-3.
- e) The swaging company shall be identified on the swage or on the rope data tag.
- f) Swaging shall not be performed in the field.
- g) The manufacturer shall provide verification means to assure the swage is crimped to manufacturer's specification.

2.20.2.6

U-bolt type rope clamps or similar devices shall not be used on the load side of suspension rope or safety wire rope fastenings.

2.20.2.7

Fastenings shall develop a minimum of at least 80% of the rope manufacturer's rated breaking force.

2.20.2.8

Means shall be provided to prevent the fastenings from having any physical contact resulting in wear of the rope or its fastening.

(21) 2.20.2.9

Use of a single suspension steel wire rope is permitted when a safety steel wire rope of equivalent size and grade as the suspension steel wire rope is provided (see [2.20.2.10](#)).

(21) 2.20.2.10

A safety rope shall be provided and used only in the event of loss of primary suspension or overspeed safety actuation and shall

- a) consist of a steel wire rope upon which a safety device (see [2.17.1](#)) actuates to stop the car, and
- b) conform to [2.20.2](#) and [2.20.3](#), except [2.20.2.3](#).

(ED) 2.20.2.11

Pertinent data located on the suspension means and safety rope shall be provided by a data tag securely attached to the fastenings or adjacent to the controller. The following data shall be provided:

- a) type of suspension
- b) the diameter of the rope in millimeters or inches
- c) the suspension-means manufacturer's minimum breaking force in kN or lbf
- d) the grade of material used
- e) construction classification
- f) for steel wire rope, nonpreformed, if applicable
- g) for steel wire rope, finish coating, if applicable
- h) name or trademark of the rope manufacturer
- i) name of person or organization who installed the ropes
- j) the month and year the ropes were installed
- k) lubrication information
- l) swaging company, if applicable.

(21) 2.20.2.12

Fastenings for suspension rope and safety rope shall have means to prevent threaded connections or sliding components from vibrating off.

(21) 2.20.3

The factor of safety shall be calculated by the following formula:

$$F = \frac{S \times N}{W}$$

where

N = number of runs of suspension members under load

S = manufacturer's rated breaking force in kN (lbf) of one suspension member

W = maximum static load in kN (lbf) imposed on all suspension members with the car and its rated load at any position in the hoistway and/or travel path

2.20.4 Replacement of suspension means

The suspension means shall be replaced in conformance with the criteria of ASME A17.6, Part 4 and manufacturer's recommendations using sound engineering practice.

(ED) 2.21 Counterweights**2.21.1 Counterweight guides**

Counterweights shall be guided to prevent any horizontal movement that would inhibit proper operation or cause counterweight to move from designated travel path and shall not be of sufficient weight to cause undue slackening of the hoisting ropes during acceleration or retardation of the car.

2.21.2 Types of counterweight construction**2.21.2.1**

One-piece solid or laminated steel counterweights shall be permitted.

2.21.2.2

Where counterweight sections are used, means shall be provided to retain the sections in place if they become broken, whether carried in a frame or not. If tie rods are used, the sections shall be fastened together by a minimum of two tie rods that pass through all weight sections. Tie rods shall be provided with locknuts and cotter pins at each end.

2.21.2.3

The frame members and their connections shall be designed with a factor of safety not less than 5 with the elevator at rest and the counterweight at the top of its travel.

2.21.2.4

The counterweight frame shall be designed with a factor of safety not less than 2.5 at bumper or buffer engagement or safety application if provided.

2.22 Buffers, bumpers, and retardations

Cars and counterweights shall be provided with bumpers conforming to [2.22.1](#) or spring buffers conforming to [2.22.2](#).

2.22.1 Bumpers

Bumpers shall conform to the following:

- a) they shall be located so as to retard the car and counterweight without exceeding allowable design stresses in the car frame and counterweight frame,
- b) they shall be made of wood or other suitably resilient material of sufficient strength to withstand without failure the impact of the car with rated load, or the counterweight, descending at overspeed where provided, and
- c) the material used shall be of a type that will resist deterioration or be so treated as to resist deterioration.

2.22.2 Spring buffers

Spring buffers shall conform to the following:

- a) the stroke of the buffer spring shall be equal to or greater 38 mm (1.5 in)
- b) the buffer shall be capable of supporting, without being compressed solid or to a fixed stop, a static load having a minimum of two times the total weight of the car and its rated load for car buffers and the total weight of the counterweight for counterweight buffers
- c) the buffer shall be compressed solid or to a fixed stop with a static load of three times the weight of the car and its rated load for car buffers and the counterweight for total weight of the counterweight buffers
- d) the buffer shall be provided with a marking plate showing its load rating and stroke; markings shall be made in a permanent and legible manner.

2.22.3 Retardations

Bumpers and buffers shall develop an average retardation not in excess of 9.81 m/s^2 (32.2 ft/s^2), and shall develop no peak retardation greater than 19.6 m/s^2 (64.4 ft/s^2), having a duration exceeding 0.04 s with any load in the car.

2.23 Car and counterweight guidance systems, supports, and fastenings

Means shall be provided to assure hazards due to relative movement between the tower ladder and elevator are provided. Guiding systems shall consist of one of the following:

- a) wire-rope-guided conforming to [2.23.1](#)
- b) ladder-guided conforming to [2.23.2](#).

(21) 2.23.1 Wire rope guidance system for uncounterweighted traction drive machines

Guide ropes shall conform to [2.23.1.1](#) through [2.23.1.11](#)

(21) 2.23.1.1

Guide ropes shall be drawn-galvanized steel wire rope conforming to ASME A17.6, Part 4 and manufacturer's recommendations using sound engineering practice.

2.23.1.2

Guide ropes shall be tensioned with an applied load to maintain a minimum horizontal clearance of 25 mm (1 in) from the cab enclosure to other structures in the tower at all times. A means shall be provided to indicate the minimum and maximum allowable tension in the guide ropes.

(21) 2.23.1.3

Guide ropes shall have a minimum factor of safety of 8. The factor of safety shall be calculated by the following formula:

$$F = \frac{S \times N}{W}$$

where

N = number of guide ropes under load

S = manufacturer's rated breaking force in kN (lbf) of one guide rope

W = maximum static load in kN (lbf) imposed by guide rope tensioners

2.23.1.4

Guide ropes shall be a minimum of 8 mm (0.3125 in) in diameter.

2.23.1.5

Guide rope fixes shall

- a) have a spacing no greater than 30 m (98 ft) apart,
- b) be attached at each landing platform,
- c) be capable of resisting the forces imposed without permanent deformation,
- d) maintain alignment of the wire guide rope throughout the life cycle of the elevator, and
- e) allow for axial movement.

(21) 2.23.1.6

- a) Upper terminal guide rope fastenings shall conform to [2.20.2.5](#) and [2.20.2.11](#).
- b) Lower terminal guide rope fastenings shall
 - i) be provided with a fixed termination that retains the applied load with a factor of safety of 3
 - ii) have a means to retension the rope
 - iii) be permanently anchored.

2.23.1.7

Wire guide rope systems shall be designed to be permanently installed and extend beyond the travel path of the car such that no equipment on the car shall strike wire guide systems terminal fastenings.

2.23.1.8

A minimum of two guide ropes shall be provided.

(ED) 2.23.1.9

Guide ropes shall be replaced according to the replacement criteria of ASME A17.6, Part 4 and replacement ropes shall be new steel wire rope of the same type and grade.

2.23.1.10

Reuse of guide ropes as suspension or safety ropes is prohibited.

2.23.1.11

Guide ropes shall be positioned to prevent uncontrolled rotation of the car.

(21) 2.23.1.12

Fastenings for guide ropes shall have means to prevent threaded connections or sliding components vibrating off.

(ED) 2.23.2 Ladder guidance systems

Ladder guidance systems shall conform to [2.23.2.1](#) through [2.23.2.9](#).

2.23.2.1

Ladder guidance systems shall be of steel or aluminum. Steel shall have an elongation not less than 20% in a length of 50 mm (2 in) and aluminum shall have an elongation not less than 12% in a length of 50 mm (2 in).

2.23.2.2

Ladder guidance systems and their brackets, rail clips, fishplates, and their fastenings to the support structure shall provide a minimum factor of safety of 4 for steel and 5 for all other metals for all applicable loads.

(ED) 2.23.2.3

Guide surfaces shall be securely fastened to the ladder, and the ladder guides shall not exceed a design deflection of $L/160$ of span and the combined deflection shall not deflect more than 13 mm (0.5 in) under normal operation, and shall have their joints well-fitted and strongly secured. Guide surfaces and their joints and fastenings shall withstand without failure the application of the car safety when stopping the car with its rated load.

2.23.2.4

Guide surfaces shall extend from the bottom of the travel path to a sufficient height above the top landing to prevent the guide shoes from running off the guide surfaces when the car is at its extreme upper position.

(ED) 2.23.2.5

A means of visually monitoring the travel path of the car shall be provided from the point of manual lowering actuation means.

2.23.2.6

Emergency evacuation shall be provided through top and bottom hatches except when the elevator is guided on the nonclimbing side of the ladder and when the door opening is perpendicular to the ladder rungs.

2.23.2.7

The car shall maintain a minimum of 175 mm (7 in) clearance from the ladder rung when the travel path is on the nonclimbing side.

2.23.2.8

A sign with letters 25 mm (1 in) in height complying with ANSI Z535.2 or CAN/CSA-Z321 shall be posted at each ladder access point saying "**CAUTION:** Elevator is guided on this ladder; beware of moving equipment."*

* The equivalent French wording is "**AVERTISSEMENT** : Ascenseur ou monte-charge guidé sur cette échelle ; attention au matériel en mouvement."

(21) 2.23.2.9

Lighting shall be provided at a minimum of 50 lx (5 ftc) at the sign.

(21) 2.24 Driving machines, sheaves, and brakes

Driving machines shall be of the traction, traction climbing, or rack-and-pinion drive type and shall conform to [2.24.1](#), [2.24.2](#), or [2.24.3](#) and the applicable requirements of [2.24.4](#) through [2.24.9](#). The installation of belt-drive, winding drum, and screw drive machines are prohibited.

2.24.1 Rack-and-pinion driving machines

Rack and-pinion machines shall conform to [2.24.1.1](#) through [2.24.1.9](#).

2.24.1.1

The rack-and-pinion drive shall consist of one or more power-driven rotating pinions mounted on the car and arranged to travel on a stationary rack mounted on the supporting structure. The drive shall have at least one pinion, one rack, and two backup rollers, which shall act on the same section of rack as the drive pinion. Driving machines utilizing a two-sided rack, where two drive pinions are located so that they are opposite each other and act as backup rollers, shall be deemed to have met this requirement.

2.24.1.2

The pinions and racks shall be of steel or of material having equivalent mechanical properties or better with a minimum factor of safety of 8 for the pinion and the rack. They shall be designed to conform to AGMA 218.01, including surface hardening and an assumption of a minimum of 200 000 life cycles.

2.24.1.3

All moving parts of the driving machine shall be properly protected with solid or perforated metal that will reject a ball of 13 mm (0.5 in) diameter and shall be securely fastened.

2.24.1.4

The rack and pinion shall be so designed that the separation of the pinion from the rack in all directions in excess of 25% of the tooth depth or 6 mm (0.25 in), whichever is the lesser, cannot occur. A guard shall be provided to prevent foreign material from lodging between the teeth, and clearance between the moving parts and the guard shall not exceed 5 mm (0.1875 in).

2.24.1.5

Rack sections shall be fastened to the supporting structure with a factor of safety of 5 with dowels at each joint.

2.24.1.6

The manufacturer shall provide the measurement for checking tooth wear on pinion and rack. The measuring instruction shall be indicated on a marking plate securely fastened and conspicuously displayed in the car with letters not less than 3 mm (0.125 in) high and conform to the design requirements of [2.31.3](#).

(21) 2.24.1.7

Each drive unit shall be provided with a driving-machine brake capable of safely stopping and holding at a minimum the weight of the car at the overload value required in [2.16.4](#).

2.24.1.8

Each drive unit shall be provided with a centrifugal brake capable of safely lowering the weight of the car plus 125% of rated load.

2.24.1.9

Where a multiple drive system is provided, means shall be provided to detect failure of a drive unit and remove power from all motors and brakes.

2.24.2 Traction driving machines, sheave and brakes

Traction machines shall conform to [2.24.2.1](#) through [2.24.2.7](#).

2.24.2.1

Driving-machine sheaves shall be integral with or directly attached to driving-machine shafts. Traction sheaves shall be constructed of metal and provided with finished grooves, steel shafts, and metal bearings. Overhead or deflecting sheaves are permitted to be nonmetallic with steel shafts and metal bearings.

2.24.2.2

Traction sheaves used with suspension means shall have a pitch diameter not less than

- a) 20 times the diameter of steel wire rope where used for suspension ropes
- b) 10 times the diameter of steel wire rope where the sheave is an overhead or deflecting sheave when on the unloaded side (trailing) of the suspension rope for uncounterweighted systems.

2.24.2.3

Where steel wire rope is used and a groove is used to provide traction, sufficient traction shall be provided between the rope and groove to safely stop and hold the car with rated load from rated speed in the down direction.

2.24.2.4

In a counterweighted system, if either the car or the counterweight bottoms on its buffers or bumpers, or becomes otherwise immovable,

- a) the suspension members shall slip on the drive sheave and not allow the car or counterweight to be raised, or
- b) the driving system shall stall and not allow the car or counterweight to be raised.

2.24.2.5

A means shall be provided to retain each suspension member in its respective position on all sheaves used in the suspension of the elevator when subjected to any retardation that can cause a slackening of the suspension members.

2.24.2.6

Driving-machine components subjected to alternating or reversing stresses shall have a factor of safety not less than 1.5. This factor of safety shall be the ratio of the endurance limit of the components to the actual alternating or reversing stress to which the components can be subjected under any normal operating condition. The endurance limit shall be based on 107 cycles of stress reversals. The actual stress shall include all designed or anticipated load conditions and stress risers, such as sharp corners, shock loading, surface finish, keyways, material variations, alignment tolerances, etc.

2.24.2.7

A fillet shall be provided at any point of change in the diameter of driving-machine shafts and sheave shafts to prevent excessive stress concentrations in the shafts. Shafts that support sheaves, gears, couplings, and other members, and that transmit torque shall be provided with tight-fitting keys.

(ED) **2.24.3 Material and grooving for sheaves**

Traction sheaves for uncounterweighted traction machines shall be of cast iron or steel and of a pitch diameter not less than 20 times the diameter of the steel wire suspension ropes. The rope grooves shall be machined. Overhead and deflecting sheaves are permitted to be nonmetallic with steel shafts and metal bearings.

(ED) **2.24.3.1**

The pitch diameter shall have a pitch diameter not less than 10 times the diameter on the unloaded side (trailing) of the suspension rope for uncounterweighted systems.

(ED) **2.24.4 Factor of safety for driving machines and sheaves**

The factor of safety to be used in the design of driving machines and sheaves used with suspension means shall be not less than

- a) 8 for metals having an elongation of at least 14% in a gauge length of 50 mm (2 in) when tested in accordance with ASTM E8.
- b) 10 for cast iron or for metals having an elongation of less than 14% in a gauge length of 50 mm (2 in) when tested in accordance with ASTM E8.
- c) 10 for sheaves of plastic, fiber-reinforced plastic, or combinations thereof. The material used shall ensure that the factor of safety is not less than 8 during the service life of the sheave.

The load to be used in determining the factor of safety shall be the resultant of the maximum tensions in the suspension means leading from the sheave with the car at rest and with the rated load in the car.

(ED) **2.24.5 Bolts transmitting torque and set screws**

The threaded portions of bolts transmitting torque and set screws located in the shear plane of bolts and screws shall not be used to transmit load. Means shall be provided to ensure that there is no relative motion between rigidly joined components transmitting load.

The factors of safety to be used in the design of fasteners transmitting load in driving machines and sheaves shall be not less than those specified in [2.24.4](#).

(ED) **2.24.6 Friction-gearing or clutch mechanism**

Friction-gearing or clutch mechanisms shall not be used for connecting the drum or sheaves to the main driving mechanism.

(ED) **2.24.7 Use of cast iron in gears**

Worms and worm gears made of cast iron shall not be used.

(ED) **2.24.8 Braking system of driving machines**

The braking system shall conform to [2.24.8.1](#) through [2.24.8.7](#).

(ED) **2.24.8.1**

The elevator braking system shall be capable of decelerating the car from its rated speed when it is carrying its rated load in the down direction. The loss of main line power shall not reduce the braking system capacity.

(21) 2.24.8.2

The driving-machine brake shall be a friction brake applied by a spring or springs, or by gravity, and released electromechanically. The driving-machine brake, on its own, shall be capable of holding at a minimum the car at rest at the overload value required in [2.16.4](#).

(ED) 2.24.8.3

The driving-machine brake design shall ensure contact of the friction material on the braking surface consistent with good engineering practice. Means shall be provided to protect the braking surfaces from any leaking fluid.

(ED) 2.24.8.4

The brake setting and method of measurement shall be permanently and legibly marked on the driving machine or on the car data tag.

(ED) 2.24.8.5

Two means shall be provided to independently remove power from the brake.

(ED) 2.24.8.6

The driving-machine brake shall apply automatically when

- a) the emergency stop switch in the car is in the stop position,
- b) a normal stopping means functions,
- c) any electrical protective device is activated, or
- d) there is a loss of power to the driving-machine brake.

(ED) 2.24.8.7

The brake shall not be permanently connected across the armature or field of a direct-current elevator driving-machine motor.

(ED) 2.24.9 Means for manual release of driving machine brake

Means for manual release of the driving-machine brake shall be provided. The means shall permit car movement in a gradual, controllable manner. Provision shall be made to prevent unintended actuation of the device. The manual release device shall be designed to be hand applied only with continuous effort. The brake shall reapply at its fully adjusted capacity in the absence of the hand applied effort.

2.25 Terminal stopping devices**2.25.1 Final terminal stopping**

Final terminal stopping devices shall conform to the following except no down final switch is required for systems with driving machines that do not maintain driving force in the down direction as a result of driving machine remaining powered when landed at the bottom landing. Final terminal stopping devices shall

- a) be mechanically operated
- b) have operating cams of metal
- c) have switch contacts directly opened mechanically.

(21) 2.25.1.1

Final terminal stopping devices shall be provided and arranged to cause the electric power to be removed automatically from the elevator driving-machine motor and brake after the car has passed the upper terminal landing. The device shall be set to function as close to the terminal landing as

practicable, but so that under normal operating conditions it will not function when the car is stopped by the normal terminal stopping device.

The operation of final terminal stopping devices shall prevent movement of the car by the normal operating devices in both directions of travel.

2.25.1.2

Elevators shall have final terminal stopping switches operated by cams and shall be operated by the movement of the car. One of the assemblies (i.e., switch or cam or actuation device) shall be mounted on the car and the other in the travel path. Where the final terminal stopping switch signals are transmitted through wiring in the traveling cable, the design shall be such that any single ground or short circuit shall not render the final terminal stopping device ineffective.

2.25.1.3

The normal terminal stopping device and final terminal stopping devices shall not control the same controller devices unless two or more separate and independent controller devices are provided, two of which shall complete both the driving-machine motor and the driving-machine brake circuits in either direction of travel.

The control circuits shall be so designed and installed that a single ground or short circuit shall not prevent both the normal terminal stopping device and final terminal stopping device control circuits from stopping the car.

2.25.2 Normal terminal stopping

Normal terminal stopping devices conforming to the following shall be provided. Obstruction-detection devices (see [2.15.9](#)) shall be permitted to function as the normal terminal stopping device.

2.25.2.1

Normal terminal stopping devices shall be provided and arranged to slow down and stop the car automatically, at or near the top and bottom terminal landings, with any load up to and including rated load in the car and from any speed attained in normal operation.

2.25.2.2

Such devices shall function independently of the operation of the normal stopping means and of the final terminal stopping device, except that the normal terminal stopping device shall be permitted to be used as the normal stopping means.

2.25.2.3

The device shall be so designed and installed that it will continue to function until the final terminal stopping device operates.

(21) 2.25.2.4

Normal terminal stopping devices shall be located either on the car, in the travel path, or in a machinery space or control space and shall be operated by the movement of the car.

(21) 2.25.2.5

Normal terminal stopping devices shall be permitted to be bypassed to allow the elevator to remove tension from the suspension ropes by resting on the bottom landing platform.

2.25.3 Slack rope detection

Uncounterweighted traction drive elevators shall be provided with a slack rope switch to detect movement of the tail line weight or a slack rope condition and cause power to be removed from the driving machine and brake in the down direction. The switches shall have contacts that are positively opened mechanically; the opening shall not be solely dependent on springs, and be designed to actuate with a maximum of 100 mm (4 in) of vertical rope movement.

2.26 Operating devices and control equipment

2.26.1 Operation and operating devices

2.26.1.1 Types of operating devices

All operating devices shall be of the enclosed electric type.

(21) 2.26.1.2 Types of operation

Only the following types of operations shall be permitted: AUTOMATIC CALL, AUTOMATIC SEND, and MANUAL. Where more than one type of operation is provided, a selector switch that will not change position without a deliberate action by the user, shall be labeled "OPERATION", with its positions marked "MANUAL", "AUTO CALL", and "AUTO SEND" (as applicable) shall be provided. Only one type of operation is permitted to be enabled at any time. The letters shall be a minimum of 7 mm (0.25 in) high in color contrasting with the background located in the car.

- a) Where the operation selection switch is in the "MANUAL" position or where no operation selection switch is provided, manual operation is enabled. Operating devices shall be of the continuous pressure type and attached inside the car.
- b) Where the operating devices are on the car, accessible from outside of the car and the Operation Selection Switch is in the "AUTO SEND" position, automatic send operation is enabled. Operating devices shall be of the momentary pressure type
- c) Where the operating devices are provided at the landing platforms and the Operation Selection Switch is in "AUTO CALL" position, automatic call operation is enabled. Operating devices shall be of momentary pressure type, and landing platform doors and gates shall be subject to the requirements of [2.12](#).

2.26.1.3 Wireless operating devices

Where wireless operating devices are provided, the operating devices shall be of the continuous pressure type.

2.26.1.4 All operating devices

All operating devices shall be

- a) labeled "UP" and "DOWN," respectively, and
- b) subject to the electrical protective devices required by [2.26.2](#).

2.26.2 Electrical protective devices

When an electrical protective device is activated (operated, opened), it shall cause the electric power to be removed from the elevator driving-machine motor and brake. Electrical protective devices shall have contacts that are positively opened mechanically; the opening shall not be solely dependent on springs, and be provided as specified in [2.26.2.1](#) through [2.26.2.6](#).

2.26.2.1 Emergency stop switch

An emergency stop switch shall be provided on wind turbine tower elevators. When open ("STOP" position), this switch shall cause the electric power to be removed from the elevator driving-machine motor and brake.

Emergency stop switches shall

- a) be of the manually opened and closed type
- b) have red operating handles or buttons
- c) be conspicuously and permanently marked "STOP", and shall indicate the "STOP" and "RUN" positions.

2.26.2.2 Stop switch on top of car

A stop switch conforming to [2.26.2.1](#) shall be provided on the top of every car where maintenance or inspection is to be performed from the top of the car.

2.26.2.3 Car safety mechanism switch

A switch conforming to [2.17.4](#) shall be required where a car safety or wire rope gripping safety is provided.

2.26.2.4 Final terminal stopping devices

Final terminal stopping devices conforming to [2.25](#) shall be provided for every electric elevator.

2.26.2.5 Car door and gate electric contacts

Car door or gate electric contacts conforming to [2.14.9](#) shall be provided for all elevators.

2.26.2.6 Ladder-guided access cover switch

Ladder-guided access cover switch(es) shall be provided conforming to [2.14.9.3](#).

(21) 2.26.2.7 Trapped key electric contacts

Where provided, electric contacts in trapped key systems shall conform to [2.12.4.6\(a\)](#).

(21) 2.26.2.8 Platform door or gate switch

Where provided, mechanical locks and electric contacts shall conform to [2.12.3](#).

2.26.3 Contactors and relays for use in critical operating circuits

Where electromechanical contactors or relays are provided to fulfill the requirements of [2.26.7.3](#) through [2.26.7.6](#), they shall be considered to be used in critical operating circuits. If contact(s) on these electromechanical contactors or relays are used for monitoring purposes, they shall be prevented from changing state if the contact(s) utilized in a critical operating circuit fail to open in the intended manner. The ability of the monitoring contact(s) to perform this function shall not be solely dependent upon springs.

2.26.4 Electrical equipment and wiring

2.26.4.1

All electrical equipment and wiring shall conform to NFPA 70 or CSA C22.1, whichever is applicable, except as specified in [2.26.4.1.1](#) and [2.26.4.1.2](#).

2.26.4.1.1

Traveling and trailing cables are not required to comply with [2.26.4.1](#) and shall have the essential properties to meet all the temperature, strength, and flexibility requirements for the application in accordance with sound engineering practice and shall be certified to a testing organization standard.

2.26.4.1.2

Where a trailing cable is provided, a means at the bottom of the travel path shall be provided to collect, mechanically protect, and prevent entanglement of the cable. The means shall be capable of holding two times the weight of the cable when the car is at its lowest limit of travel.

2.26.4.2

Electrical equipment shall be listed/certified and labeled/marked. CSA B44.1/ASME A17.5 defines the scope and applicable requirements for this listing/certification.

2.26.4.3

The devices covered by [2.26.2](#) shall have contacts that are positively opened mechanically; their opening shall not be solely dependent on springs.

2.26.4.4

Control equipment shall be tested in accordance with the testing requirements of BS EN 12016 by exposing it to interference levels at the test values specified for "safety circuits." The interference shall not cause any of the conditions described in [2.26.8.1](#) and [2.26.8.2](#) and shall not cause the car to move while on inspection operation.

- a) The test for voltage dips in Table 6 of BS EN 12016 shall be conducted by either using the times specified in Table 6, or using a voltage reduction of 30% of the nominal input voltage for 0.5 cycles at 60 Hz and a voltage reduction of 60% of nominal input voltage for 5 cycles at 60 Hz.
- b) If enclosure doors or suppression equipment must remain installed to meet the above requirements, warning signs to that effect shall be posted on the control equipment.

Note: ([2.26.4.4](#)) The test requirements for voltage dips in [2.26.4.4\(a\)](#) are adjusted for 60 Hz operation.

2.26.5 Phase protection of motors

Elevators having a polyphase AC power supply shall be provided with means to prevent the starting of the elevator drive motor if a reversal of phase rotation or phase failure of the incoming polyphase AC power will cause the car to operate in the wrong direction.

2.26.6 Installation of capacitors or other devices to make electrical protective devices ineffective

The installation of capacitors or other devices, the operation or failure of which will cause an unsafe operation of the elevator, is prohibited.

2.26.7 Control and operating circuits

2.26.7.1

If springs are used to actuate switches, contactors, or relays to break the circuit to stop the car at the terminal landings, they shall be of the compression type.

2.26.7.2

The completion or maintenance of an electric circuit shall not be used to interrupt the power to the elevator driving-machine motor or brake at the terminal landings nor to stop the car when any of the electrical protective devices operate. Requirement [2.26.7.2](#) does not apply to dynamic braking.

2.26.7.3

The occurrence of a single ground or the failure of any single magnetically operated switch, contactor, or relay, or any single solid-state device not a part of a software system shall not permit the car to move if any electrical protective device is not in the closed position. Use of software systems are permitted, provided that a nonsoftware-controlled means is also used to remove power from the driving-machine motor and brake.

2.26.7.4

Methods used to satisfy [2.26.7.3](#) shall be checked prior to each start of the elevator. When a single ground or failure as specified in [2.26.7.3](#) occurs, the car shall not be permitted to restart.

2.26.7.5

Elevators employing alternating-current driving motors driven from a direct-current power source through a static inverter shall have two separate means provided to independently inhibit the flow of alternating current through the solid-state devices that connect the direct-current power source to the alternating-current driving motor by an electromechanical relay arranged to

- a) open each time the car stops, or
- b) open, at the latest, each time the car reverses direction and it has been verified at each stop that there is no current flow exceeding normal leakage current through the other means.

The means used for conformance to [2.26.7.5](#) shall cause power to be removed from the driving-machine brake circuit.

2.26.7.6

Where relays are used to satisfy [2.26.7.3](#), after each time the relay is required to open in conformance with [2.26.7.4](#), the car shall not respond to a signal to start unless the relay that inhibits the flow of alternating current through the solid-state devices, as well as the contactors in the brake circuit, are in the de-energized position. After each stop in conformance to [2.26.7.5](#), the car shall not respond to a signal to start if current flow exceeding normal leakage current through the other means is detected.

2.26.7.7

The control circuits shall be so designed and installed that the car speed in the down direction with rated load in the car, under normal operating conditions with the power supply on or off, shall not exceed 125% of rated speed.

2.26.8 Release and application of driving-machine brakes

2.26.8.1

Driving-machine brakes shall not be electrically released until power has been applied to the driving-machine motor.

2.26.8.2

Two devices shall be provided to independently remove power from the brake. If the brake circuit is ungrounded, all power feed lines to the brake shall be opened.

2.26.8.3

The driving-machine brake shall apply automatically when

- a) the operating device of a pressure-operation elevator is in the stop position
- b) a normal stopping means functions
- c) any electrical protective device is activated
- d) there is a loss of power to the driving-machine brake.

2.27 Emergency operation and signaling devices

Wired or wireless two-way communication between elevator personnel and a location staffed by authorized personnel attended while the tower is occupied shall be provided.

2.28 Layout drawings

Elevator layout drawings shall, in addition to other data, indicate the following:

- a) the maximum bracket, wire fix, or tie-in spacing
- b) the estimated maximum vertical forces on application of the safety or other retarding device to the safety wire
- c) the total static and impact loads imposed on machinery and sheave beams, supports, and floors or foundations
- d) the impact load due to buffer or bumper engagement at the maximum permissible speed and load
- e) the total static and dynamic loads from the ropes and tension system
- f) the horizontal forces imposed on the tower structure
- g) for wire guided systems, tension loads on the bottom attachment point
- h) the car dimensions and minimum required through-platform clearances.

(ED) 2.29 Welding

2.29.1 Qualification of welders

Where required in ASME A17.1/CSA B44, welding of parts, except for tack welds later incorporated into finished welds, shall be undertaken

- a) by welders qualified in accordance with the requirements of Section 4 of ANSI/AWS D1.1, whereby the welders shall be qualified by the manufacturer or contractor; a professional consulting engineer; or a recognized testing laboratory, or
- b) by a fabricator qualified to the requirements of CSA W47.1, whichever is applicable.

2.29.2 Welding steel

Where required in ASME A17.1/CSA B44, welding shall conform to either of the following, whichever is applicable:

- a) the design and procedure requirements of the applicable section of ANSI/AWS D1.1 or ANSI/AWS D1.3, or
- b) the design and procedure requirements of CSA W59.

2.29.3 Welding metals other than steel

Where required in ASME A17.1/CSA B44, welding of materials other than steel shall be done in accordance with the latest AWS or CSA Group requirements applicable to the specific materials used.

(21) 2.30 Engineering tests, type tests, and certification requirements

2.30 covers:

- a) type of tests and certifications of
 - 1. hoistway door combination mechanical locks, electric contracts, and door or gate electric contacts, as required in [2.12](#)
 - 2. car door or gate electric contacts, and car door interlocks as required in [2.14.11](#)

2.30.1 General requirements for tests and certifications**2.30.1.1 General**

- a) Type tests (see [1.3](#)) shall be carried out when required.
- b) Engineering test (see [1.3](#)) shall be carried out when required.
- c) The tests shall be permitted to be made by laboratories other than the certifying organization or manufacturers, but the responsibility shall remain with the original certifying organization.

2.30.1.2 Application for certification**2.30.1.2.1**

The application for engineering or type tests shall be made by the component manufacturer, equipment manufacturer, installer, or importer.

2.30.1.2.2

The application shall include

- a) the manufacturer's name and the equipment or component designation or model
- b) two sets of assembly and detail drawings showing details as specified in ASME A17.1/CSA B44 8.3 or Section [2.30](#).
- c) a description of the elevator component or equipment, and its field of application, along with calculated performance features

2.30.1.3 Certification and test records**2.30.1.3.1**

A certificate shall be issued for a component or equipment that has been successfully tested.

The certificate shall include

- a) the name of the applicant (see [2.30.1.2.1](#))
- b) the name of the manufacturer
- c) the manufacturer's designation of the type or model tested
- d) the certifying organization's label/mark and the method of affixing the label/mark to each component or each piece of equipment subsequently manufactured, where required
- e) the method of testing, the test report, and a list of the instruments used (Note: this may be attached to the certificate)
- f) the conditions for use of the certificate and label/mark
- g) a statement to the effect that the component or equipment tested has met the specified test requirements
- h) any other information required in ASME A17.8/CSA B44.8 or the requirements of the jurisdiction where the elevator is being installed
- i) the edition of the Code under which the component was tested and certified

2.30.1.3.2

The certificate shall be valid until recalled by the certifying organization or until the applicable requirements in ASME A17.8/CSA B44.8 or the requirements of the jurisdiction where the elevator is being installed are changed unless otherwise stated (see [2.30.1.4](#)).

2.30.1.3.3

The drawings and other documents submitted by the applicant (see [2.30.1.2](#)), together with the original test records, data, performance curves, and certificate shall be filed, as a permanent record for future reference.

2.30.1.3.4

The applicant shall be permitted to examine and copy the test records upon request.

2.30.1.4 Changes to listed/certified components or equipment

2.30.1.4.1

Where any change is made in the design of the component or equipment after certification, including changes resulting from the revisions in applicable code requirements, revised drawings showing such changes shall be filed with the original or other certifying organization. The certifying organization shall issue to the applicant a revised certificate, based upon the previous test results or any new tests that are needed, depending on the nature of the changes.

2.30.1.4.2

Changes in the design that do not affect the performance of the component or equipment shall be permitted to be made without the approval of the certifying organization. The certifying organization shall be apprised in writing of the change.

2.30.1.5 Testing instruments

The precision of the instruments shall allow measurements to be made, unless otherwise specified, within the following tolerances:

- a) $\pm 1\%$ - masses, forces, distances, time, speeds, and hydraulic pressure
- b) $\pm 2\%$ - accelerations, retardations, and flow rating
- c) $\pm 5\%$ - voltages and currents
- d) $\pm 10\%$ - temperatures

2.30.2 Type tests of interlocks, combination mechanical locks and electric contacts, and door or gate electric contacts

2.30.2.1 General

This section specifies the type test of hoistway door interlocks, car door interlocks, combination mechanical locks and electric contacts, and hoistway door and car door or gate electric contacts.

2.30.2.2 Examination before test

Prior to testing, the certifying organization shall examine each device submitted to ascertain that it conforms to the applicable requirements in Part 2.

2.30.3 General requirements

2.30.3.1 Connections for and test of electrical parts

During the test specified by Section 2.30, the devices shall have their electrical parts connected in a noninductive electrical circuit having a constant resistance and in which a current of twice the rated current at rated voltage is flowing. The electric circuit shall be closed, but shall not be broken at the contact within the device on each cycle of operation during the tests.

2.30.3.2 Retesting of electric contacts previously tested

If the electric contact of a device submitted for test has already been tested as part of another device, and has successfully met the test requirements (see ASME A17.1/CSA B44 8.3.3 or Section 2.30), the electrical tests of the contact need not be repeated.

2.30.3.3 Tests of platform enclosure gate combination mechanical locks and electric contacts

The testing equipment shall actuate the mechanical locking members of combination mechanical locks and electric contacts to unlock at each cycle of operation during the tests specified by 2.30.4.1, 2.30.4.3 and 2.30.4.4.

2.30.4 Required tests and procedure

Each device submitted shall be subjected to, and shall successfully pass, the following tests.

2.30.4.1 Endurance test

The device, lubricated in accordance with the manufacturer's instructions, shall complete 25 000 cycles of operation without failure of any kind, without excessive wearing or loosening of parts, or without undue burning or pitting of the contacts (see 2.30.2.1).

2.30.4.2 Current interruption test

After completion of the test specified by 2.30.4.1, the device used therein shall satisfactorily complete the following additional tests, to check that the ability to break alive circuit is adequate.

The tests shall be carried out with the locking device located in accordance with the manufacturer's drawings. If several positions are indicated, the test shall be made in the position that the laboratory judges to be the most favorable.

The sample tested shall be provided with covers and electrical wiring in accordance with the manufacturer's drawings.

- a) AC rated locking devices shall have their electrical parts connected to an inductive circuit with a power factor of 0.7 ± 0.05 in which a current of 11 times the rated current, at 110% of rated voltage, is flowing. The AC locking devices shall open and close 50 times, at normal speed, and at intervals of 5 s to 10 s, with the contact remaining closed for at least 0.5 s.
- b) DC rated locking devices shall have their electrical parts connected to an inductive circuit in which the current reaches 95% of the steady state value of 110% of the rated current in 0.3 s maximum, at 110% of rated voltage. The DC locking devices shall open and close 20 times, at normal speed, and at intervals of 5 s to 10 s, with the contact remaining closed for at least 0.5 s.
- c) The test results are considered satisfactory if no evidence of insulation breakdown due to arcing or tracking occurs and if no deterioration occurs that could adversely affect safety.

2.30.4.3 Test without lubricant

After completion of the test specified by [2.30.4.2](#), the device used therein shall be used for this test.

The devices, except self-lubricating bearings and bearings of a type not requiring frequent replenishment of lubricant, shall then be taken apart and freed of lubricant by washing in nonflammable liquids having cleansing characteristics.

After reassembling, the device shall, without other than the usual initial adjustment (i.e., without adjustment especially made to meet the conditions of the particular test) and without further attention, complete 20 000 cycles of operation without failure of any kind, without excessive wearing or loosening of parts, and without undue burning or pitting of contacts.

2.30.4.4 Test in moist atmosphere

Where wind turbines are located at sea, after completion of the test specified by [2.30.4.3](#), the device used therein shall be used for this test.

The device shall be subjected continuously, in an unventilated enclosure, to an atmosphere saturated with a range of 3.5% to 5% solution of sodium chloride for 72 consecutive hours. During this period, it shall be operated for only 10 consecutive cycles at the end of each of the first two 24 h periods and shall be allowed to stand exposed to the air for 24 h, and shall not fail in a manner that creates an unsafe condition.

The device shall again be lubricated and shall, without adjustment and without further attention, complete 10 000 cycles of operation without failure of any kind.

2.30.4.5 Misalignment test

- a) All types of doors – the device shall operate effectively when the cam or other equivalent operating device used in making the test has been displaced horizontally from its normal position (the position in which it was when the device was installed) successively as follows:
 1. in a direction perpendicular to the plane of the door opening
 - a. backward 6 mm (0.25 in)
 - b. forward 6 mm (0.25 in)
 2. in a direction parallel to the plane of the door opening
 - a. to the right 6 mm (0.25 in)
 - b. to the left 6 mm (0.25 in)
- b) Horizontally sliding doors – the device shall operate effectively
 1. when the bottom of the door has been displaced horizontally from its normal position in a direction perpendicular to the plane of the door opening
 - a. backward 6 mm (0.25 in)
 - b. forward 6 mm (0.25 in)
 2. when the top of the door has been displaced horizontally from its normal position in a direction perpendicular to the plane of the door opening
 - a. backward 3 mm (0.125 in)
 - b. forward 3 mm (0.125 in)
- c) Swinging doors – the device shall operate effectively when the strike edge of the door has been displaced
 1. perpendicular to the plane of the door opening
 - a. forward 3 mm (0.125 in)
 - b. backward 3 mm (0.125 in)

2. parallel to the place of the door opening
 - a. 3 mm (0.125 in) to the right
 - b. 3 mm (0.125 in) to the left
 - c. 3 mm (0.125 in) up
 - d. 3 mm (0.125 in) down

2.30.4.6 Insulation test

The insulation of the electrical parts shall withstand a test with a root-mean square (effective) voltage twice the rated voltage plus 1 000 V, 60 HZ, applied for 1 min.

2.30.4.7 Static test

After completion of the endurance test in [2.30.4.1](#), a type test shall be made consisting of a static force applied over a period of 300 s with the force increasing incrementally. The force shall be applied in the opening direction of the door and at a location as near to the locking element as possible, but not to exceed 300 mm (12 in). The force shall be 1 000 N (225 lbf) applied at right angles to the panel evenly distributed over an area 5 cm² (0.78 in²) in round or square section in the case of a locking device intended for use with swinging doors.

2.30.4.8 Examination of electrical spacings

The electrical spacing shall comply with requirements of the jurisdiction where the elevator is being installed.

2.30.4.9 Examination of operation

It shall be verified that there is at least 7 mm (0.28 in) engagement of the locking elements before the hoistway door interlock contact closes.

2.30.4.10 Testing of bridging means

The electrical contact bridging means shall be tested to verify conformance to [2.12.3](#).

(21) 2.31 Code data plate

2.31.1 Required information

A data plate shall be provided and maintained for each elevator. The data plate shall indicate the Code and edition in effect at the time of installation. The data plate shall also indicate the Standard in effect at the time of any alteration and indicate the applicable requirements of the alteration.

2.31.2 Location

The data plate shall be in plain view, securely attached to the main line disconnect or controller.

2.31.3 Material and construction

The data plate shall be of such material and construction that the letters and figures stamped, etched, cast, or otherwise applied to the face shall remain permanently and readily legible. The height of the letters and figures shall be not less than 3 mm (0.125 in).

All data plates not located in the controller shall be provided with either

- a) a durable means to prevent common contaminants (such as paint, adhesives, oil, and grease) from adhering to the data plate parent surface and permit the removal of these contaminants, without obscuring the Standard required data, or

- b) letters and figures that are raised or depressed a minimum of 0.8 mm (0.03125 in) from the plate surface face, and have a minimum character-stroke width of 0.5 mm (0.02 in).

If the plates are exposed to weathering or a chemical atmosphere, then a durable means shall be provided to protect the information from deterioration while permitting the information to be easily read.

(21) **3 Maintenance, repair, replacement, testing, and alterations**

Part 3 applies to maintenance, repairs, replacements, testing, and alterations. Maintenance, repair and replacement shall be performed to provide compliance with the code applicable at the time of the installation or alteration.

3.1 Maintenance

Maintenance Equipment covered within the scope of this Standard shall be maintained in accordance with [3.1](#).

3.1.1 General maintenance requirements

A written Maintenance Control Program (MCP) shall be in place to maintain the equipment in compliance with the requirements of [3.1](#). The MCP shall specify examinations, tests, cleaning, lubrication, and adjustments to applicable components at regular intervals (see definition for maintenance) and shall comply with the following:

- a) An MCP for each unit shall be provide by the person(s) and/or firm maintaining the equipment and shall be viewable on-site by elevator personnel at all times from time of acceptance inspection and test or from the time of equipment installation or alteration.

Note: [\[3.1.1\(a\)\]](#)

- 1) "On-site" means inside the wind turbine tower or at the management building.
 - 2) When the "on site" MCP is maintained at the management building, the inspector should review the records prior to accessing the tower for inspection.
- b) The MCP shall include, but not be limited to, the Code required maintenance tasks, maintenance procedures, and examinations and tests listed with the associated requirement (see [3.1.4](#) through [3.1.6](#)). When maintenance tasks, maintenance procedures, or examinations or tests have been revised in [3.1](#), the MCP shall be updated.
 - c) The MCP shall reference On-site Equipment Documentation needed to fulfill [3.1.1.1](#) and On-Site Maintenance Records that record the completion of all associated maintenance tasks specified in [3.1.5](#).
 - d) Where the MCP is maintained remotely from the machinery space or control space, instructions for on-site locating or viewing of the MCP either in hard copy or in electronic format shall be posted on the controller. The instructions shall be permanently legible with characters a minimum of 3 mm (0.125 in) in height.
 - e) The specified scheduled maintenance intervals (see [1.3](#)) shall, as applicable be based on
 - 1) equipment age, condition, and accumulated wear
 - 2) design and inherent quality of the equipment
 - 3) usage
 - 4) environmental conditions
 - 5) improved technology
 - 6) the manufacturer's recommendations and original equipment certification for any SIL rated devices or circuits
 - 7) the manufacturer's recommendations based on any ASME A17.7/CSA B44.7 approved components or functions

- f) Procedures for tests, periodic inspections, maintenance, replacements, adjustments, repairs, and alternative test methods shall be incorporated into and made part of the MCP.

3.1.1.1 On-site documentation

The following documents shall be written and permanently accessible on-site in the elevator, tower, or management building for all units for elevator personnel.

- a) Up-to-date wiring diagrams detailing circuits of all electrical protective devices (see [2.26.2](#)) and critical operating circuits (see [2.26.3](#)).
- b) Procedures for inspections, tests, and/or methods required for elevator personnel to perform maintenance, repairs, replacements, and adjustments, as follows:
 - 1) All procedures specifically identified in the code as required
 - 2) Unique maintenance procedures or methods required for inspection, tests, and replacement of equipment applied under alternative arrangements shall be provided by the manufacturer or installer,
 - 3) Unique maintenance procedures or methods required for inspection and test of equipment specified in an ASME A17.7/CSA B44.7 Code Compliance Document (CCD).

3.1.1.2

Where a defective part directly affecting the safety of the operation is identified, the equipment shall be taken out of service until the defective part has been adjusted, repaired, or replaced.

3.1.2 Maintenance personnel

Maintenance, repairs, replacements, tests and alterations shall be performed only by elevator personnel.

3.1.3 Maintenance records

Maintenance records shall document compliance with [3.1](#). Instructions for locating the maintenance records of each unit, for viewing on site, shall be posted on the controller or in the car. The provided instructions shall be permanently legible with the characters a minimum of 3 mm (0.125 in) in height. These records shall be retained for the most recent 5 years or from the date of installation or adoption of this Standard edition, whichever is less or as specified by the authority having jurisdiction. Existing maintenance records up to 5 years shall be retained.

3.1.3.1 On-site maintenance records

3.1.3.1.1 Maintenance control program records

- a) The records shall document compliance with Part 3 and include the specified scheduled intervals for each maintenance task, examination, adjustment, and as applicable, be based on the criteria given in [3.1.1](#). Maintenance records up to 5 years shall be accessible at the controller or at the management building.
- b) The specified scheduled maintenance intervals (see [1.3](#)) shall, as applicable, be based on the criteria given in [3.1.1\(e\)](#).
- c) The records shall be viewable on-site by elevator personnel in either hard copy or electronic format and shall include, but not limited to, the following:
 - 1) site name and address,
 - 2) service provider name,
 - 3) conveyance identification (ID) and type,
 - 4) date of record,

- 5) a description of the maintenance task, interval, and associated requirements of [3.1](#),
- 6) indication of completion of maintenance task.

Note: [3.1.3.1(a)] Recommended format for documenting Maintenance Control Program records can be found in Annex B (informative). This is only an example format. A specific maintenance control program that includes all maintenance needs is required for each unit.

3.1.3.1.2 Repair and replacement records

All repairs and replacements shall be recorded, including but not limited to any

- a) trapped keys system or gate interlock,
- b) guide ladders,
- c) doors
- d) gates, or
- e) listed/certified devices.

The record shall include an explanation of the repair or replacement, date, and name of person(s) and/or firm performing the task.

3.1.3.1.3 Permanent record

A permanent record of the results of all acceptance tests as required by [3.6](#) shall be kept with the on-site records. Test tags shall be provided and permanently attached to or adjacent to the controller.

3.1.3.2 Call backs (trouble calls)

A record of callbacks shall be maintained and shall include the description of reported trouble, dates, time, and corrective action(s) taken that are reported by any means to elevator personnel. These records shall be made available to elevator personnel when performing corrective action. For elevator personnel other than personnel performing the corrective action, records will be available upon request. Instructions on how to report any need for corrective action (trouble calls) to the responsible party shall be posted on the controller or at the means.

3.1.4 Code data plate

The Code data plate shall comply with [2.31](#).

3.1.5 General maintenance methods and procedures

3.1.5.1 Making safety devices inoperative or ineffective

No person shall at any time make inoperative or ineffective any device on which safety of users is dependent, including any electrical protective device, except where necessary during tests, inspections (see [3.6](#) and [3.7](#)), maintenance, repair, and replacement, provided that the installation is first removed from normal operation. Such devices shall be restored to their normal operating condition in conformity with the applicable requirements prior to returning the equipment to service.

3.1.5.2 Lubrication

All parts of the machinery and equipment requiring lubrication shall be lubricated with lubricants equivalent to the type and grade recommended by the manufacturer. Alternative lubricants shall be permitted when intended lubrication effects are achieved. All excess lubricant shall be cleaned from the equipment. Containers used to catch leakage shall not be permitted to overflow.

3.1.5.3 Controllers and wiring

3.1.5.3.1

The interiors or controllers and their components shall be cleaned when necessary to minimize the accumulation of foreign matter that can interfere with the operation of the equipment.

3.1.5.3.2

Temporary wiring and insulators or blocks in the armatures or poles of magnetically operated switches, contactors, or relays on equipment in service shall be prohibited.

3.1.5.3.3

When jumpers are used during maintenance, repairs, or testing, all jumpers shall be removed and the equipment tested prior to returning it to service. Jumpers shall not be stored in the tower.

Note: ([3.1.5.3.3](#)) See "Elevator Industry Field Employees' Safety Handbook" for jumper control procedures

3.1.5.3.4

Control and operating circuits and devices shall be maintained in compliance with applicable Code requirements.

3.1.5.3.5

Substitution of any wire or current-carrying device for the correct fuse or circuit breaker in an elevator circuit shall be prohibited.

3.1.5.4 Painting

Care shall be used in the painting of the equipment to make certain that it does not interfere with the proper functioning of any component. Painted components shall be tested for proper operation upon completion of painting.

3.1.5.5 Fire extinguishers

Class "ABC" fire extinguishers shall be provided and located convenient to the tower entrance door.

3.1.5.6 Workmanship

Care shall be taken during operations such as torqueing, drilling, cutting, and welding to ensure that no component of the assembly is damaged or weakened. Rotating parts shall be properly aligned.

3.1.5.7 Signs and data plates

Required signs and data plates that are damaged or missing shall be repaired or replaced.

3.1.6 Periodic tests

The frequency of periodic tests shall be established by the authority having jurisdiction.

3.1.6.1 Witnessing tests

Periodic tests shall be witnessed by an inspector employed by the authority having jurisdiction or by a person authorized by the authority having jurisdiction. The inspector shall conform to the requirements of [3.7.2](#).

3.1.6.2 Periodic test record

A periodic test record for all periodic tests containing the applicable Code requirement(s) and date(s) performed, and the name of the person or firm performing the test, shall be permanently accessible in the MCP or installed to be readily visible and adjacent to or securely attached to the controller of each unit in the form of a metal tag or other format designated by and acceptable to the authority having jurisdiction. If any of the alternative test methods contained in [3.7.4.1](#) were performed, then the test tag must indicate alternative testing was utilized for the applicable requirement.

3.1.6.3

No person shall at any time make any required safety device or electrical protective device ineffective, except where necessary during tests. Such devices shall be restored to their normal operating condition in conformity with the applicable requirements prior to returning the equipment to service.

3.2 General repair requirements

Repairs shall be made with parts of at least equivalent material, strength, and design.

3.2.1 Applicable codes

Maintenance shall conform to the applicable

- a) Code at the time of installation; and
- b) Code requirements at the time of any alteration.

3.2.2 Welding and design

Welding and design of welding shall conform to [3.5.4](#).

3.2.3 Repair of suspension, guide, and safety ropes

Suspension, guide, and safety ropes shall not be lengthened or repaired by splicing.

3.2.4 Repair of safety

Where a repair is made to a car or counterweight safety device that affects the tripping linkage or speed adjustment mechanism, the safety shall be tested. A test tag shall be attached indicating the date the test was performed.

3.3 General replacement requirements

3.3.1 Replacement parts

Replacements shall be made with parts of at least equivalent materials, strength, and design.

3.3.2 Replacement suspension, guide, and safety rope

Suspension, guide, and safety ropes shall be replaced when they no longer conform to the applicable requirements of ASME A17.6, manufacturer's recommendations using sound engineering practice, or the equivalent standard of the jurisdiction where the elevator is being installed.

3.3.2.1 Suspension, guide, or safety ropes

Suspension, guide, and safety ropes shall be of the same size, materials, and construction as the rope specified and installed by the manufacturer and comply with [2.20](#).

3.3.2.2

A new rope data tag conforming to [2.20](#) shall be installed at each rope replacement, and the date of the rope replacement shall be recorded in the maintenance records.

3.3.2.3

When suspension and safety ropes are replaced, safety devices shall be tested as required by [3.7.4.2](#).

3.3.3 Replacement of car or counterweight safety

When a safety is replaced, it shall conform to [2.17](#) and [3.7.3.1](#).

3.3.4 Replacement of driving machine

When a driving machine is replaced, it shall conform to [2.24](#).

3.3.5 Replacement of controller

When a motion controller or operational controller is replaced, it shall conform to [2.26](#).

3.3.6 Listed/certified devices

3.3.6.1

Where a listed/certified device is replaced, the replacement shall be subject to the applicable engineering or type test as specified in Section [2.30](#) or the requirements of CSA B44.1/ASME A17.5 (see Section 1.4) or the equivalent standard of the jurisdiction where the elevator is being installed. Combination mechanical lock and electric contact, and door or gate electric contact, shall conform to the type tests specified in [2.30.1](#). The device shall be labeled by the certifying organization (see [2.30.1.3.1](#)).

3.3.6.2

Where a component in a listed/certified device is replaced, the replacement component shall be subject to the requirements of the applicable edition of CSA B44.1/ASME A17.5 (see Section 1.4) or the equivalent standard of the jurisdiction where the elevator is being installed and/or the engineering or type test in ASME A17.1/CSA B44.8.3 or Section [2.30](#). Combination mechanical lock and electric contact, and door or gate electric contact, shall conform to the type tests specified in [2.12.3](#). The component shall be included in the original manufacturer's listed/certified device documentation or as a listed/certified replacement component (see [3.1](#)).

Each replacement component shall be plainly marked for identification in accordance with the certifying organization's procedures.

Note: ([3.3.6.2](#)) Devices that may fall under this requirement are included but not limited to travel path gate locking devices and electric contacts, car door contacts and interlocks, and electrical equipment.

3.4 Maintenance and testing of wind turbine tower elevators

3.4.1 Suspension means

The maintenance and testing of wind turbine tower elevators shall conform to [3.4](#).

3.4.1.1

Suspension means shall be kept sufficiently clean so that they can be visually inspected.

3.4.1.2

Steel wire ropes shall be lightly lubricated. Precautions shall be taken in lubricating suspension steel wire ropes to prevent the loss of traction. Lubrication shall be in accordance with instructions on the rope date tag.

3.4.2 Wire rope gripping safeties

Safety mechanisms shall be kept lubricated and free of rust, corrosion, and dirt that can interfere with the operation of the safety.

3.4.2.1

The required clearance between the safety jaws and the rail shall be maintained where Type A or Type B safeties are provided.

3.4.3 Brakes

3.4.3.1

The driving-machine brake shall be maintained to ensure proper operations, including, but not limited to the following:

- a) residual pads (antimagnetic pads)
- b) lining and running clearances
- c) pins and levers
- d) springs
- e) sleeves and guide bushings
- f) discs and drums
- g) brake coil and plunger

3.4.3.2

If any part of the driving-machine brake is changed or adjusted that can affect the holding capacity or decelerating capacity of the brake when required (see [2.24.8.3](#)), it shall be adjusted and checked by means that will verify its proper function and holding capacity. A test complying with [3.7.4.1](#) shall be performed.

3.4.4 Car and counterweight safeties

Wire rope gripping safeties with slack rope actuation, or wire rope gripping safeties with an internal centrifugal governor shall be tested with rated load in the car. Counterweight safety tests shall be made with no load in the car. Tests for governor operated safeties shall be made by manually tripping the governor at the rated speed. The overspeed switch on the governor shall be made ineffective during the test. Type A safeties and wire rope gripping safeties without governors that are operated as a result for the breaking or slackening of the hoisting ropes shall be tested by obtaining the necessary slack rope to cause it to function and hold the car with rated load. The following operational conditions shall be checked.

Centrifugal governors that do not have a dropping jaw shall be tested by engaging the flyweight into the actuating device before starting the car down and running the car down until the machine stalls or drives through the hoisting ropes or shall be subjected to an overspeed test with the suspension rope(s) attached by gradually increasing the speed of the car until the governor causes application of the safety.

Rack and pinion safeties shall be subjected to overspeed testing, by gradually increasing the speed of the car until the governor causes application of the safety.

3.4.5 Tests without load via alternative test methodologies

3.4.5.1 Where permitted

Alternative test methods without load are permitted for testing subject to approval by the authority having jurisdiction of

- a) car and counterweight safeties per [3.7.4.3](#),
- b) driving-machine brakes per [3.7.4.1](#), and
- c) braking system, traction, and traction limits per [3.7.4.2](#).

3.4.5.2 Alternative test method and tools

3.4.5.2.1

An alternative test method shall be

- a) based on sound engineering principles
- b) validated and documented via engineering tests

3.4.5.2.2

The method, measuring devices, and tools shall be capable of producing reliable and consistent measurements, suitable for the intended measurement. The monitoring and calibration of the measuring devices or tools shall be in accordance with the provider's guidelines.

3.4.5.3 Alternative test method procedure

The alternative test method shall

- a) include requirements to obtain and verify car and counterweight masses if necessary for the test
- b) have a procedure document that
 - 1. defines the permissible equipment range and limitations regarding use
 - 2. establishes monitoring and calibration criteria for tools or measuring devices as appropriate
 - 3. defines the test set-up procedure
 - 4. provides instructions on how to interpret results and correlate the results to pass-fail criteria
- c) describe how to correlate no load test results with previously acquired full load and no load results
- d) be included in the maintenance control program (see [3.1.1](#))
- e) include the information required by [3.1.1\(f\)](#) where applicable, and
- f) require a report conforming to [3.4.5.4](#).

3.4.5.4 Alternative test method report

The alternative test method report shall

- a) identify the alternative test tool (make/model) used to perform the test
- b) identify the company performing the tests, names of personnel conducting and witnessing the tests, and testing dates
- c) contain all required printouts or record of tests required to demonstrate compliance to the testing requirement that were gathered during an acceptance test
- d) identify which results from the baseline test are to be used for future compliance evaluation
- e) record the car and counterweight masses that were obtained per [3.4.5.3\(a\)](#) during the acceptance test and during any subsequent Category 5 test if required by test method
- f) contain all subsequent Category 5 results with pass-fail conclusions regarding Code compliance
- g) remain on site or shall be available to elevator personnel and the authority having jurisdiction

3.5 Alterations

3.5.1 Applicability of alteration requirements

When any alteration is performed, regardless of any other requirements of [3.5](#), the installation, as a minimum, shall conform to the following applicable Code requirements:

- a) the Code at the time of the installation
- b) the Code requirements for the alteration at the time of the alteration

3.5.2 Items not covered in [3.5](#)

Where an alteration not specifically covered in [3.5](#) is made, it shall not diminish the level of safety below that which existed prior to the alteration. See also [1.2.1](#).

3.5.3 Testing

Where alterations are made, acceptance inspections and tests shall be conducted as required by [3.6](#).

3.5.4 Welding

Welding of parts on which the support of the car, counterweight, or driving machines depends shall conform to [2.29](#) and [3.5.5](#).

3.5.5 Design

Design shall be verified by a licensed professional engineer for welding, repair, cutting, or splicing of members upon which the support of the car or counterweight, depends.

3.5.6 Temporary wiring

During alterations, temporary wiring shall be permitted. The electrical protective devices of cars in normal operation shall not be rendered inoperative or ineffective.

3.5.7 Repairs and replacements

Repairs and replacements shall conform to [3.2](#) and [3.3](#).

3.5.8 Code data plate

A data plate shall be provided conforming to [2.31](#) and shall include the code and edition in effect at the time of alteration and the requirements in [3.5](#) that were applicable to any alteration.

3.5.9 Location and guarding of counterweights

Where new counterweights are installed or where counterweights are relocated, their location, guarding, and clearances shall conform to [2.3](#).

3.5.10 Vertical car and counterweights clearances and runbys

No alteration shall reduce any clearance or runby below that required by [2.4](#).

3.5.11 Horizontal car and counterweight clearances

No alteration shall reduce any clearance below that required by [2.5](#).

3.5.12 Machinery spaces, and control spaces

Where an alteration consists of the construction of new machinery spaces, or control spaces, it shall conform to [2.7](#). Electrical equipment clearances shall conform to NFPA 70 or CSA C22.1, or the

equivalent standard of the jurisdiction where the elevator is being installed whichever is applicable. Where alterations are made to any portion of machinery spaces, or control spaces, that portion which is altered shall conform to [2.7](#).

3.5.13 Machinery and sheave beams, and supports

Where new machinery and sheave beams, supports, or supporting floors are installed, relocated, or where alterations increase the original building design reactions by more than 5% they shall conform to [2.9](#) and the adequacy of the affected building structure to support the loads shall be verified by a licensed professional engineer.

3.5.14 Platform door locking devices

Where the alteration consists of the installation of platform door locking devices, the installation shall conform to [2.12](#).

3.5.15 Car enclosures, car doors and gates, and car illumination

3.5.15.1

Where an alteration consists of the installation of a new car, the installation shall conform to [2.14](#), [2.15](#), and [2.17](#).

3.5.15.2

The following requirements shall be conformed to where alterations are made to existing cars:

- a) Car enclosures shall conform to [2.14](#).
- b) Where an alteration consists of the installation of glass in an elevator car it shall conform to [2.14.3](#) and [2.14.4](#).
- c) Any alteration to car illumination or lighting fixtures shall conform to [2.14.7](#).

3.5.16 Car frames and platforms

3.5.16.1 Alterations to car frames and platforms

Where alterations are made to a car frame or platform, the frame and platform shall conform to [2.15](#).

3.5.17 Change in rated speed

3.5.17.1 Increase in rated speed

Where the alteration involves an increase in the rated speed, the following requirements shall be conformed to

- a) the top clearances for cars and counterweights shall conform to [2.4](#)
- b) horizontal clearances shall conform to [2.5](#)
- c) the driving machine and sheaves shall conform to [2.24](#)
- d) new electrical equipment, wiring, operating devices, and control equipment shall conform to [2.26](#)
- e) retardations shall conform to [2.22.3](#)
- f) where the new rated speed exceeds the rating of the safety, the safety shall conform to [2.17](#).
- g) The plate required in [2.16.2.2](#) shall reflect the change in rated speed.