

AMERICAN NATIONAL STANDARD

Solid Steel Rectangular Metal Cutting Squaring Shear Knives Dimensional Tolerances

ANSI B94.53 - 1978

Reaffirmed 1984
Reaffirmed 1984

SECRETARIAT

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

PUBLISHED BY

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

United Engineering Center

345 East 47th Street

New York, N. Y. 10017

ASMENORMDOC.COM : Click to view the full PDF of ASME B94.53 1978

No part of this document may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Copyright © 1978 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S.A.

FOREWORD

The Metal Cutting Knife Association appointed the "Standards Committee" of the Association to review the possibility of standardizing "Squaring Shear Knives."

After reviewing this program the committee notified the members of Technical Committee #17 about this proposed standard and meetings were held on October 8, 1974, April 8, 1975, October 7, 1975, March 9, 1976, September 21, 1976, December 7, 1976 and March 22, 1977.

On May 6, 1977 this Standardization Program was forwarded to the Chairman of the B94 Standards Committee, Technical Committee 17 for review and with anticipation of having it adopted as an American National Standard. This Standard was approved as an American National Standard on April 5, 1978.

AMERICAN NATIONAL STANDARDS COMMITTEE B94
Standardization of Cutting Tools, Holders, Drivers and Bushings

OFFICERS

Harry McLinden, Chairman A. M. Mezey, Vice-Chairman
Richard K. Buckley, Secretary

AMERICAN GEAR MANUFACTURERS ASSOCIATION, THE

P. M. Dean, Jr., Mechanical Technology, Inc., Latham, New York
G. L. Scott, Alternate, American Gear Manufacturers Association, Washington, D.C.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS, THE

M. E. Merchant, Dr., Cincinnati Milacron, Inc., Cincinnati, Ohio
G. M. Monacelli, General Electric Company, Detroit, Michigan
C. J. Oxford, Jr., National Twist Drill & Tool Company, Rochester, Michigan

CEMENTED CARBIDE PRODUCERS ASSOCIATION

J. A. Woodward, Teledyne Firth Sterling, Pittsburgh, Pennsylvania
A. P. Wherry, Alternate, Cemented Carbide Producers Association, Cleveland, Ohio

CUTTING TOOL MANUFACTURERS ASSOCIATION

E. J. Czapor, Falcon Tool Company, Detroit, Michigan
C. W. Jatho, Alternate, Cutting Tool Manufacturers Association, Birmingham, Michigan

GENERAL SERVICES ADMINISTRATION

W. R. Wacker, General Services Administration, Washington, D.C.

HACK AND BAND SAW MANUFACTURERS ASSOCIATION OF AMERICA

Richard Schrade, Clemson Brothers, Inc., Middletown, New York
C. M. Stockinger, Alternate, Hack & Band Saw Manufacturers Association of America, Cleveland, Ohio

METAL CUTTING TOOL INSTITUTE

W. A. Wagner, Cleveland Twist Drill Company, Cleveland, Ohio
R. M. Byrne, Alternate, Metal Cutting Tool Institute, New York, New York

NATIONAL ASSOCIATION OF PUNCH MANUFACTURERS

To Be Appointed

NATIONAL BUREAU OF STANDARDS

To Be Appointed

NATIONAL MACHINE TOOL BUILDERS' ASSOCIATION

G. F. Wilson, General Electric Company, Worthington, Ohio
E. J. Loeffler, Alternate, National Machine Tool Builders Association, McLean, Virginia

SOCIETY OF CARBIDE ENGINEERS

C. H. Lang, c/o Society of Carbide Engineers, Bridgeville, Pennsylvania

SOCIETY OF MANUFACTURING ENGINEERS

K. A. Lundell, The Product Machine Company, Jamestown, New York
Harry McLinden, Caterpillar Tractor Company, Peoria, Illinois
W. N. Moore, The Ford Motor Company, Dearborn, Michigan

TELEPHONE GROUP, THE

R. A. Agnew, Western Electric Company, Inc., Chicago, Illinois
S. P. Rogacki, Alternate, Western Electric Company, Inc., Kearney, New Jersey

U.S. DEPARTMENT OF THE AIR FORCE

To be appointed

U.S. DEPARTMENT OF THE ARMY

D. L. York, Liaison, General Thomas J. Rodman Laboratories, Rock Island, Illinois

U.S. DEPARTMENT OF THE NAVY

J. R. Ruff, Liaison, Naval Ship Systems Command, Washington, D.C.

U.S. MACHINE SCREW BUREAU

Herman Muenchinger, Continental Screw Company, New Bedford, Massachusetts

D. E. Chase, Alternate, Continental Screw Company, New Bedford, Massachusetts

INDIVIDUAL COMPANIES

Harold Cooper, Chrysler Corporation, Detroit, Michigan

Kenneth Hull, The Ingersoll Milling Machine Company, Rockford, Illinois

A. M. Mezey, Richard Brothers Punch Company, Detroit, Michigan

Lyle Storrer, Mohawk Tools, Inc., Montpelier, Ohio

INDIVIDUAL MEMBERS

Anderson Ashburn, American Machinist, New York, New York

**TECHNICAL COMMITTEE 17
ROTARY SLITTERS AND SHEAR KNIVES**

C. W. Murray, Chairman, Heppenstall Company, Pittsburgh, Pennsylvania

W. W. Burns, Stamco, Inc., New Bremen, Ohio

R. R. Ebbing, Detroit Edge Tool Company, Detroit, Michigan

F. A. Krauss, The Yoder Company, Cleveland, Ohio

S. A. Jacoby, American Shear Knife Company, W. Homestead, Pennsylvania

D. H. Turk, Production Machinery Corporation, Mentor, Ohio

C. E. Pritchard, Republic Steel Corporation, Cleveland, Ohio

L. C. Fischer, The Wapakoneta Machine Company, Wapakoneta, Ohio

J. B. Randolph, Jr., Ohio Knife Company, Cincinnati, Ohio

R. J. White, Cincinnati, Inc., Cincinnati, Ohio

R. Novy, Dreis and Krump Manufacturing Company, Chicago, Illinois

CONTENTS

	Page
Scope	1
Terminology	1
Table 1 Dimensional Tolerances of Solid Steel Rectangular, Metal Cutting Squaring Shear Knives (Inch)	3
Table 2 Dimensional Tolerances of Solid Steel Rectangular, Metal Cutting Squaring Shear Knives (Metric)	5

AMERICAN NATIONAL STANDARD

**SOLID STEEL RECTANGULAR METAL CUTTING SQUARING
SHEAR KNIVES DIMENSIONAL TOLERANCES****1. SCOPE**

This document specifies dimensions and tolerances in inches and millimeters for solid steel metal cutting squaring shear knives used for shearing ferrous and non-ferrous metals. The dimensions and tolerances together with the terminology represent within the industry practice for the manufacture, assembly and use of shear knives covered in this standard. This document contains two separate series of shear knives, a customary unit series and a metric series. The metric series are hard converted and not interchangeable with the customary product.

2. TERMINOLOGY

2.1 Gap Shear. A sheet or plate shear whose side housings have a throat or gap allowing the handling of material of a greater width than the width of the machine.

2.2. Plate Shear. A shear to cut flat rolled material $\frac{1}{4}$ " (6 mm) and thicker.

2.3 Sheet Shear. A shear to cut flat rolled material less than $\frac{1}{4}$ " (6 mm) thick.

2.4 Squaring Shear. Shear used to square plates and sheets.

2.5 Shear Capacity. Capacity of the shear expressed in maximum thickness and length of cut in mild steel. (55,000 PSI Tensile) (380 MPa).

2.6 Solid Steel Shear Knife. Knife composed of one homogeneous grade of tool steel.

2.7 Four Edge Shear Knife. Straight rectangular in section, having all four corners (edges) available for cutting.

2.8 Length. The straight line dimension from one

end of the cutting edge to the other, and the greatest dimension.

2.9 Width. The second largest external dimension on a shear knife.

2.10 Thickness. The least of the three dimensions used to identify the size of a shear knife.

2.11 Parallelism. Two surfaces following the same plane at an equal distance. The tolerances on parallelism indicate the degree of variation acceptable from the true parallel surfaces.

2.12 Squareness. Two adjacent surfaces being 90° to each other.

2.13 Tolerances. Allowable deviation from nominal dimensions.

2.14 Bow. Variation from straight plane edgewise or flatwise over full length of knife. (See Table 1.)

2.15 Flatness. Having an even surface without depressions or elevations when gauged along the same plane. Tolerance on flatness is the degree of variation acceptable from the true flat surface. (See Table 1.)

BOLT HOLES

2.16 Angle of Countersink. The included angle formed by the two opposite sides of the countersink. (Measured in degrees.)

2.17 Countersink. Enlarged conical part of a hole to allow for the head of a fastener.

2.18 Keyslot. Slot in or through hole and countersink to accommodate lug on plow bolt to prevent bolt from turning in knife.

2.19 Tapped Hole. A through-hole with internal threads to accept a thread fastener.

Cross Section Recommendations

Width (in Inches)	Thickness
2	1/2
3	3/4
3	1
4	1
5	1-1/8
5-1/2	1-1/2
6-1/2	1-3/4

Lengths

Recommended knife length should be the shearing length capacity of the shear plus the width of the knife:

Example:

4" x 1" cross section on a 10 ft. shear would be 120" plus 4" or 124" for knife length. Similarly, a 5-1/2" x 1-1/2" cross section for 10 ft. shear would be 120" plus 5-1/2" or 125-1/2" for knife length. Recommended maximum length of one piece knives should be nominal 168". Longer knives should be sectional.

Holes

The following table shows knife thickness, bolt diameter, and diameter of the bolt hole:

Knife Thickness (in inches)	Bolt Diameter (in inches)	Hole Diameter (in inches)
1/2	3/8	7/16
3/4	1/2	9/16
1	3/4	13/16
1-1/8	3/4	13/16
1-1/2	1	1-1/16
1-3/4	1	1-1/16

Hole Spacing

It is recommended that end holes should be no closer to end of knife than 1/2 the width of the knife.

Example:

4" wide knife, end holes to be 2" from end of knife minimum. Where feasible, holes to be on 8" centers.

AMERICAN NATIONAL STANDARD
SOLID STEEL RECTANGULAR METAL CUTTING
SQUARING SHEAR KNIVES

ANSI B94.53-1978




Table 1 Dimensional Tolerances in Inches of Solid Steel Rectangular Metal Cutting Squaring Shear Knives
(Dimensions in Inches)

Knife Lengths	Length	Width	Thickness	Permissible Bow Flatwise	Permissible Bow Edgewise	A Tolerance Between End Holes	B Tolerance Between Holes
12" & Shorter	± 0.031	$+ 0.000$ $- 0.031$	$+ 0.000$ $- 0.015$	0.031	0.015	± 0.031	± 0.031
Over 12" to 36"	± 0.062	$+ 0.000$ $- 0.031$	$+ 0.000$ $- 0.015$	0.062	0.015	± 0.062	± 0.062
Over 36" to 96"	± 0.125	$+ 0.000$ $- 0.031$	$+ 0.000$ $- 0.015$	0.093	0.031	± 0.125	± 0.062
Over 96" to 126"	$+ 0.125$ $- 0.187$	$+ 0.000$ $- 0.031$	$+ 0.000$ $- 0.015$	0.125	0.062	± 0.187	± 0.062
Over 126"	$+ 0.125$ $- 0.250$	$+ 0.000$ $- 0.031$	$+ 0.000$ $- 0.015$	0.250	0.062	± 0.250	± 0.062

Squareness of edge to face of knife within 0.005".

Parallelism of Knife Faces: Within 0.003" with no variation greater than 0.001" within any 12" length throughout entire length.

Parallelism of Knife Edges: Within 0.005" with no variation greater than 0.001" within any 12" length throughout entire length.