

**ASME Y14.2-2008**

**[Revision of ASME Y14.2M-1992 (R2003)]**

# **Line Conventions and Lettering**

**Engineering Drawing and Related  
Documentation Practices**

ASMENORMDOC.COM : Click to view the full PDF of ASME Y14.2-2008

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**



## ADOPTION NOTICE

ASMEY14.2, Line Conventions and Lettering, was adopted on 30 September, 2008 for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Commander, U.S. Army Research, Development and Engineering Center (ARDEC), ATTN: AMSRD-AAR-QES-E, Picatinny Arsenal, NJ 07806-5000. Copies of this document may be purchased from The American Society of Mechanical Engineers (ASME), Three Park Avenue, New York, NY 10016-5990. <http://www.asme.org>

**Custodians:**

Army — AR  
Navy — SA  
Air Force — 16

Adopting Activity:  
Army — AR

(Project DRPR-2008-006)

**Review Activities:**

Army — CR, IE, MI, PT, TM2  
Navy — AS, CG, CH, EC, MC, NP, TD  
Air Force — 13, 99  
DLA — DH  
OSD — SE  
NSA — NS  
Other — CM, MP, DC2

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://assist.daps.dla.mil>.

AMSCN/A

AREA DRPR

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

**ASME Y14.2-2008**

**[Revision of ASME Y14.2M-1992 (R2003)]**

# **Line Conventions and Lettering**

---

**Engineering Drawing and Related  
Documentation Practices**

ASMENORMDOC.COM : Click to view the full PDF of ASME Y14.2-2008

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**



Date of Issuance: December 3, 2008

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda or written interpretations of the requirements of this Standard issued to this edition.

Periodically certain actions of the ASME Y14 Committee may be published as Cases. Cases are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org> as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,  
in an electronic retrieval system or otherwise,  
without the prior written permission of the publisher.

The American Society of Mechanical Engineers  
Three Park Avenue, New York, NY 10016-5990

Copyright © 2008 by  
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS  
All rights reserved  
Printed in U.S.A.

# CONTENTS

Foreword .....	iv
Committee Roster .....	v
Correspondence With the Y14 Committee .....	vi
<b>1 General</b> .....	1
<b>2 Line Conventions</b> .....	1
<b>3 Arrowheads</b> .....	8
<b>4 Lettering</b> .....	8
<b>Figures</b>	
1 Width and Types of Lines .....	2
2 Applications of Lines .....	3
3 Hidden Line Techniques and Symmetry Line Application .....	4
4 Section Lining of Adjacent Parts .....	4
5 Direction of Section Lines .....	5
6 Full Section .....	5
7 Outline Section Lining .....	6
8 Arrowhead Placement on Dimension Lines .....	7
9 Special Applications of Extension Lines .....	7
10 Termination of Leaders .....	7
11 Phantom Line Applications .....	9
12 Arrowhead Styles .....	10
13 Inclined Letters .....	10
14 Vertical Letters .....	11
<b>Table</b>	
1 Minimum Letter Heights (Millimeter) .....	11
<b>Mandatory Appendix</b>	
I Minimum Letter Heights (Inch) .....	13

# FOREWORD

This revision was prepared by Subcommittee 2 of the ASME Y14 Committee, Engineering Drawing and Related Documentation Practices. The successful completion of this revision is attributed to the Subcommittee members, the support of their respective companies/organizations, and the U. S. Department of Defense departments and agencies that participated in the review process.

It consists primarily of minor changes to the text to enhance readability. The more substantial changes are as follows:

- (a) A "no terminator" option for datum targets was added to the terminator options.
- (b) The rules for crossing leader lines were rewritten for consistency.
- (c) Due to changes in drawing preparation since the last revision, the lettering type section has been greatly simplified.
- (d) All the figures have been redrawn.

Suggestions for improvement of this Standard are welcome. They should be sent to The American Society of Mechanical Engineers; Attn: Secretary, Y14 Standards Committee; Three Park Ave., New York, NY 10016-5990.

This revision was approved as an American National Standard on September 19, 2008.

ASME NORMDOC.COM : Click to view the full PDF of ASME Y14.2 2008

# ASMEY14 COMMITTEE

## Engineering Drawing and Related Documentation Practices

(The following is the roster of the Committee at the time of approval of this Standard.)

### STANDARDS COMMITTEE OFFICERS

**F. Bakos, Jr.,** *Chair*  
**K. E. Wiegandt,** *Vice Chair*  
**C. J. Gomez,** *Secretary*

### STANDARDS COMMITTEE PERSONNEL

**A. R. Anderson,** Dimensional Control Systems, Inc.  
**J. B. Baker,** Consultant  
**F. Bakos, Jr.,** Consultant  
**J. V. Burleigh,** Consultant  
**R. A. Chadderdon,** Southwest Consultants  
**D. E. Day,** TEC-EASE, Inc.  
**K. Dobert,** UGS PLM Solutions  
**C. W. Ferguson,** WM Education Services  
**L. W. Foster,** L. W. Foster & Associates, Inc.  
**C. J. Gomez,** The American Society of Mechanical Engineers

**B. A. Harding,** Purdue University  
**D. H. Honsinger,** Consultant  
**W. A. Kaba,** Boeing Commercial Airplanes  
**K. S. King,** BAE Systems  
**A. Krulikowski,** Effective Training, Inc.  
**P. J. McCuiston,** Ohio University  
**J. D. Meadows,** James D. Meadows & Associates, Inc.  
**E. Niemiec,** Consultant  
**J. M. Smith,** Caterpillar, Inc.  
**K. E. Wiegandt,** Sandia National Laboratory  
**B. A. Wilson,** The Boeing Co.

### SUBCOMMITTEE 2 — LINE CONVENTIONS AND LETTERING

**P. J. McCuiston,** *Chair*, Ohio University  
**D. V. Alvarez,** Boeing Defense & Space Group  
**J. V. Burleigh,** Consultant  
**R. J. Campbell,** Harper College  
**J. G. Dadez,** Applied Geometrics, Inc.  
**M. E. Foster,** Applied Geometrics, Inc.

**K. S. King,** BAE Systems  
**D. H. McCurry II,** Boeing Commercial Airplanes  
**J. I. Miles, Sr.,** Lockheed Martin Aeronautics  
**R. H. Settle,** Naval Surface Warfare Center  
**B. A. Wilson,** The Boeing Co.

# CORRESPONDENCE WITH THE Y14 COMMITTEE

**General.** ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by proposing revisions and attending Committee meetings. Correspondence should be addressed to:

Secretary, Y14 Standards Committee  
The American Society of Mechanical Engineers  
Three Park Avenue  
New York, NY 10016-5990

**Proposing Revisions.** Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

**Proposing a Case.** Cases may be issued for the purpose of providing alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee Web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the standard, the paragraph, figure or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the standard to which the proposed Case applies.

**Attending Committee Meetings.** The Y14 Standards Committee regularly holds meetings or telephone conferences, which are open to the public. Persons wishing to attend any meeting or telephone conference should contact the Secretary of the Y14 Standards Committee or check the ASME Web site at <http://cstools.asme.org>.



# LINE CONVENTIONS AND LETTERING

## 1 GENERAL

### 1.1 Scope

This Standard establishes the line and lettering practices for use in the preparation of drawings, including the recognition of the requirements for computer aided design (CAD) and manually prepared drawings.

### 1.2 Units of Measurement

All dimensions used in this Standard are in millimeters, except in Mandatory Appendix I.

### 1.3 Applicable Documents

The following revisions of American National Standards form a part of this Standard to the extent specified herein. A more recent revision may be used, provided there is no conflict with the text of this Standard. In the event of a conflict between the text of this Standard and the references cited herein, the text of this Standard shall take precedence.

ASME Y14.3M-2003, Multiview and Sectional View Drawings

ASME Y14.5M-1994, Dimensioning and Tolerancing

Publisher: The American Society of Mechanical Engineers (ASME), Three Park Avenue, New York, NY 10016-5990; Order Dept: 22 Law Drive, P.O. Box 2900, Fairfield, NJ 07007-2900

## 2 LINE CONVENTIONS

Line conventions describe the size, construction, and application of the various lines used in making drawings. Paragraphs 2.1 through 2.14 identify the type and style of lines for use on drawings.

### 2.1 Line Widths

Two widths of line should be used on drawings (see Fig. 1). The thin line width shall be 0.3 mm minimum. The thick line width shall be 0.6 mm minimum. These approximate line widths are intended to differentiate between thick and thin lines and are not values for control of acceptance or rejection of drawings. All lines of the same type shall be uniform throughout the drawing. The ratio of line widths should be approximately two-to-one (2:1).

### 2.2 Line Spacing

Spacing between parallel lines may be exaggerated to a maximum of 3 mm, so there is no fill-in when the drawing is reproduced.

### 2.3 Visible Lines

Visible lines are continuous and shall be used for representing visible edges or contours of objects (see Figs. 1 and 2).

### 2.4 Projection Line

Projection lines are lines used to indicate the line of sight between two successive orthographic views.

### 2.5 Hidden Lines

Hidden lines are used to represent hidden edges and contours. They consist of short evenly spaced dashes and are used to show the hidden features of an object (see Figs. 1 and 2). The length of the dashes may vary slightly in relation to the scale of the view.

Hidden lines should begin and end with a dash in contact with the visible or hidden line from which they start or end, except when such a dash would form a continuation of a visible line or when a CAD system has limitations that cannot comply with these requirements. Dashes should join at corners, and arcs should start with dashes at tangent points (see Fig. 3).

When features located behind transparent materials are depicted, they shall be treated as concealed features and shown with hidden lines. Hidden lines should be omitted when their use is not required for the clarity of the drawing.

### 2.6 Section Lines

Section lines are used to show surfaces cut by a cutting plane. They are drawn as a pattern of straight, equally spaced, parallel lines used to indicate the cut surfaces of an object in section views (see Figs. 1 and 2).

**2.6.1 General Principles.** Cut surfaces of sectional views may be identified by using section lines. Section lines are optional and may be used when necessary to distinguish individual components of an assembly or to distinguish different surface levels of a full or partial section through a part (see ASME Y14.3M).

Lettering should not be placed in section areas. However, when it is unavoidable, the section lines shall be omitted in the area for the lettering (see Fig. 4). When


**Fig. 1 Width and Types of Lines**

Line Type		Line Style	Paragraph Reference
Visible line	1	Thick	2.3
Hidden line	2	Thin	2.5
Section line	3	Thin	2.4, 2.6
Projection line	4	Thin	2.7
Center line	5	Thin	2.8
Symmetry line	5	Thick	2.8
Dimension line	6	Dimension line	2.9.1
Extension line	7	Extension line	2.9.2
and Leader line	8	Leader	2.9.3
Cutting-plane line	9	Thick	2.10
or	10	Thick	2.10
Viewing-plane line	11	Thick	2.10
Break line	12	Thick	2.11
	13	Thin	2.11
Phantom line	14	Thin	2.12
Reference line	15	Thin	2.13
Stitch line	16	Thin	2.13
Chain line	17	Thick	2.14


GENERAL NOTES:

(a) **Line and Space Lengths.** Because of variances in drawing size and scale used, specifying the length and blank spaces for these line conventions is not practical. It is advisable to select the line and blank space length which depict the appropriate line convention commensurate with the drawing size and scale required.


**Fig.2 Applications of Lines**





**Fig. 3 Hidden Line Techniques and Symmetry Line Application**



**Fig. 4 Section Lining of Adjacent Parts**



**Fig. 5 Direction of Section Lines****Fig. 6 Full Section**

several adjacent parts are shown in a section view, the parts may be sectioned as shown in Fig. 4. For section views of thin materials, see ASME Y14.3M.

**2.6.2 Direction and Spacing.** Section lines should be drawn at a 45 deg angle within the view [see Fig. 4, item (a)]. On adjacent parts, these section lines should be drawn in the opposite direction [see Fig. 4, item (b)]. For additional adjacent parts, any suitable angle may be used to make each part stand out separately and clearly [see Fig. 4, item (c)]. A suitable angle should be chosen to avoid section lines that are parallel or perpendicular to visible lines (see Fig. 5). Section lines shall not meet at common boundaries.

Section lines shall be uniformly spaced a minimum of 1.5 mm, and spaced as generously as possible and yet preserve the unity and contrast of the sectioned areas (see Fig. 6).

Outline section lines are drawn adjacent to the boundaries only of the sectioned area, and are preferred for large areas when section lines are required, provided clarity is not sacrificed (see Fig. 7).

## 2.7 Center Lines


Center lines are used to represent axis, center points, or center planes of symmetrical parts and features, bolt circles, and paths of motion (see Figs. 2 and 3).

Center lines shall start and end with long lines and shall intersect by crossing the long lines or short dashes (see Fig. 1). The long line portion of the center line may vary in length depending on the scale of the view. Center lines shall extend uniformly and distinctly a short distance beyond the object or feature. The center line may be extended for dimensioning or for some other purpose.

Center lines shall not extend through the space between views. Short center lines may be unbroken when no confusion results with other lines.

## 2.8 Symmetry Line

Symmetry lines are used to identify a plane of symmetry. The plane of symmetry is identified by placing two short parallel lines (symmetry lines), drawn at right angles, crossing a center line near each end and outside the boundary of the part (see Fig. 1).

**Fig. 7 Outline Section Lining**

Symmetry lines are used when representing partially drawn views and partial sections of symmetrical parts (see Fig. 3). Visible and hidden lines in symmetrical views may extend past the center line when clarity is improved.

## 2.9 Dimension, Extension, and Leader Lines

These are solid lines used to dimension drawings as described in paras. 2.9.1 through 2.9.3.2 (see ASMEY14.5M).

**2.9.1 Dimension Line.** Dimension lines are used to indicate the extent and direction of dimensions, and are terminated with uniform arrowheads (see Figs. 1 and 2). Arrowheads shall be drawn within the limits of the dimension line when possible [see Fig. 8, illustration (a)]. When inadequate space is available, the dimension lines and arrowheads may be shown outside the dimensional limit [see Fig. 8, illustration (b)].

**2.9.2 Extension Lines.** Extension lines are used to indicate the point or line on the drawing to which the dimension applies (see Figs. 1 and 2). They are also used to indicate the extension of a surface to a theoretical intersection (see Fig. 9).

**2.9.3 Leader Lines.** Leader lines are used to direct notes, dimensions, symbols, item numbers, or part numbers on the drawing (see Figs. 1 and 2). A leader line should be a straight inclined line, except for a short horizontal portion extending to the center of the height of the first or last letter or digit of the note. Leader lines may consist of one or more line segments (see Fig. 10). Leaders may be drawn with a hidden line style when pointing to a hidden surface. The horizontal portion of the leader shall not underline the note, and may be omitted entirely.

A vertical line may be used at the end of the leader to group information. When the vertical line is used,

the leader line may terminate at any point on the vertical line.

### 2.9.3.1 Terminate leaders as follows:

- (a) without an arrowhead or dot, when they end on a dimension line [see Fig. 10, illustration (a)]
- (b) with a dot 1.5 mm minimum diameter, when they end within outlines of an object [see Fig. 10, illustration (b)]
- (c) with an arrowhead, when they end on the outline of an object [see Fig. 10, illustration (c)]
- (d) without a terminator for a datum target

### 2.9.3.2 Leader lines


- (a) should not cross
- (b) should not be excessively long
- (c) shall not be parallel to adjacent dimension, extension, or section lines
- (d) shall not be drawn at small angles to terminating surfaces
- (e) shall not be vertical or horizontal

## 2.10 Cutting-Plane and Viewing-Plane Lines


Cutting-plane and viewing-plane lines are used to indicate the location of cutting planes for sectional views and the viewing position for removed views (see Figs. 1 and 2). Cutting-plane and viewing-plane lines shall be drawn to stand out clearly on the drawing. The ends of the lines are at 90 deg, and terminated by arrowheads to indicate the direction of sight for viewing (see Fig. 2 and ASMEY14.3M). Three forms of cutting-plane and viewing-plane lines are as follows:

- (a) evenly spaced dashes [see Fig. 1 (line 9)].
- (b) alternating long dashes and pairs of short dashes. The long dashes may vary in length, depending on the size of the drawing [see Fig. 1 (line 10)].
- (c) Figure 1 (line 11), same as lines 9 and 10, except the dashes between line ends are omitted.


**Fig. 8 Arrowhead Placement on Dimension Lines**



**Fig. 9 Special Applications of Extension Lines**



**Fig. 10 Termination of Leaders**



### 2.11 Break Line

Break lines are used when complete views are not required. The two forms of break lines are

- (a) freehand line [see Fig. 1 (line 12) and Fig. 2]
- (b) long lines joined by zigzags [see Fig. 1 (line 13) and Fig. 11, illustration (a)]

### 2.12 Phantom Line

Phantom lines are used to indicate

- (a) alternate positions of moving parts (see Fig. 2)
- (b) reference parts [see Fig. 11, illustration (a)]
- (c) repeated detail [see Fig. 11, illustrations (b) and (c)]
- (d) filleted and rounded corners [see Fig. 11, illustration (d)]
- (e) a reference plane between adjacent orthographic views

Phantom lines consist of long lines separated by pairs of short dashes. Phantom lines should start and end with long lines which may vary in length depending on the size of the drawing [see Fig. 1 (line 14)].

### 2.13 Stitch Line

Stitch lines are used for indicating a sewing or stitching process [see Fig. 1 (lines 15 and 16)]. The two forms of stitch lines are as follows:

- (a) short dashes and spaces of equal lengths
- (b) dots approximately 0.3 mm diameter, and 3 mm apart

### 2.14 Chain Line

Chain lines are used to indicate a surface or surface zone receiving additional treatment or consideration within limits specified on the drawing (see Fig. 2). They may also be used to indicate the location of a projected tolerance zone as defined in ASMEY14.5M. Chain lines consist of alternating lines and short dashes [see Fig. 1 (line 17)].

## 3 ARROWHEADS

Arrowheads are used to terminate dimension, leader, and cutting and viewing plane lines (see paras. 2.9.1, 2.9.3, and 2.10). Arrowhead length and width should be a ratio of approximately 3:1. The width of the arrowhead should be proportionate to the thickness of the lines used. A single style of arrowhead shall be used throughout the drawing (see Fig. 12).

## 4 LETTERING

For clarity within this Standard, lettering means both letters and numerals. Paragraphs 4.1 through 4.6 identify the type and style of lettering for use on drawings.

### 4.1 Lettering Type

Lettering should be single stroke gothic, opaque, and well spaced characters as shown in Figs. 13 and 14. When additions or revisions are made to a drawing, the original style of lettering shall be maintained.

### 4.2 Letter Style

Either inclined or vertical lettering is permissible. Only one style of lettering shall be used throughout a drawing. The preferred slope for the inclined characters is approximately 68 deg from the horizontal (see Fig. 13).

### 4.3 Letters — Upper and Lower Case

Upper case letters shall be used for all lettering on drawings unless lower case letters are required (see Figs. 13 and 14).

### 4.4 Letter Height

The minimum letter heights for various sized drawings are shown in Tables 1 and I-1.

### 4.5 Letter Spacing

Letters in words should be spaced so the background areas between the letters are approximately equal, and words are clearly separated. The space between two numerals having a decimal point between them is to be a minimum of two-thirds the height of the lettering. The vertical space between lines of lettering shall be no more than the height of the lettering, or no less than half the height of the lettering.

### 4.6 Legibility

The lettering heights, spacing, and proportions in Figs. 13 and 14, and also Table 1, normally provide acceptable reproduction. When applying lettering manually, or by typewriter, or CAD equipment which utilizes heights, spacing, or proportions other than those recommended, the lettering is acceptable when the minimum legibility and reproduction requirements of the accepted industry or military reproduction specifications are met. Therefore, the basic requirement for lettering on a drawing is to produce fully legible copies.



**Fig. 11 Phantom Line Applications**




Fig. 12 Arrowhead Styles




Fig. 13 Inclined Letters

