# INTERNATIONAL STANDARD **•** 5835/1

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION MEXIVY APOULA OF A HUBALIZATION FOR STANDARD TO A HUBALIZATION ORGANIZATION INTERNATIONAL FOR NORMALISATION

Implants for surgery — Metal bone screws — Dimensions — Part I: Screws with asymmetrical thread variable fitting (spherical)

STANDARDSISO. COM. Ciick to view the Implants pour la chirurgie – Vis métalliques pour os – Dimensions – Partie I : Vis à filet asymétrique, embase (sphérique)

First edition - 1978-03-01

UDC 615.465: 621.882.215

Ref. No. ISO 5835/I-1978 (E)

Descriptors: surgical implants, screws, screw threads, specifications, dimensions, dimensional tolerances.

#### **FOREWORD**

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

0115058351.1918

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 5835/I was developed by Technical Committee ISO/TC 150, Implants for surgery, and was circulated to the member bodies in December 1976.

It has been approved by the member bodies of the following countries:

Australia Austria

Germany

Hungary

Belgium

Italy

Brazil

Mexico

Canada

New Zealand

Czechoslovakia

Romania

Denmark

South Africa, Rep. of

Spain

Turkey

U.S.A.

Switzerland

United Kingdom

No member body expressed disapproval of the document.

© International Organization for Standardization, 1978 •

This part is one of a series of four which will comprise the International Standard for dimensions of metal bone screws for use in implant surgery.

#### The series as follows:

- Part I : Screws with asymmetrical thread, variable fitting (spherical).
- Part II: Screws with asymmetrical thread, constant fitting (spherical).
- Part III: Screws with asymmetrical thread, variable fitting (conical).
- Part IV: Screws with symmetrical thread, variable fitting (conical).

Parts III and IV are still under development.

STANDARDS & O.COM. Click to view the full Police of the O.C. Com. Click to view the full Police of the O.C. Click to view the O.C. Cl

Implants for surgery — Metal bone screws — Dimensions — Part I: Screws with asymmetrical thread, variable fitting the full PDF of ISO 58 (spherical)

#### 1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies dimensions and tolerances for metal bone screws used in surgery and having shallow and deep asymmetrical threads, heads with spherical under-surfaces, and head diameters that vary with the diameters of the thread (hence "variable fitting"):

The screws are provided exclusively with hexagonal drive sockets. STANDARDSISC

## 2 CODE FOR SCREW THREAD

The following code shall be used to distinguish the type of thread of screws conforming to this International Standard:

Type of thread		Code	
Shallow (for cortical screws)		НА	
Deep (for spongiosa screws)	,	НВ	

# 3 DIMENSIONS AND TOLERANCES (All dimensions are given in millimetres)

## 3.1 Screws with shallow thread




FIGURE 1 - Screw with shallow thread

TABLE 1 - Dimensions of the HA series screws

Code and diameter of thread	d <sub>1</sub> Nominal diameter	d <sub>2</sub> 0 -0,1	d <sub>3</sub>	k max.	r <sub>1</sub> + 0,25 0	r <sub>2</sub> ≈	3	SW E8	t min.
HA 2,7	2,7	5	3,5	2,3	2,5	2,5	0,4	2,5	1,2
HA 3,5	3,5	6	3,5	2,6	3	3,5	-1	2,5	1,5
HA 4,5	4,5	. 8		4,6	<b>3</b> 4	2,5	1	3,5	2,8




FIGURE 2 - Shallow thread (HA)

TABLE 2 — Dimensions of the HA thread

Code and diameter of thread	d <sub>1</sub> 0 - 0,1	d <sub>5</sub> 0 -0,2	<i>e</i> ≈	p	<i>r</i> <sub>4</sub>	<i>r</i> <sub>5</sub>	α	β
HA 2,7	2,7	1,9	0,1	1	0,6	0,15	35°	3°
HA 3,5	3,5	2,4	0,1	1,25	0,8	0,2	35°	3°
HA 4,5	4,5	3	0,1	1,75	1	0,3	35°	3°