



INTERNATIONAL STANDARD ISO/IEC 14496-11:2005  
TECHNICAL CORRIGENDUM 5

Published 2008-12-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION  
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

**Information technology — Coding of audio-visual objects —**  
**Part 11:**  
**Scene description and application engine**

TECHNICAL CORRIGENDUM 5

*Technologies de l'information — Codage des objets audiovisuels —*

*Partie 11: Description de scène et moteur d'application*

RECTIFICATIF TECHNIQUE 5

Technical Corrigendum 5 to ISO/IEC 14496-11:2005 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

---

*Replace the electronic attachment with the enclosed archive file.*

*In 7.1.1.2.13.6, replace:*

The angle distortion is such that a sound source that was localized at azimuth  $\theta$  will be moved to azimuth  $\theta'$ , with:  $\cos \theta' = (m + \cos \theta)/(1 + \mu \cos \theta)$  and  $\mu = (\lambda^2 - 1)/(\lambda^2 + 1)$ .

*with:*

The angle distortion is such that a sound source that was localized at azimuth  $\theta$  will be moved to azimuth  $\theta'$ , with:  $\cos \theta' = (\mu + \cos \theta)/(1 + \mu \cos \theta)$  and  $\mu = (\lambda^2 - 1)/(\lambda^2 + 1)$ .