
Information technology — Programming languages, their environments and system software interfaces — Extensions to the C Library to support mathematical special functions

Technologies de l'information — Langages de programmation, leur environnement et interfaces des logiciels de systèmes — Extensions à la bibliothèque C pour supporter les fonctions mathématiques spéciales

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Contents	iii
List of Tables	v
Foreword	vi
Introduction	vii
1 Scope	1
1.1 Relation to C Standard Library Introduction	1
1.2 Categories of extensions	1
2 Normative references	3
3 Terms, definitions, and symbols	5
4 Conformance	7
5 Predefined macro names	9
6 Mathematical special functions	11
6.1 Standard headers	11
6.2 Additions to header <math.h>	11
6.2.1 associated Laguerre polynomials	14
6.2.2 associated Legendre polynomials	14
6.2.3 beta function	15
6.2.4 (complete) elliptic integral of the first kind	15
6.2.5 (complete) elliptic integral of the second kind	15
6.2.6 (complete) elliptic integral of the third kind	16
6.2.7 regular modified cylindrical Bessel functions	16
6.2.8 cylindrical Bessel functions (of the first kind)	16
6.2.9 irregular modified cylindrical Bessel functions	17
6.2.10 cylindrical Neumann functions	17
6.2.11 (incomplete) elliptic integral of the first kind	17
6.2.12 (incomplete) elliptic integral of the second kind	18

CONTENTS

CONTENTS iv

6.2.13	(incomplete) elliptic integral of the third kind	18
6.2.14	exponential integral	18
6.2.15	Hermite polynomials	19
6.2.16	Laguerre polynomials	19
6.2.17	Legendre polynomials	19
6.2.18	Riemann zeta function	20
6.2.19	spherical Bessel functions (of the first kind)	20
6.2.20	spherical associated Legendre functions	20
6.2.21	spherical Neumann functions	21
6.3	Additions to header <tmath.h>	21
Bibliography		23
Index		25

List of Tables

1	Numerical library summary	1
2	Additions to header <math.h> synopsis	14
3	Additions to header <tgmath.h> synopsis	22

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 24747 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

Introduction

This International Standard is divided into three major subdivisions:

- preliminary elements (clauses 1 - 4);
- indicating conformance (clause 5);
- the library facilities (clause 6).

Footnotes are provided to emphasize consequences of the rules described in that subclause or elsewhere in this International Standard. References are used to refer to other related documents and subclauses. A bibliography lists documents that were referred to during the preparation of this International Standard.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

Information technology — Programming languages, their environments and system software interfaces — Extensions to the C Library to support mathematical special functions

1 Scope [scop]

1.1 Relation to C Standard Library Introduction [descr]

- 1 This International Standard defines extensions to the *C standard library* that is defined in the International Standard for the C programming language, see Clause 2.
- 2 Unless otherwise specified, the whole of the *C Standard Library* is included into this International Standard by reference, see Clause 2.

1.2 Categories of extensions [exten]

- 1 This International Standard defines library extensions to the C Standard Library to support Mathematical Special functions to be added to `<math.h>` and `<tgmath.h>`.

Table 1: Numerical library summary

Subclause	Header(s)
6.2 Additions to	<code><math.h></code>
6.3 Additions to	<code><tgmath.h></code>

(Blank page)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

2 Normative references

[norm]

- 1 The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.
- 2 ISO/IEC 9899:1999, *Programming languages — C*
- 3 ISO/IEC 9899:1999/Cor. 1:2001, *Programming languages — C — Technical Corrigendum 1*
- 4 ISO/IEC 9899:1999/Cor. 2:2004, *Programming languages — C — Technical Corrigendum 2*
- 5 ISO/IEC 9899:1999/Cor. 3:2007, *Programming languages — C — Technical Corrigendum 3*
- 6 ISO/IEC 2382-1:1993, *Information technology — Vocabulary — Part 1: Fundamental terms*

(Blank page)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

3 Terms, definitions, and symbols

[terms]

- ¹ For the purposes of this document, the terms and definitions given in ISO/IEC 9899:1999 and the associated Technical Corrigenda and ISO/IEC 2382-1 apply, see Clause [2](#).

(Blank page)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

4 Conformance

[confor]

- 1 If a "shall" requirement is violated, the behavior is undefined.

(Blank page)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

5 Predefined macro names

[pred]

- ¹ The following macro name is conditionally defined by the implementation:

`__STDC_MATH_SPEC_FUNCS__` The integer constant 200808, intended to indicate conformance to this International Standard. ¹⁾

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

¹⁾The intention is that this will remain an integer constant of type `long int` that is increased with each revision of this International Standard.

(Blank page)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24747:2009

6 Mathematical special functions

[num.sf]

6.1 Standard headers

[num.sf.header]

- 1 The functions declared in Clause 6 and its subclauses are not declared by their respective header if `__STDC_WANT_MATH_SPEC_FUNCS__` is defined as a macro which expands to the integer constant 0 at the point in the source file where the appropriate header is included.
- 2 The functions declared in Clause 6 and its subclauses are declared by their respective headers if `__STDC_WANT_MATH_SPEC_FUNCS__` is defined as a macro which expands to the integer constant 1 at the point in the source file where the appropriate header is included.²⁾
- 3 Functions declared in Clause 6 and its subclauses shall not be declared by their respective headers if `__STDC_WANT_MATH_SPEC_FUNCS__` is not defined as a macro at the point in the source file where the appropriate header is included.
- 4 Within a preprocessing translation unit, `__STDC_WANT_MATH_SPEC_FUNCS__` shall be defined identically for all inclusions of any headers from Clause 6. If `__STDC_WANT_MATH_SPEC_FUNCS__` is defined differently for any such inclusion, the implementation shall issue a diagnostic as if a preprocessor error directive was used.

6.2 Additions to header <math.h>

[num.sf.math]

- 1 Table 2 summarizes the functions that are added to header <math.h>. The detailed signatures are given in the synopsis.
- 2 Each of these functions is provided for arguments of type float, double, and long double. The signatures added to header <math.h> are:

```
// [6.2.1] associated Laguerre polynomials:
double      assoc_laguerre(unsigned n, unsigned m, double x);
float       assoc_laguerref(unsigned n, unsigned m, float x);
long double assoc_laguerrel(unsigned n, unsigned m, long double x);

// [6.2.2] associated Legendre polynomials:
double      assoc_legendre(unsigned l, unsigned m, double x);
float       assoc_legendref(unsigned l, unsigned m, float x);
long double assoc_legendrel(unsigned l, unsigned m, long double x);

// [6.2.3] beta function:
double      beta(double x, double y);
float       betaf(float x, float y);
long double betal(long double x, long double y);
```

²⁾Future revisions of this International Standard may define meanings for other values of `__STDC_WANT_MATH_SPEC_FUNCS__`.

```

// [6.2.4] (complete) elliptic integral of the first kind:
double      comp_ellint_1(double k);
float       comp_ellint_1f(float k);
long double comp_ellint_1l(long double k);

// [6.2.5] (complete) elliptic integral of the second kind:
double      comp_ellint_2(double k);
float       comp_ellint_2f(float k);
long double comp_ellint_2l(long double k);

// [6.2.6] (complete) elliptic integral of the third kind:
double      comp_ellint_3(double k, double nu);
float       comp_ellint_3f(float k, float nu);
long double comp_ellint_3l(long double k, long double nu);

// [6.2.7] regular modified cylindrical Bessel functions:
double      cyl_bessel_i(double nu, double x);
float       cyl_bessel_if(float nu, float x);
long double cyl_bessel_il(long double nu, long double x);

// [6.2.8] cylindrical Bessel functions (of the first kind):
double      cyl_bessel_j(double nu, double x);
float       cyl_bessel_jf(float nu, float x);
long double cyl_bessel_jl(long double nu, long double x);

// [6.2.9] irregular modified cylindrical Bessel functions:
double      cyl_bessel_k(double nu, double x);
float       cyl_bessel_kf(float nu, float x);
long double cyl_bessel_kl(long double nu, long double x);

// [6.2.10] cylindrical Neumann functions:
// cylindrical Bessel functions (of the second kind):
double      cyl_neumann(double nu, double x);
float       cyl_neumannf(float nu, float x);
long double cyl_neumannl(long double nu, long double x);

// [6.2.11] (incomplete) elliptic integral of the first kind:
double      ellint_1(double k, double phi);
float       ellint_1f(float k, float phi);
long double ellint_1l(long double k, long double phi);

// [6.2.12] (incomplete) elliptic integral of the second kind:
double      ellint_2(double k, double phi);
float       ellint_2f(float k, float phi);
long double ellint_2l(long double k, long double phi);

// [6.2.13] (incomplete) elliptic integral of the third kind:
double      ellint_3(double k, double nu, double phi);
float       ellint_3f(float k, float nu, float phi);
long double ellint_3l(long double k, long double nu, long double phi);

```

13 Mathematical special functions

6.2 Additions to header <math.h>

```

// [6.2.14] exponential integral:
double      expint(double x);
float       expintf(float x);
long double expintl(long double x);

// [6.2.15] Hermite polynomials:
double      hermite(unsigned n, double x);
float       hermitef(unsigned n, float x);
long double hermitel(unsigned n, long double x);

// [6.2.16] Laguerre polynomials:
double      laguerre(unsigned n, double x);
float       laguerref(unsigned n, float x);
long double laguerrel(unsigned n, long double x);

// [6.2.17] Legendre polynomials:
double      legendre(unsigned l, double x);
float       legendref(unsigned l, float x);
long double legendrel(unsigned l, long double x);

// [6.2.18] Riemann zeta function:
double      riemann_zeta(double);
float       riemann_zetaf(float);
long double riemann_zetal(long double);

// [6.2.19] spherical Bessel functions (of the first kind):
double      sph_bessel(unsigned n, double x);
float       sph_besself(unsigned n, float x);
long double sph_bessell(unsigned n, long double x);

// [6.2.20] spherical associated Legendre functions:
double      sph_legendre(unsigned l, unsigned m, double theta);
float       sph_legendref(unsigned l, unsigned m, float theta);
long double sph_legendrel(unsigned l, unsigned m, long double theta);

// [6.2.21] spherical Neumann functions:
// spherical Bessel functions (of the second kind):
double      sph_neumann(unsigned n, double x);
float       sph_neumannf(unsigned n, float x);
long double sph_neumannl(unsigned n, long double x);

```

Table 2: Additions to header <math.h> synopsis

Functions:		
assoc_laguerre	cyl_bessel_j	hermite
assoc_legendre	cyl_bessel_k	legendre
beta	cyl_neumann	laguerre
comp_ellint_1	ellint_1	riemann_zeta
comp_ellint_2	ellint_2	sph_bessel
comp_ellint_3	ellint_3	sph_legendre
cyl_bessel_i	expint	sph_neumann

- 3 Each of the functions declared above shall return a NaN (Not a Number) if any argument value is a NaN, but it shall not report a domain error. Otherwise, each of the functions declared above shall report a domain error for just those argument values for which:
- the function description's Returns clause explicitly specifies a domain, and those arguments fall outside the specified domain; or
 - the corresponding mathematical function value has a non-zero imaginary component; or
 - the corresponding mathematical function is not mathematically defined.³⁾
- 4 Unless otherwise specified, a function is defined for all finite values, for negative infinity, and for positive infinity.

6.2.1 associated Laguerre polynomials**[num.sf.Lnm]**

```
double    assoc_laguerre(unsigned n, unsigned m, double x);
float     assoc_laguerref(unsigned n, unsigned m, float x);
long double assoc_laguerrel(unsigned n, unsigned m, long double x);
```

- 1 *Effects:* These functions compute the associated Laguerre polynomials of their respective arguments n, m, and x.
- 2 *Returns:* The assoc_laguerre functions return

$$L_n^m(x) = (-1)^m \frac{d^m}{dx^m} L_{n+m}(x), \quad \text{for } x \geq 0.$$

- 3 *Note:* The effect of calling each of these functions is implementation-defined if $n \geq 128$ or if $m \geq 128$.

6.2.2 associated Legendre polynomials**[num.sf.Plm]**

```
double    assoc_legendre(unsigned l, unsigned m, double x);
float     assoc_legendref(unsigned l, unsigned m, float x);
long double assoc_legendrel(unsigned l, unsigned m, long double x);
```

³⁾A mathematical function is mathematically defined for a given set of argument values if it is explicitly defined for that set of argument values or if its limiting value exists and does not depend on the direction of approach.

15 Mathematical special functions**6.2 Additions to header <math.h>**

1 *Effects:* These functions compute the associated Legendre functions of their respective arguments l , m , and x .

2 *Returns:* The `assoc_legendre` functions return

$$P_{\ell}^m(x) = (1-x^2)^{m/2} \frac{d^m}{dx^m} P_{\ell}(x), \quad \text{for } |x| \leq 1.$$

3 *Note:* The effect of calling each of these functions is implementation-defined if $l \geq 128$.

6.2.3 beta function**[num.sf.beta]**

```
double    beta(double x, double y);
float     betaf(float x, float y);
long double betal(long double x, long double y);
```

1 *Effects:* These functions compute the beta function of their respective arguments x and y .

2 *Returns:* The beta functions return

$$B(x, y) = \frac{\Gamma(x)\Gamma(y)}{\Gamma(x+y)}, \quad \text{for } x > 0, y > 0.$$

6.2.4 (complete) elliptic integral of the first kind**[num.sf.ellK]**

```
double    comp_ellint_1(double k);
float     comp_ellint_1f(float k);
long double comp_ellint_1l(long double k);
```

1 *Effects:* These functions compute the complete elliptic integral of the first kind of their respective arguments k .

2 *Returns:* The `comp_ellint_1` functions return

$$K(k) = F(k, \pi/2), \quad \text{for } |k| \leq 1.$$

3 See 6.2.11.

6.2.5 (complete) elliptic integral of the second kind**[num.sf.ellEx]**

```
double    comp_ellint_2(double k);
float     comp_ellint_2f(float k);
long double comp_ellint_2l(long double k);
```

1 *Effects:* These functions compute the complete elliptic integral of the second kind of their respective arguments k .

2 *Returns:* The `comp_ellint_2` functions return

$$E(k) = E(k, \pi/2), \quad \text{for } |k| \leq 1.$$

3 See 6.2.12.

6.2.6 (complete) elliptic integral of the third kind**[num.sf.ellPx]**

```
double    comp_ellint_3(double k, double nu);
float     comp_ellint_3f(float k, float nu);
long double comp_ellint_3l(long double k, long double nu);
```

1 *Effects:* These functions compute the complete elliptic integral of the third kind of their respective arguments k and nu .

2 *Returns:* The `comp_ellint_3` functions return

$$\Pi(v, k) = \Pi(v, k, \pi/2), \quad \text{for } |k| \leq 1.$$

3 See 6.2.13.

6.2.7 regular modified cylindrical Bessel functions**[num.sf.I]**

```
double    cyl_bessel_i(double nu, double x);
float     cyl_bessel_if(float nu, float x);
long double cyl_bessel_il(long double nu, long double x);
```

1 *Effects:* These functions compute the regular modified cylindrical Bessel functions of their respective arguments nu and x .

2 *Returns:* The `cyl_bessel_i` functions return

$$I_\nu(x) = i^{-\nu} J_\nu(ix) = \sum_{k=0}^{\infty} \frac{(x/2)^{\nu+2k}}{k! \Gamma(\nu+k+1)}, \quad \text{for } x \geq 0.$$

3 *Note:* The effect of calling each of these functions is implementation-defined if $nu \geq 128$.

6.2.8 cylindrical Bessel functions (of the first kind)**[num.sf.J]**

```
double    cyl_bessel_j(double nu, double x);
float     cyl_bessel_jf(float nu, float x);
long double cyl_bessel_jl(long double nu, long double x);
```

1 *Effects:* These functions compute the cylindrical Bessel functions of the first kind of their respective arguments nu and x .

2 *Returns:* The `cyl_bessel_j` functions return

$$J_\nu(x) = \sum_{k=0}^{\infty} \frac{(-1)^k (x/2)^{\nu+2k}}{k! \Gamma(\nu+k+1)}, \quad \text{for } x \geq 0.$$

3 *Note:* The effect of calling each of these functions is implementation-defined if $nu \geq 128$.

17 Mathematical special functions

6.2 Additions to header <math.h>

6.2.9 irregular modified cylindrical Bessel functions

[num.sf.K]

```
double    cyl_bessel_k(double nu, double x);
float     cyl_bessel_kf(float nu, float x);
long double cyl_bessel_kl(long double nu, long double x);
```

1 *Effects:* These functions compute the irregular modified cylindrical Bessel functions of their respective arguments nu and x.

2 *Returns:* The cyl_bessel_k functions return

$$K_v(x) = (\pi/2)i^{v+1}(J_v(ix) + iN_v(ix)) = \begin{cases} \frac{\pi}{2} \frac{I_{-v}(x) - I_v(x)}{\sin v\pi}, & \text{for } x \geq 0 \text{ and non-integral } v \\ \frac{\pi}{2} \lim_{\mu \rightarrow v} \frac{I_{-\mu}(x) - I_{\mu}(x)}{\sin \mu\pi}, & \text{for } x \geq 0 \text{ and integral } v \end{cases}$$

3 *Note:* The effect of calling each of these functions is implementation-defined if nu >= 128.

6.2.10 cylindrical Neumann functions

[num.sf.N]

```
double    cyl_neumann(double nu, double x);
float     cyl_neumannf(float nu, float x);
long double cyl_neumannl(long double nu, long double x);
```

1 *Effects:* These functions compute the cylindrical Neumann functions, also known as the cylindrical Bessel functions of the second kind, of their respective arguments nu and x.

2 *Returns:* The cyl_neumann functions return

$$N_v(x) = \begin{cases} \frac{J_v(x) \cos v\pi - J_{-v}(x)}{\sin v\pi}, & \text{for } x \geq 0 \text{ and non-integral } v \\ \lim_{\mu \rightarrow v} \frac{J_{\mu}(x) \cos \mu\pi - J_{-\mu}(x)}{\sin \mu\pi}, & \text{for } x \geq 0 \text{ and integral } v \end{cases}$$

3 *Note:* The effect of calling each of these functions is implementation-defined if nu >= 128.

4 See 6.2.8.

6.2.11 (incomplete) elliptic integral of the first kind

[num.sf.ellF]

```
double    ellint_1(double k, double phi);
float     ellint_1f(float k, float phi);
long double ellint_1l(long double k, long double phi);
```

1 *Effects:* These functions compute the incomplete elliptic integral of the first kind of their respective arguments k and phi (phi measured in radians).

2 *Returns:* The `ellint_1` functions return

$$F(k, \phi) = \int_0^{\phi} \frac{d\theta}{\sqrt{1 - k^2 \sin^2 \theta}}, \quad \text{for } |k| \leq 1.$$

6.2.12 (incomplete) elliptic integral of the second kind

[num.sf.ellE]

```
double    ellint_2(double k, double phi);
float     ellint_2f(float k, float phi);
long double ellint_2l(long double k, long double phi);
```

1 *Effects:* These functions compute the incomplete elliptic integral of the second kind of their respective arguments `k` and `phi` (`phi` measured in radians).

2 *Returns:* The `ellint_2` functions return

$$E(k, \phi) = \int_0^{\phi} \sqrt{1 - k^2 \sin^2 \theta} d\theta, \quad \text{for } |k| \leq 1.$$

6.2.13 (incomplete) elliptic integral of the third kind

[num.sf.ellP]

```
double    ellint_3(double k, double nu, double phi);
float     ellint_3f(float k, float nu, float phi);
long double ellint_3l(long double k, long double nu, long double phi);
```

1 *Effects:* These functions compute the incomplete elliptic integral of the third kind of their respective arguments `k`, `nu`, and `phi` (`phi` measured in radians).

2 *Returns:* The `ellint_3` functions return

$$\Pi(\nu, k, \phi) = \int_0^{\phi} \frac{d\theta}{(1 - \nu \sin^2 \theta) \sqrt{1 - k^2 \sin^2 \theta}}, \quad \text{for } |k| \leq 1.$$

6.2.14 exponential integral

[num.sf.ei]

```
double    expint(double x);
float     expintf(float x);
long double expintl(long double x);
```

1 *Effects:* These functions compute the exponential integral of their respective arguments `x`.

2 *Returns:* The `expint` functions return

$$\text{Ei}(x) = - \int_{-x}^{\infty} \frac{e^{-t}}{t} dt.$$

19 Mathematical special functions

6.2 Additions to header <math.h>

6.2.15 Hermite polynomials

[num.sf.Hn]

```
double    hermite(unsigned n, double x);
float     hermitef(unsigned n, float x);
long double hermitel(unsigned n, long double x);
```

1 *Effects:* These functions compute the Hermite polynomials of their respective arguments n and x.

2 *Returns:* The hermite functions return

$$H_n(x) = (-1)^n e^{x^2} \frac{d^n}{dx^n} e^{-x^2}.$$

3 *Note:* The effect of calling each of these functions is implementation-defined if $n \geq 128$.

6.2.16 Laguerre polynomials

[num.sf.Ln]

```
double    laguerre(unsigned n, double x);
float     laguerref(unsigned n, float x);
long double laguerrel(unsigned n, long double x);
```

1 *Effects:* These functions compute the Laguerre polynomials of their respective arguments n and x.

2 *Returns:* The laguerre functions return

$$L_n(x) = \frac{e^x}{n!} \frac{d^n}{dx^n} (x^n e^{-x}), \quad \text{for } x \geq 0.$$

3 *Note:* The effect of calling each of these functions is implementation-defined if $n \geq 128$.

6.2.17 Legendre polynomials

[num.sf.Pl]

```
double    legendre(unsigned l, double x);
float     legendref(unsigned l, float x);
long double legendrel(unsigned l, long double x);
```

1 *Effects:* These functions compute the Legendre polynomials of their respective arguments l and x.

2 *Returns:* The legendre functions return

$$P_\ell(x) = \frac{1}{2^\ell \ell!} \frac{d^\ell}{dx^\ell} (x^2 - 1)^\ell, \quad \text{for } |x| \leq 1.$$

3 *Note:* The effect of calling each of these functions is implementation-defined if $l \geq 128$.