



UL 1180

STANDARD FOR SAFETY

Fully Inflatable Recreational Personal Flotation Devices

[ULNORM.COM](https://www.ulnorm.com) : Click to view the full PDF of UL 1180 2024

ULNORM.COM : Click to view the full PDF of UL 1180 2024

UL Standard for Safety for Fully Inflatable Recreational Personal Flotation Devices, UL 1180

Second Edition, Dated February 13, 2009

Summary of Topics

This revision to ANSI/UL 1180 dated June 14, 2024, includes an alternate marking correction to labeling requirements for UL 1180 inflatables; [45A.1.1](#) – [45A.1.4A](#), and the titles only for Sections [45B](#), [45C](#), [45D](#), [45E](#) and [45F](#)

Text that has been changed in any manner or impacted by ULSE's electronic publishing system is marked with a vertical line in the margin.

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated March 22, 2024 and May 10, 2024.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 1180 2024

FEBRUARY 13, 2009
(Title Page Reprinted: June 14, 2024)



ANSI/UL 1180-2024

1

UL 1180

Standard for Fully Inflatable Recreational Personal Flotation Devices

First Edition – May, 1995

Second Edition

February 13, 2009

This ANSI/UL Standard for Safety consists of the Second Edition including revisions through June 14, 2024.

The most recent designation of ANSI/UL 1180 as an American National Standard (ANSI) occurred on June 14, 2024. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in ULSE's Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

COPYRIGHT © 2024 ULSE INC. ALL RIGHTS RESERVED.

ULNORM.COM - Click to buy the PDF of UL 1180 2024

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 1180 2024

CONTENTS

INTRODUCTION

1 Scope 9
 2 References 9
 3 Units of Measurement 9
 4 Definitions 9

CONSTRUCTION

5 Inflatable Devices 12
 6 Components and Materials 12
 7 Sizing and Arrangement 13
 8 Inflatable Compartments 14
 9 Over-Pressure-Relief Valves 14
 10 Inflation Systems 14
 11 Deflation Systems 15
 12 Closure, Adjustment, and Attachment Means 16
 13 Seams and Stitching 17
 14 Buddy Line 17

PERFORMANCE

GENERAL

15 Selection and Preparation of Test Samples 17

USE CHARACTERISTICS TESTS

16 Test Participants 18
 17 Ease of Donning, Adjustment and Operation Test 19
 18 Inflated Donning Test 20
 19 Ease of Use Test 20
 20 Post-Donning Ease of Adjustment Test 20
 21 Water Entry Tests 20
 22 In-Water Second-Stage Donning Test 22
 23 Turning Test 22
 24 Static Flotation Tests 23
 25 H.E.L.P. Position Test 25
 26 Rearming and Repacking Test 25
 27 Pre-Inflated Automatic Discharge Test 26

PHYSICAL PROPERTIES TESTS

28 Automatic, Manual-auto, and Manual Inflation Test 26
 29 Buoyancy Test 28
 30 Water Entrapment Test 29
 31 Body, Primary Closure, Shoulder, and Collar Strength Tests 29
 32 Secondary Closure Strength Test 31
 33 Miscellaneous Fastener Strength Test 31
 34 Body Strap – Hardware Securement Test 31
 35 Seam Strength Test 32
 36 Strength of Attachment Tests 32

37	Temperature Resistance / Stability Tests	33
38	Solvent Resistance Test.....	34
39	Flame Resistance Test	34
40	Puncture Resistance Test	34
41	Over-Pressure Tests.....	35
42	Air Retention Test.....	36
43	Environmental Tests	36
44	Pull Test.....	40

MARKINGS

45	PFD Label Markings	40
45A	Markings	40
	45A.1 General	40
	45A.2 Label Location and Format.....	42
	45A.3 Label Content.....	43
	45A.4 Alternative Attachment Means for PFD Markings	48
45B	General Alternate PFD Markings.....	49
45C	Alternate PFD Label Markings	49
45D	Alternate Donning Instructions	52
45E	Alternate Status Indicator Instructions.....	52
45F	Alternate Use, Care, and Maintenance Instructions.....	52
46	PFD Label Markings	54
47	Donning Instructions.....	54
48	Status Indicator Instructions	54
49	Use, Care, and Maintenance Instructions.....	54
50	User Identification and Service Record Area.....	54
51	Initial Arming Warning.....	54
52	Inflation Medium Container Area Identification.....	55
53	Inflation Medium Container Identification.....	55
54	Visibility of Manual Actuation Means	55
55	Buddy line identification	55
56	Sewn Labels	55
57	Hang Tags	55

OWNER'S MANUAL

58	Owner's Manual	56
58A	Owner's Manual	56
	58A.1 General	56
	58A.2 Required Text.....	56
59	Consumer Information at Point of Sale	70
59A	Consumer Information at Point of Sale.....	70
	59A.1 Safe Choice Placard	70
	59A.2 Placard Strength of Attachment Test.....	75

REARMING KITS

60	General	75
----	---------------	----

SUPPLEMENT SA – TYPE V USER ASSISTED INFLATABLE PFD

INTRODUCTION

SA1	Scope.....	77
-----	------------	----

SA2 General.....77
 SA3 Definitions.....77

CONSTRUCTION

SA4 General.....78
 SA5 Components and Materials.....78

PERFORMANCE

SA6 Use Characteristics Tests78
 SA6.1 Water entry tests78
 SA6.2 In-water second-stage donning test79
 SA6.3 Turning test79
 SA6.4 Static flotation test.....79
 SA6.5 H.E.L.P position80
 SA6.6 In-water bobbing test.....80
 SA7 Physical Properties Tests81
 SA7.1 Buoyancy test.....81
 SA7.2 Temperature resistance test.....81
 SA7.3 Secondary closure strength test81

MARKINGS

SA8 PFD Label Marking81

PAMPHLET

SA9 PFD Information Pamphlet82

OWNER'S MANUAL

SA10 PFD Owner's Manual.....82

SUPPLEMENT SB – Inflatable Type V Convertible PFDs

INTRODUCTION

SB1 Scope.....83
 SB2 Glossary83
 SB3 General.....83
 SB3.2 Conversion components83
 SB3.3 Stowage pocket84

MARKINGS

SB4 PFD Label Marking84

OWNER'S MANUAL

SB5 Explanation of Conversion in Owner's Manual85

SUPPLEMENT SC – Inflatable Type V PFDs Using Manual Inflators Without Cylinder Seal Indication

INTRODUCTION

SC1	Scope	87
SC2	General	87

MARKINGS

SC3	PFD Label Markings	87
-----	--------------------------	----

PAMPHLET

SC4	PFD Information Pamphlet	87
-----	--------------------------------	----

OWNER'S MANUAL

SC5	PFD Owner's Manual	88
-----	--------------------------	----

SUPPLEMENT SD – INFLATABLE WORK VEST PFDs**INTRODUCTION**

SD1	Scope	89
SD2	General	89

CONSTRUCTION

SD3	Sizing and Arrangement	89
-----	------------------------------	----

PERFORMANCE

SD4	Excess Webbing Evaluation	90
SD5	Water entry tests	90
SD6	In-Water Removal Test	90
SD7	Dynamic Strength Test	91
SD8	Tensile Test	91
SD9	Oil Resistance Test	91
SD10	Puncture Resistance Test	91
SD11	Abrasion Resistance Test	91
SD12	Rotating Shock Test	92

MARKINGS

SD13	PFD Label Marking	92
------	-------------------------	----

INSTRUCTIONS

SD14	Manufacturer's Service Manual	92
------	-------------------------------------	----

**SUPPLEMENT SE – UL 1180 LABEL WARNINGS FOR SUPPLEMENTS SA, SB, SC, AND SD
MARKINGS****APPENDIX A**

Standards for Components 98

APPENDIX B (Informative) Alternate Markings and Point of Sale Information

B1 General 99
B2 PFD Label Markings 99
B3 Donning Instructions 99
B4 Status Indicator Instructions 99
B5 Use, Care, and Maintenance Instructions 99
B6 User Identification and Service Record Area 100
B7 Initial Arming Warning 100
B8 Inflation Medium Container Area Identification 100
B9 Inflation Medium Container Identification 100
B10 Visibility of Manual Actuation Means 100
B11 Buddy Line Identification 100
B12 Sewn Labels 100
B13 Hang Tags 101

OWNER'S MANUAL

B14 General 101
B15 Required Text 101

ULNORM.COM : Click to view the full PDF of UL 1180 2024

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 1180 2024

INTRODUCTION

1 Scope

1.1 These requirements cover adult recreational wearable devices having at least one buoyancy compartment that relies upon inflation by gas or other medium to provide flotation to the wearer, for use by individuals at least 16 years of age and weighing 80 pounds (36.3 kg) or more.

1.2 These requirements cover devices intended for general boating activities where impacts with the water or other objects (i.e. those which occur during water skiing, white water paddling, personal watercraft use, and parasailing) are not likely.

1.3 These requirements cover rearming kits for the devices covered by this Standard.

1.4 Several levels of performance are set out by this standard to meet the needs of various boating activities, locations, and water conditions. The performance levels are designated by performance type.

1.5 *Deleted*

2 References

2.1 The following alpha-numeric list of Standards related to the American Society for Testing and Materials (ASTM) is provided for reference purposes:

- a) Method for Salt Spray (Fog, Testing), ASTM B117-94.
- b) Method for Rubber Property – Effect of Liquids, ASTM D471-79 (R1991).
- c) Methods of Testing Coated Fabrics, ASTM D751-89.
- d) Method for Gas Transmission Rate of Plastic Film and Sheeting, ASTM D1434-82 (R1992).
- e) Method for Failure in Sewn Seams in Woven Fabrics, ASTM D1683-90a.
- f) Practice for Operating Light Exposure Apparatus (Carbon-Arc Type) With or Without Water for Exposure of Nonmetallic Materials, ASTM G23-93.

3 Units of Measurement

3.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

4 Definitions

4.1 For the purpose of this standard the following definitions apply.

4.2 CLOSURE, PRIMARY – A primary closure is considered to be a means of securing the device onto the body so that the device can be expected to function substantially in the intended manner without the use of any other means of fastening the device onto the body.

4.3 CLOSURE, SECONDARY – A secondary closure is considered to be a closure that meets the following:

- a) Does not result in the device being donned as intended if it is the only closure that is closed on the device; and

b) Is not usually required to be closed in order for the device to substantially comply with the requirements in this standard.

4.4 DESIGN INFLATION RANGE – The range of buoyancy and pressure, as specified by the manufacturer, to which a compartment may be inflated to provide the intended in-water performance.

4.5 FACE PLANE ANGLE – The angle, relative to the surface of the water, of the plane formed by the most forward part of the forehead and chin of a wearer floating in the attitude of static balance. A positive angle is achieved when a user's forehead is higher than their chin.

4.6 FREEBOARD – A distance measured perpendicularly from the surface of the water to the lowest point where the wearer's respiration may be impeded, typically to the corner of the mouth. See [Figure 4.1](#).

Figure 4.1

Freeboard



4.7 FULL INFLATION – A chamber or chambers inflated to any value within the design inflation range.

4.8 FUNCTIONAL RESIDUAL CAPACITY (FRC) – The amount of lung volume that a person has remaining at the bottom of the normal breathing cycle when at rest.

4.9 H.E.L.P. (HEAT ESCAPE LESSENING POSTURE) POSITION – A position recommended by the United States Coast Guard and the American Red Cross to lessen the rate of body heat loss in cold water. In the H.E.L.P. Position, test participants have their knees drawn up toward their chests, their faces forward and out of the water, their upper arms held at their sides, and their lower arms folded across their chests.

4.10 INFLATABLE COMPARTMENT – A container that is inflated by a gas or other medium through an automatic, manual-auto, manual, or oral inflation system.

4.11 INFLATION SYSTEM – A means of inflating one or more compartments to make the device buoyant or more buoyant on demand, either actively or passively of the wearer's action, dependent on its type as follows:

a) AUTOMATIC INFLATION SYSTEM – A system that activates to inflate one or more compartments upon immersion in water without any action by the user (a passive system), and which has no provision for manually actuated inflation.

b) MANUAL-AUTO INFLATION SYSTEM – A system that activates to inflate one or more compartments upon immersion in water without any action by the user (a passive system) but which also has provision for being activated by a single deliberate user action, such as by the pulling of a lanyard.

c) MANUAL INFLATION SYSTEM – A system that inflates one or more compartments when activated by a single deliberate user action, such as by the pulling of a lanyard, and which has no provision for automatically actuated inflation.

d) ORAL INFLATION SYSTEM – A means for a user to blow air into a compartment by mouth.

4.12 JACKET – A device having sleeves.

4.13 LOCK STITCH – A stitch that will not unravel when a force is applied to any of the threads forming the stitch, such as the stitch designated as Type 301 in Federal Standard No. 751a (November 21, 1983).

4.14 LOT NUMBER – A marking assigned to each group of PFD's produced which incorporates a means for the user to identify the year and quarter of manufacture of the device (unless provided elsewhere). If a manufacturer produces PFDs at more than one factory, the lot number shall also provide a means of identifying the device as the product of a particular factory, although this information may be coded.

4.15 PERFORMANCE TYPE – The classification of the level and redundancy of assistance provided to the wearer based on the device's in-water flotation characteristics, number of compartments, and need for second stage donning as follows:

a) Type I devices have at least two flotation compartments, turn the largest percentage of participants face up, support the wearer's head such that the mouth is well clear of the water, and do not require second stage donning.

b) Type II devices have at least one flotation compartment, turn most test participants face up, support the wearer's head such that the mouth is well clear of the water, and do not require second stage donning.

c) Type III devices have at least one flotation compartment, turn many test participants face up, and support the wearer's head such that the mouth is well clear of the water, but may require second stage donning to achieve this in-water performance.

4.16 REFERENCE VEST – Stearns Manufacturing Company Model 1150, 30 – 52 inches (762 – 1321 mm) adult, inflatable PFD or equivalent. The vest utilizes a single 35 lbf (156.9 N) buoyancy chamber, built in sailing harness design with nylon chestbelt and shoulder harness, and a stainless steel front chest closure.

4.17 SECOND-STAGE DONNING – Additional donning or adjustment that is required to place the device in its functioning position from the position in which it is normally worn.

4.18 SERVICEABILITY – The ease with which the inflation system mechanism can be properly rearmed. Use Code 1F inflation systems have the most stringent serviceability requirements, with Use Code 2F and 3F systems having correspondingly less stringent requirements.

4.19 SERVICEABLE – Acceptable for continued use (e.g. exhibits no signs of functional deterioration such as deformation of hardware, a rip or tear, a loose seam, indicators not functional, oral inflation tube blocked or detached, manual inflator trigger detached, or the like).

4.20 STATUS INDICATOR – The part or parts of an inflation system which provide user feedback to assist in keeping an inflatable PFD in an armed and ready condition. Use Code 1F inflation systems have the most stringent status indicator user recognition requirements, with Use Code 2F and 3F systems having correspondingly less stringent requirements.

4.21 STRUCTURAL SEAM – A seam that serves a functional purpose, as distinguished from a decorative purpose.

4.22 TORSO ANGLE – The angle between a vertical line and a line passing through the shoulder and hip. A positive angle is achieved when a test participant's hips are forward with respect to their shoulders.

4.23 TURNING TIME – The time required for a device to turn a face-down wearer to a position in which the wearer's respiration is not impeded.

4.24 UNINFLATED – A device with the chamber(s) deflated and in the packed condition.

4.25 UNIVERSAL SIZE – A size of device constructed to fit, as a minimum, persons in the 5th through 95th percentile of the adult U.S. population, as reported by the National Center for Health Statistics, with respect to height and girth. The universal size includes the chest size range of 30 – 52 inches (80– 130 cm).

4.26 USCG APPROVAL TYPE – A classification assigned based on a device's performance, serviceability, and status indicators.

4.27 VEST – A device that covers the shoulders but has no sleeves. A yoke-style device is considered to be a vest.

4.28 WHITE WATER PADDLING – Any activity with a vessel on Class II and above rapids as determined by the six-class "International Scale of River Difficulty"^{4.28}. This definition applies only to those sections of the river with such rapids, and not the entire river.

* American Whitewater, PO Box 1540, Cullowhee, NC 28723; 1-866-BOAT-4-AW; <http://www.americanwhitewater.org/>; info@amwhitewater.org.

CONSTRUCTION

5 Inflatable Devices

5.1 The construction and assembly of an inflatable device shall be judged with respect to its intended use as well as the requirements in this standard.

6 Components and Materials

6.1 A component of a device covered by this standard shall:

- a) Comply with the requirements for the component in UL 1191; and
- b) Comply with any USCG requirements for the component.

6.2 Unless its function is such that failure of the component will not affect the ability of the device to meet the requirements of this standard, a nonmetallic component of an inflatable device which is permanently covered shall retain at least 60 percent of its as-received strength after being subjected to 100 hours of light and water exposure in accordance with Method I of ASTM G23-93, using apparatus designated Type E. The lower arcs are to be No. 15 copper clad carbon. The black panel temperature is to be $68 \pm 5^{\circ}\text{C}$ ($155 \pm 10^{\circ}\text{F}$) per Federal Standard 191A, Method 5804-90. The arcs are to be replaced and the corex D glass cleaned every 24 hours.

6.3 Unless its function is such that failure of the component will not affect the ability of the device to meet the requirements of this standard, a nonmetallic component of an inflatable device which may be exposed to sun light when in service shall retain at least 40 percent of its as-received strength after being subjected to 300 hours of light and water exposure in accordance with Method I of ASTM G23-93, using apparatus designated Type E as specified in [6.2](#).

6.4 Inflation chamber compartment material shall retain at least 90 percent of its strength and the rate of transmission of CO_2 gas through the material shall not be increased by more than ten percent after being subjected to the mildew resistance test specified in Federal Test Method, Standard 191, Method 5762-78, when untreated cotton is used as the control specimen.

6.5 Unless it is expendable, or if failure of the component will not affect the ability of the device to meet the requirements of this standard, a metallic component of an inflatable device shall have salt water and salt air corrosion characteristics equal or superior to 410 stainless steel, or perform its intended function and have no visible pitting or other damage on any surface after 720 hours of salt spray testing in accordance with ASTM B117-94.

Exception: An expendable component need not be of corrosion-resistant material, provided that the component is provided with a durable zinc or cadmium plating, or is equivalently protected against corrosion.

6.6 Metals shall be used in combinations that are galvanically compatible.

Exception: Where galvanic compatibility cannot be provided, an expendable component may be utilized as a sacrificial anode.

6.7 An exposed edge or projection of a component shall not be sufficiently sharp to damage the material of an inflatable compartment or constitute a risk of injury to persons during intended use. Referee measurements necessary to determine compliance with this requirement are to be those described in UL 1439.

6.8 Material used in the manufacture of a device shall be new.

7 Sizing and Arrangement

7.1 An inflatable device shall not be constructed for persons weighing less than 80 lbs (36 kg).

7.2 Type II and Type III performance inflatable devices shall be constructed to fit chest sizes over a marked range of at least 2 inches (51 mm). Type I performance devices shall be constructed to fit chest sizes over a marked range of at least the universal chest size range. In addition, all devices shall fit users having chest sizes 1.5 inches (38 mm) above and below the marked chest size range.

7.3 Hardware shall be arranged and attached to facilitate operation.

7.4 For devices which do not require second stage donning, oral and manual inflation systems shall be located and arranged to be operated by either hand of the wearer in a single deliberate action. Moving an unsecured flap, or the like, to gain access to the actuation means is not to be considered a deliberate action. For an oral inflation system, this requirement applies to the device in any intended condition of inflation, except the uninflated, packed condition. In this regard, the term "operated" refers only to the action of bringing the inflation tube to the mouth (not to the process of oral inflation). For devices which require second stage donning, manual inflation systems shall be located and arranged to be operated by either hand of the wearer in a single deliberate action with the device in the donned, packed condition, and oral and manual inflation systems shall be located and arranged to be operated by either hand of the wearer in a single deliberate action after second stage donning has been completed.

7.5 The construction and assembly of an inflatable device shall be designed to minimize the likelihood of inflation compartments, and other device components whose positioning within the device are critical to the performance of the device, from becoming bunched, knotted, tangled, dislocated, or otherwise rendered inoperative.

7.6 The construction and assembly of an inflatable device shall be designed to minimize the likelihood of inflation compartments being abraded or otherwise damaged by adjacent components such as the inflation system.

7.7 The arrangement of an inflatable device shall acceptably reduce the likelihood of snagging, such as by providing means to secure the free ends of body straps and the like.

8 Inflatable Compartments

8.1 A Type I performance device shall have at least two inflatable compartments.

8.2 Type II and Type III performance devices shall have at least one inflatable compartment.

9 Over-Pressure-Relief Valves

9.1 Over-pressure-relief valves may only be provided on one compartment of a multi-compartmented device. If provided, an over-pressure-relief valve shall be located and arranged to reduce the likelihood of the valve becoming blocked or otherwise rendered ineffective.

10 Inflation Systems

10.1 An inflatable device shall be provided with inflation systems in accordance with [10.2](#) – [10.7](#), as applicable.

10.2 A Type I performance device shall have a Use Code 1F automatic or manual-auto inflator on one compartment which shall be mounted such that its status indicator is viewable before and after donning the device. A second compartment shall have a Use Code 3F or 6F manual, or Use Code 1F, 2F, or 6F manual-auto inflator mounted so the status indicator(s) are accessible for checking prior to donning the device.

10.3 A Type II performance device shall have a Use Code 1F or 2F manual-auto inflator or both a Use Code 1F automatic inflator and a Use Code 3F or 6F manual inflator. The manual-auto inflator and automatic inflator shall be mounted on the PFD so the status indicator(s) can be viewed before and after donning the device. The manual inflator shall be mounted on the PFD so the indicator(s) can be easily accessed for checking prior to donning the device.

10.4 A Type III performance device shall have at least one Use Code 3F manual inflator or one Use Code 1F or 2F manual-auto inflator on one compartment which shall be mounted on the PFD such that its indicator(s) can be viewed before and after donning the device.

10.5 A Type V device shall use an inflation system that complies with the appropriate supplement to the standard, or the following .

a) For those Type V PFDs provided with at least one 6F manual or manual-automatic inflator, the cylinder shall be easily accessed for checking its status prior to donning the PFD. The devices shall be marked as Type V PFDs, APPROVED ONLY WHEN WORN and incorporate educational material into the Owners Manual, Think Safe pamphlet, and approval label on the risk of not checking the indicators and cylinder cap prior to each use; or

b) For those Type V PFDs provided with at least one non-convertible Use Code 6F manual-auto inflator, the cylinder shall be easily accessed for checking its status prior to donning the PFD. These devices shall be marked as Type V PFD, APPROVED ONLY WHEN WORN and meet the following requirements:

1) Incorporate educational material on the risk of premature inflation in the "THINK SAFE" pamphlet, and the "Owner's Manual" with the PFD.

2) Include a label that states DO NOT ALTER THIS PFD. Contact [insert Manufacturer and phone] for adjustment/replacement if dissatisfied with performance of the inflator".

10.6 All inflatable devices shall be provided with both an oral inflator and either an manual-auto or manual inflator for each compartment whose presence is required for the device to meet the in-water performance requirements of this standard.

Exception: Type I performance devices may be provided with only automatic and oral inflators on one compartment (see [10.2](#)).

10.7 Where a device has one or more redundant compartments which are not required to be inflated to achieve the in-water performance requirements, then the redundant compartment(s) may be fitted with an oral inflation system only. (For Type I performance devices this applies to compartments in excess of two.)

10.8 Inflation systems shall be located in a manner which permits servicing equivalent in ease to that performed in UL 1191.

10.9 Window material used as a non-load bearing component for viewing the indicator(s) of the inflation system, shall comply with the requirements of UL 1191, Window Material.

11 Deflation Systems

11.1 An inflatable compartment shall be provided with means to be deflated, which may be integral with or separate from any inflation system provided for the compartment. The deflation means shall be located and arranged to:

a) Be easily operated by either hand without the use of tools;

b) Reduce the likelihood of unintentional operation;

c) Self-seal after operation and permit reinflation of the compartment; and

d) Not be lockable in an open position.

12 Closure, Adjustment, and Attachment Means

12.1 An inflatable device shall incorporate strapping or other means of adjustment that provides a secure fit (as tight as possible without causing discomfort, or as tight a fit as is consistent with the intended use).

12.2 The cut ends of a body strap, tie tape, belt loop, or the like shall be turned under and stitched or the equivalent, to prevent raveling. Synthetic materials may be heat sealed in lieu of being turned under.

12.3 The free end of a body strap shall be provided with means to reduce the likelihood of unintentional disengagement from the hardware, such as a tab formed by box-x stitching two 1-1/2 inch (40 mm) turn-unders.

12.4 Body straps shall be permanently attached to the device using box-x stitching covering a minimum area of 0.3125 sq. inch per inch (7.9 sq. mm per mm) of webbing width or the equivalent, such as two bar-tack stitches bracketing the same minimum area and providing equal or greater strength. Equivalent performance is to be determined based on peel and shear strength test results.

12.5 Where body straps are held in their intended positions using belt loops or belt tunnels, the opening width of the loop or tunnel nearest the free end of the body strap shall not be more than 3/4 inch (19 mm) greater than the width of the body strap webbing, or shall be sized so as not to permit the unsecured end of the primary closure to pass through the opening.

Exception No. 1: Devices may have larger belt loop and belt tunnel openings provided they successfully meet the Use Characteristics Tests Sections 16 – 27 with the body straps free of the belt loops and/or tunnels.

Exception No. 2: This requirement does not apply to sliding belt loops provided to stow excess strap lengths while the device is worn.

12.6 The width of the opening in a closure such as a buckle or dee ring shall be not more than 1/8 inch (3 mm) greater than the width of the associated webbing, as measured at the line of contact.

12.7 Drawstrings shall be positively secured to the device using means other than a knot alone. Drawstrings shall also:

- a) Be not less than 1 inch (25 mm) wide; or
- b) Have a positive closing mechanism; or
- c) Comply with the tieability requirements for tie tapes as specified in UL 1191.

12.8 For devices where the inflatable chambers may be displaced if worn by users having a chest size greater than those for which the device is intended, body straps shall have no more than 3 inches (76 mm) of remaining adjustment when measured:

- a) On the largest test participant successfully tested in accordance with the Use Characteristics Tests in Sections 16 – 27; or
- b) With the device placed over a cylinder having an outer circumference equal to the maximum chest size for which the device is intended.

12.9 An inflatable device shall not provide means intended to fasten the device to a boat.

Exception No. 1: This requirement does not apply to harness assemblies, or the like, intended to be attached to harness lines during activities such as board-sailing or hiking out on a sailboat, and that have been investigated and found to be acceptable for the application.

Exception No. 2: This requirement does not apply to a means that is rendered inoperative when subjected to the Miscellaneous Fastener Strength Test, Section [33](#).

Exception No. 3: This requirement does not apply to a device provided with an owner's manual containing the text specified in [B15.4](#).

13 Seams and Stitching

13.1 A lock stitch shall be used for a structural seam formed by sewing. Also, see Seam Strength Test, Section [35](#).

13.2 Monofilament thread shall not be used for making structural seams.

13.3 Thread and fabric combinations shall be compatible.

13.4 A structural seam shall have at least 1/2 inch (12.7 mm) of seam allowance or have equivalent mechanical characteristics. The equivalency of the mechanical characteristics is to be determined by the Seam Breaking Strength Test – Overedge Stitch evaluation in UL 1123, except that the candidate stitch is to be compared to a 1/2 inch (12.7 mm), ssA-1 seam produced with size E thread meeting the requirements of Federal Standard V-T-295E(1985) or V-T-285F(1991), at 9 stitches per inch (.35 stitches/mm).

13.5 Window material attachments to the PFD shall have minimum seam strength (sewn or welded) of 53 N (12 pounds) for a 1-inch grip, in an as received condition, using the test method in Section [35](#), Seam Strength Test.

14 Buddy Line

14.1 A buddy line installed on a PFD shall comply with the requirements specified in [14.2](#), Section [44](#), Pull Test, and Section [55](#), Buddy Line Identification.

14.2 The buddy line shall be a minimum of 600 mm (24 inches) long and shall be attached so that risk of the buddy line snagging is reduced. Means of stowage shall be provided to secure the buddy line to the PFD, so that it is not a snag hazard.

PERFORMANCE

GENERAL

15 Selection and Preparation of Test Samples

15.1 Representative samples of an inflatable device shall be subjected to the applicable Use Characteristics Tests described in Sections [17](#) – [27](#), and the Physical Properties Test in Sections [28](#) – [31](#), [33](#), [36](#) – [41](#), and [43](#). Components or material specimens are to be used for the Physical Properties Tests specified in [32.1](#), Sections [34](#), [35](#), and [42](#).

15.2 A device having an optional or detachable feature, such as a harness assembly, which may adversely effect performance of the device shall be tested both with and without the optional or detachable feature in place.

15.3 For tests involving inflation of sample compartments to specific pressures, the inflation systems provided on the device may be modified to permit external pressurization, measurement of pressure, and the like.

15.4 If one or more compartments experience significant dimensional changes between the minimum and maximum pressure values of the design inflation range, the Use Characteristics Tests specified in Sections 22 – 27 are to be repeated with the inflation compartment(s) inflated to a sufficient number of buoyancy/pressure values within the design inflation range to demonstrate compliance with these requirements over the entire design pressure range.

USE CHARACTERISTICS TESTS

16 Test Participants

16.1 For the Use Characteristics Tests described in Section 17 – 27, human test participants as specified in Table 16.1 are to be employed. A test participant shall not be familiar with the particular device under test, but may be familiar with PFDs in general. Prior to testing, test participants are to be given a video orientation which covers the following topics:

- a) The general purpose of an inflatable PFD.
- b) General information regarding inflation medium containers.
- c) General demonstration of reference vest donning.
- d) The general principal and method of manual inflation.
- e) The general principal and method of automatic inflation.

Table 16.1
Test subject selection

Chest size adjustment range of device, inches (mm)	Number of test participants
6 (150) or less	6
More than 6 but not more than 12 (300)	12
More than 12 (300)	18

NOTES

1. Test participants selected are to be of varying height and weight so as to represent endomorphic, mesomorphic, and Ectomorphic anatomic builds. The chest sizes of the test participants are to be within the Intended chest size range of the device; except that one subject shall have a chest size 1 ± 0.5 inch (25 ± 13 mm) larger than the marked maximum size, and one test participant shall have a chest size 1 ± 0.5 inch smaller than the marked minimum size.
2. Test participants may be any combination of males and females, provided that at least one male and one female is used. Participants shall have basic swimming skills (e.g. be capable of treading water for 1 minute).
3. A youth test participant may be used to satisfy specific anthropomorphic characteristics for weight, chest size, or girth of an adult-size device. When testing an adult-size device, when the youth is less than 16 years of age, his or her test results may be excluded for the Ease of Donning, Adjustment and Operation Test, Section 17, Inflated Donning Test, Section 18, Ease of Use Test, Section 19, Post-Donning Ease of Adjustment Test, 20, In-Water Second-Stage Donning Test, Section 22, or Rearing and Repacking Test, Section 26, due to the participant's inherent limitations in dexterity, strength, and maturity. For an adult-size device, where the results for a youth test participant are excluded, a substitute test participant shall be used for the excluded test. The substitute participant shall have anthropomorphic characteristics within the candidate devices specified range, that are similar to, but not necessarily identical to the excluded participant.
4. A series of marked sized devices (for example, S,M,L,XL) utilizing the same inflation chamber is considered a single chest size adjustment range when the cover and closure materials differ proportionally over the chest size range. Test participant selection shall be such that each individual chest size range is represented proportionally and in accordance with Note 1.